

## SAFETY DATA SHEET

# SÜDWEST 2K-Acryllack- Verdünnung lang

|               |               |
|---------------|---------------|
| Ref.          | 130000006226/ |
| Rev. no.      | 1.2           |
| Revision Date | 27.03.2019    |
| Print Date    | 05.07.2019    |

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Trade name SÜDWEST 2K-Acryllack-Verdünnung lang

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Thinner, Diluent

Reserved for industrial and professional use.

Uses advised against

This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG  
Iggelheimer Str. 13  
D - 67459 Böhl-Iggelheim  
Telephone: +49 6324/709-0  
Telefax: +49 6324/709-175  
www.suedwest.de

E-mail address of person responsible for the SDS  
European Union

sdb@suedwest.de

#### 1.4 Emergency telephone number European Union

Phone: +44 (0)1235 239 670

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids,  
Category 3

H226: Flammable liquid and vapour.

# SÜDWEST 2K-Acryllack- Verdünnung lang

|  |  |
|--|--|
| Specific target organ toxicity<br>- single exposure, Category<br>3, Central nervous system | H336: May cause drowsiness or dizziness.               |
| Specific target organ toxicity<br>- single exposure, Category<br>3, Respiratory system     | H335: May cause respiratory irritation.                |
| Aspiration hazard, Category<br>1   | H304: May be fatal if swallowed and enters airways.    |
| Long-term (chronic) aquatic<br>hazard, Category 2  | H411: Toxic to aquatic life with long lasting effects. |

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



|                                |  |  |
|--------------------------------|--|--|
| Signal word                    | Danger   |  |
| Hazard statements              | H226<br>H304<br><br>H335<br>H336<br>H411       | Flammable liquid and vapour.<br>May be fatal if swallowed and enters airways.<br>May cause respiratory irritation.<br>May cause drowsiness or dizziness.<br>Toxic to aquatic life with long lasting effects. |
| Supplemental Hazard Statements | EUH066   | Repeated exposure may cause skin dryness or cracking.  |
| Precautionary statements       | <b>Prevention:</b><br>P210<br><br>P260<br>P280 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.<br>Do not breathe vapours.<br>Wear protective gloves/ protective clothing/ eye protection/ face protection.   |

# SÜDWEST 2K-Acryllack- Verdünnung lang

**Response:**

P301 + P310 IF SWALLOWED: Immediately call a  
POISON CENTER/doctor.  
P331 Do NOT induce vomiting.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off  
immediately all contaminated clothing.  
Rinse skin with water or shower.

**Disposal:**

P501 Contents/container to be disposed of  
through approved disposal contractor or  
taken to municipal collection point.

Hazardous components  
which must be listed on  
the label:

Hydrocarbons, C9, aromatics

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**3.2 Mixtures**

Chemical nature

Solvent mixture

## Components

| Chemical name                  | CAS-No.<br>EC-No.<br>Registration number       | Classification<br>(REGULATION (EC)<br>No 1272/2008)  | Concentration (%<br>w/w) |
|--------------------------------|--|--|--------------------------|
| n-butyl acetate                | 123-86-4<br>204-658-1<br>01-2119485493-29-XXXX | Flam. Liq.3; H226<br>STOT SE3; H336  | ≥ 50 - < 75              |
| Hydrocarbons, C9,<br>aromatics | 64742-95-6<br><br>01-2119455851-35-XXXX        | Asp. Tox.1; H304<br>Flam. Liq.3; H226<br>STOT SE3; H335,<br>H336<br>Aquatic Chronic2;<br>H411<br><br>Note H (Table 3.1),<br>Note P<br>The CAS number is no | ≥ 50 - < 75              |

# SÜDWEST 2K-Acryllack- Verdünnung lang

|  |  |  |  |
|--|--|--|--|
|  |  | longer specified in REACH registration, but still serves as identification in other areas. |  |
|--|--|--|--|

For explanation of abbreviations see section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

|                |  |
|----------------|--|
| General advice | When symptoms persist or in all cases of doubt seek medical advice.<br>Never give anything by mouth to an unconscious person.<br>If unconscious, place in recovery position and seek medical advice.   |
| Inhalation     | Move to fresh air in case of accidental inhalation of vapours or decomposition products.<br>Keep patient warm and at rest.<br>If breathing is irregular or stopped, administer artificial respiration.<br>If symptoms persist, call a physician. |
| Skin contact   | Take off contaminated clothing and shoes immediately.<br>Wash skin thoroughly with soap and water or use recognized skin cleanser.<br>Do NOT use solvents or thinners.<br>If skin irritation persists, call a physician.                         |
| Eye contact    | In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.<br>Seek medical advice.   |
| Ingestion      | Rinse mouth with water.<br>If swallowed, seek medical advice immediately and show this container or label.<br>Keep at rest.<br>Do NOT induce vomiting.   |

### 4.2 Most important symptoms and effects, both acute and delayed

|          |                           |
|----------|---------------------------|
| Symptoms | No information available. |
|----------|---------------------------|

### 4.3 Indication of any immediate medical attention and special treatment needed

|           |   |
|-----------|---|
| Treatment | Treat symptomatically.<br>No information available. |
|-----------|---|

# SÜDWEST 2K-Acryllack- Verdünnung lang

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Suitable extinguishing media      CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable extinguishing media      High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Fight fire with normal precautions from a reasonable distance.

### Additional advice

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.  
Ensure adequate ventilation.  
Do not breathe vapour.  
Prevent unauthorized access.

### 6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Clean with detergents. Avoid solvents.  
Clean contaminated surface thoroughly.  
Dispose of contaminated material as waste according to item 13.

### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

# SÜDWEST 2K-Acryllack- Verdünnung lang

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

|                         |  |
|-------------------------|--|
| Advice on safe handling | <p>Comply with the statutory regulations on health and safety at work.</p> <p>Avoid formation of aerosol.</p> <p>Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values.</p> <p>The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.</p> <p>All metal parts of the mixing and processing equipment must be earthed.</p> <p>Operators should wear antistatic footwear and clothing. No sparking tools should be used.</p> |
| Hygiene measures        | <p>Do not breathe spray, vapour.</p> <p>Take off immediately all contaminated clothing.</p> <p>Avoid contact with skin, eyes and clothing.</p> <p>Wash hands before breaks and immediately after handling the product.</p> <p>After washing hands, replenish lost skin oil by means of oily skin ointment.</p> <p>When using do not eat, drink or smoke.</p>   |

### 7.2 Conditions for safe storage, including any incompatibilities

|   |  |
|---|--|
| Requirements for storage areas and containers   | <p>Store in original container.</p> <p>Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nosmoking.</p> <p>Prevent unauthorized access.</p> <p>Containers which are opened must be carefully resealed and kept upright to prevent leakage.</p> <p>Keep in a well-ventilated place.</p> <p>Protect from frost, heat and sunlight.</p> |
| Advice on protection against fire and explosion | <p>Vapours are heavier than air and may spread along floors.</p> <p>Vapours may form explosive mixtures with air.</p> <p>Keep away from sources of ignition - No smoking.</p> <p>Take measures to prevent the build up of electrostatic charge.</p>  |
| Advice on common                                | <p>Keep away from combustible materials.</p>   |

# SÜDWEST 2K-Acryllack- Verdünnung lang

storage Keep away from food, drink and animal feedingstuffs.  
Keep away from oxidizing agents and strongly acid or alkaline materials.

**7.3 Specific end use(s)** For further information, see also Technical Data Sheet for the product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

Contains no substances with occupational exposure limit values. The lists that were valid during the creation were used as basis.

### 8.2 Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn. Washing facilities / water for rinsing eyes and skin should be available.

#### Individual protection measures, such as personal protective equipment

a) Eye/face protection Safety glasses with side-shields conforming to EN166

b) Skin protection  
Hand protection

Recommended preventive skin protection  
Before starting work, apply water-resistant skincare preparations to exposed skin areas.  
Protective gloves should be worn in case of skin contact during preparation and application.

Break through time: 480 min  
Minimum thickness: 0,4 mm  
Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent.  
Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard

# SÜDWEST 2K-Acryllack- Verdünnung lang

EN 374 derived from it.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

## Body Protection

Preventive skin protection  
Long sleeved clothing  
Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthehic fiber. All parts of the body should be washed after contact.

## c) Respiratory protection

When workers are facing concentrations above the occupational exposure limit values they must use appropriate certified respirators.  
Breathing protection equipment required in inadequately ventilated places and during spraying.  
In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.  
Combination filter A-P2  
Respiratory protection complying with EN 14387.

## Environmental exposure controls

### General advice

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

|   |                   |
|---|-------------------|
| Appearance                              | liquid            |
| Colour                                  | colourless        |
| Odour                                   | characteristic    |
| Odour Threshold                         | No data available |
| pH                                      | Not applicable    |
| Melting point/freezing point            | No data available |
| Initial boiling point and boiling range | ca. 128 - 185 °C  |
| Flash point                             | ca. 29 °C         |



# SÜDWEST 2K-Acryllack- Verdünnung lang

Method: DIN 51755 Part 1

|   |  |
|---|--|
| Evaporation rate                                    | not applicable   |
| Flammability (solid, gas)                           | not applicable   |
| Upper explosion limit /<br>Upper flammability limit | 10,5 %(V)<br>Upper explosion limit                                       |
| Lower explosion limit /<br>Lower flammability limit | 1,0 %(V)<br>Lower explosion limit  |
| Vapour pressure                                     | No data available  |
| Density   | ca. 0,876 g/cm <sup>3</sup> (20 °C)                                      |
| Solubility(ies)<br>Water solubility                 | 5,0 g/l (20 °C)  |
| Partition coefficient: n-<br>octanol/water          | not determined   |
| Auto-ignition temperature                           | not auto-flammable   |
| Decomposition<br>temperature                        | No data available  |
| Viscosity<br>Viscosity, dynamic                     | No data available  |
| Explosive properties                                | Not explosive<br>In use may form flammable/explosive vapour-air mixture. |
| Oxidizing properties                                | Not applicable   |

## 9.2 Other information

|                      |                   |
|----------------------|-------------------|
| Ignition temperature | 420 °C            |
| Flow time            | No data available |

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

# SÜDWEST 2K-Acryllack- Verdünnung lang

Stable under normal conditions.

## 10.3 Possibility of hazardous reactions

Hazardous reactions                      No dangerous reaction known under conditions of normal use.  
Vapours may form explosive mixture with air.

## 10.4 Conditions to avoid

Conditions to avoid                      Direct sources of heat.  
Strong sunlight for prolonged periods.

## 10.5 Incompatible materials

Materials to avoid                      Strong acids and strong bases  
Strong oxidizing agents

## 10.6 Hazardous decomposition products

Hazardous decomposition products      No decomposition if stored and applied as directed.  
Decomposition temperature              No data available

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on toxicological effects

#### Acute toxicity

##### Product:

Acute oral toxicity                      Based on available data, the classification criteria are not met.

Acute inhalation toxicity                Based on available data, the classification criteria are not met.

Acute dermal toxicity                    Based on available data, the classification criteria are not met.

#### Skin corrosion/irritation

##### Product:

Repeated exposure may cause skin dryness or cracking.

##### Components:

##### n-butyl acetate:

Repeated exposure may cause skin dryness or cracking.

##### Hydrocarbons, C9, aromatics:

Repeated exposure may cause skin dryness or cracking.

# SÜDWEST 2K-Acryllack- Verdünnung lang

**Serious eye damage/eye irritation****Product:**

Based on available data, the classification criteria are not met.

**Respiratory or skin sensitisation****Product:**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

**Carcinogenicity****Product:**

Based on available data, the classification criteria are not met.

**Reproductive toxicity****Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

**STOT - single exposure****Product:**

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

**Components:****n-butyl acetate:**

Exposure routes

inhalation (vapour)

Assessment

May cause drowsiness or dizziness.

**Hydrocarbons, C9, aromatics:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

**STOT - repeated exposure****Product:**

Based on available data, the classification criteria are not met.

# SÜDWEST 2K-Acryllack- Verdünnung lang

## Aspiration toxicity

### Product:

May be fatal if swallowed and enters airways.

### Components:

#### **Hydrocarbons, C9, aromatics:**

May be fatal if swallowed and enters airways.

## Experience with human exposure

### Product:

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness. Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

## Further information

### Product:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### Product:

Toxicity to fish

No data available

#### Components:

##### **Hydrocarbons, C9, aromatics :**

Toxicity to fish

LC50 (Oncorhynchus mykiss (rainbow trout)): 9,22 mg/l  
Exposure time: 96 h

# SÜDWEST 2K-Acryllack- Verdünnung lang

Toxicity to daphnia and other aquatic invertebrates      EC50 (Daphnia magna (Water flea)): 6,14 mg/l  
Exposure time: 48 h

## 12.2 Persistence and degradability

### Product:

Biodegradability      No data available

### Components:

#### **n-butyl acetate :**

Biodegradability      Result: rapidly degradable  
Biodegradation: > 90 %  
Exposure time: 28 d

#### **Hydrocarbons, C9, aromatics :**

Biodegradability      Result: rapidly degradable

## 12.3 Bioaccumulative potential

### Product:

Bioaccumulation      No data available

### Components:

#### **n-butyl acetate :**

Partition coefficient: n-octanol/water      log Pow: 2,3Method: OECD Test Guideline 117

## 12.4 Mobility in soil

### Product:

Mobility      No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment      This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Other adverse effects

### Product:

Additional ecological information      Do not allow product to enter into ground water, bodies of water or sewage systems. Harmful to aquatic life with long lasting effects.

# SÜDWEST 2K-Acryllack- Verdünnung lang

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

|                                  |  |
|----------------------------------|--|
| Product                          | <p>The user is responsible for proper coding and marking of any waste.</p> <p>When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste"</p> <p>Partial and residual quantities can be reused.</p> <p>Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.</p> |
| Contaminated packaging           | <p>Packaging that is not properly emptied must be disposed of as the unused product.</p> <p>Empty packaging should be recycled through disposal systems.</p>   |
| Waste key for the unused product | <p>07 01 04* other organic solvents, washing liquids and mother liquors</p> <p>(* ) hazardous waste in terms of the European directive 2008/98/EG</p>  |

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number

|      |      |
|------|------|
| ADR  | 1993 |
| IMDG | 1993 |
| IATA | 1993 |

### 14.2 UN proper shipping name

|      |   |
|------|---|
| ADR  | FLAMMABLE LIQUID, N.O.S.<br><br>(butyl acetates, Hydrocarbons, C9, aromatics) |
| IMDG | FLAMMABLE LIQUID, N.O.S.  |

# SÜDWEST 2K-Acryllack- Verdünnung lang

(butyl acetates, Hydrocarbons, C9, aromatics)

**IATA** Flammable liquid, n.o.s.

(butyl acetates, Hydrocarbons, C9, aromatics)

## 14.3 Transport hazard class(es)

**ADR** 3

**IMDG** 3

**IATA** 3

## 14.4 Packing group

### ADR

Packing group III

Classification Code F1

Hazard Identification  
Number 30

Labels 3

Tunnel restriction code (D/E)

### IMDG

Packaging group III

Labels 3

EmS number F-E, S-E

### IATA

Packaging group III

Labels 3

## 14.5 Environmental hazards

### ADR

Environmentally hazardous yes

### IMDG

# SÜDWEST 2K-Acryllack- Verdünnung lang

Marine pollutant                      yes

## 14.6 Special precautions for user

Remarks                                      This information is not available.

## 14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks                                      Not applicable

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC  
Directive 2010/75/EU                      100 %

VOC  
Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Other regulations                              Comply with the statutory regulations on health and safety at work.

Take note of Dir 94/33/EC on the protection of young people at work.

Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

### 15.2 Chemical safety assessment

This information is not available.



# SÜDWEST 2K-Acryllack- Verdünnung lang

## SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin.

The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

### Full text of H-Statements

|      |  |
|------|--|
| H226 | : Flammable liquid and vapour.                     |
| H304 | : May be fatal if swallowed and enters airways.    |
| H335 | : May cause respiratory irritation.                |
| H336 | : May cause drowsiness or dizziness.               |
| H411 | : Toxic to aquatic life with long lasting effects. |

### Full text of other abbreviations

|                 |  |
|-----------------|--|
| Aquatic Chronic | : Long-term (chronic) aquatic hazard               |
| Asp. Tox.       | : Aspiration hazard                                |
| Flam. Liq.      | : Flammable liquids                                |
| STOT SE         | : Specific target organ toxicity - single exposure |

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic

# SÜDWEST 2K-Acryllack- Verdünnung lang

Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## Further information

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing  
MSDS  
REG\_EU / EN

sdb@suedwest.de

# **SÜDWEST 2K-Acryllack- Verdünnung lang**