

SAFETY DATA SHEET

SÜDWEST IsolierSpray

Ref.	130000006276/
Rev. no.	1.3
Revision Date	11.09.2018
Print Date	05.07.2019

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name SÜDWEST IsolierSpray

1.2 Relevant identified uses of the substance or mixture and uses advised against

Coating compound/ Surface coating/ paint

Uses advised against This information is not available.

1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG
Iggelheimer Str. 13
D - 67459 Böhl-Iggelheim
Telephone: +49 6324/709-0
Telefax: +49 6324/709-175
www.suedwest.de

E-mail address of person responsible for the SDS
European Union sdb@suedwest.de

1.4 Emergency telephone number
European Union

Phone: +44 (0)1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Aerosols, Category 1

H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

SÜDWEST IsolierSpray

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word	Danger	
Hazard statements	H222	Extremely flammable aerosol.
	H229	Pressurised container: May burst if heated.
	H412	Harmful to aquatic life with long lasting effects.
Precautionary statements	P101	If medical advice is needed, have product container or label at hand.
	P102	Keep out of reach of children.
	Prevention:	
	P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
	P211	Do not spray on an open flame or other ignition source.
	P251	Do not pierce or burn, even after use.
	P260	Do not breathe spray.
	Storage:	
P410 + P412	Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.	
Disposal:		
P501	Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.	

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

SÜDWEST IsolierSpray**3.2 Mixtures**

Chemical nature

Lacquer-type paint.

Spraying

Hazardous components

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
dimethyl ether	115-10-6 204-065-8 01-2119472128-37-XXXX	Flam. Gas1; H220 Press. GasH280	≥ 20 - ≤ 25
propane	74-98-6 200-827-9 01-2119486944-21-XXXX	Flam. Gas1; H220 Press. GasH280 Note U (Table 3)	≥ 5 - ≤ 10
butane (containing < 0.1% butadiene (203-450-8))	106-97-8 203-448-7 01-2119474691-32-XXXX	Flam. Gas1; H220 Press. GasH280 Note U (Table 3), Note C	≥ 5 - ≤ 10
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0 01-2119475514-35-XXXX	Flam. Liq.2; H226 Aquatic Chronic2; H411 STOT SE3; H336 Asp. Tox.1; H304 Skin Irrit.2; H315 The CAS number is no longer specified in REACH registration, but still serves as identification in other areas.	≥ 5 - ≤ 10
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	90622-57-4 01-2119472146-39-XXXX	Flam. Liq.3; H226 Aquatic Chronic4; H413 Asp. Tox.1; H304 The CAS number is no longer specified in REACH registration, but still serves as identification in other	≥ 2,5 - < 5

SÜDWEST IsolierSpray

isobutane	75-28-5 200-857-2 01-2119485395-27-XXXX	areas. Flam. Gas1; H220 Press. GasH280 Note C	≤ 2,5
2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine	222417-26-7	Skin Irrit.2; H315 Eye Dam.1; H318 Aquatic Chronic1; H410 Aquatic Acute1; H400	≤ 0,5
Substances with a workplace exposure limit :			
(2-methoxymethylethoxy) propanol	34590-94-8 252-104-2 01-2119450011-60-XXXX	WEL substance, Not a dangerous substance according to GHS.	< 2,5

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice	When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Rinse mouth with water. If swallowed, seek medical advice immediately and show

SÜDWEST IsolierSpray

this container or label.
Keep at rest.
Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.
No information available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable extinguishing media High volume water jet

5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:
Carbon monoxide
Carbon dioxide (CO₂)
Nitrogen oxides (NO_x)
Exposure to decomposition products may be a hazard to health.
Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Fight fire with normal precautions from a reasonable distance.

Additional advice

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.
Ensure adequate ventilation.
Do not breathe vapour.
Prevent unauthorized access.

6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth,

SÜDWEST IsolierSpray

containment and cleaning up

vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Clean with detergents. Avoid solvents.
Clean contaminated surface thoroughly.
Do not flush with water or aqueous cleansing agents
Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

Advice on safe handling

Comply with the statutory regulations on health and safety at work.
Avoid formation of aerosol.
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values.
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
All metal parts of the mixing and processing equipment must be earthed.
Operators should wear antistatic footwear and clothing. No sparking tools should be used.

Hygiene measures

Do not breathe spray, vapour.
Take off immediately all contaminated clothing.
Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
After washing hands, replenish lost skin oil by means of oily skin ointment.
When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container.
Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nosmoking.
Prevent unauthorized access.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Protect from frost, heat and sunlight.

SÜDWEST IsolierSpray

Do not keep container sealed.

Advice on protection
against fire and
explosion

Vapours are heavier than air and may spread along floors.
Vapours may form explosive mixtures with air.
Keep away from sources of ignition - No smoking.
Take measures to prevent the build up of electrostatic
charge.

Advice on common
storage

Keep away from combustible materials.
Keep away from food, drink and animal feedingstuffs.
Keep away from oxidizing agents and strongly acid or
alkaline materials.

7.3 Specific end use(s)

For further information, see also Technical Data Sheet for
the product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

dimethyl ether		115-10-6
2000/39/EC	Limit Value - eight hours	1.920 mg/m ³
2000/39/EC	Limit Value - eight hours	1.000 ppm
Additional advice:	Indicative	
(2-methoxymethylethoxy) propanol		34590-94-8
2000/39/EC	Limit Value - eight hours	308 mg/m ³
2000/39/EC	Limit Value - eight hours	50 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	

The lists that were valid during the creation were used as basis.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn. Washing facilities / water for rinsing eyes and skin should be available.

Individual protection measures, such as personal protective equipment

- a) Eye/face protection Safety glasses with side-shields conforming to EN166
- b) Skin protection
Hand protection Break through time: 60 min

SÜDWEST IsolierSpray

Minimum thickness: 0,7 mm
e.g. KCL 898 "Butoject®" - butyl rubber protective glove -
(Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300,
kcl-uk@kcl.de) or equal.

Dispose of wetted gloves at the end of the shift!

Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.

The selected protective gloves have to satisfy the specifications of EU Directive 89/686/EEC and the standard EN 374 derived from it.

The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Body Protection

Preventive skin protection
Long sleeved clothing
Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

c) Respiratory protection

When workers are facing concentrations above the occupational exposure limit values they must use appropriate certified respirators.
Breathing protection equipment required in inadequately ventilated places and during spraying.
In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.
Combination filter A-P2
Respiratory protection complying with EN 14387.

Environmental exposure controls

General advice

The product should not be allowed to enter drains, water courses or the soil.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance aerosol

Colour various

SÜDWEST IsolierSpray

Odour	characteristic
Odour Threshold	not determined
pH	No data available
Melting point/freezing point	not determined
Initial boiling point and boiling range	Not applicable
Flash point	Not applicable, as aerosol.
Evaporation rate	Not applicable
Flammability (solid, gas)	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	18,6 %(V) Upper explosion limit
Lower explosion limit / Lower flammability limit	3,0 %(V) Lower explosion limit
Vapour pressure	5.200 hPa (20 °C)
Vapour density	No data available
Density	ca. 1,12 g/cm ³ (20 °C)
Solubility(ies) Water solubility	immiscible
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity Viscosity, dynamic	No data available
Explosive properties	In use may form flammable/explosive vapour-air mixture.
Oxidizing properties	Not applicable

9.2 Other information

Ignition temperature	235 °C
----------------------	--------

SÜDWEST IsolierSpray

Flow time No data available

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid No dangerous reaction known under conditions of normal use.
danger of bursting and explosion by pressure increase

10.5 Incompatible materials

Materials to avoid Strong acids and strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

Hazardous decomposition products No decomposition if stored and applied as directed.
Decomposition temperature No data available

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on toxicological effects

Acute toxicity

Product:

Acute oral toxicity Based on available data, the classification criteria are not met.

Acute inhalation toxicity Based on available data, the classification criteria are not met.

Acute dermal toxicity Based on available data, the classification criteria are not met.

SÜDWEST IsolierSpray

Skin corrosion/irritation

Product:

Based on available data, the classification criteria are not met.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Causes skin irritation.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

Repeated exposure may cause skin dryness or cracking.

2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine:

Species

Rabbit

Method

OECD Test Guideline 404

Causes skin irritation.

Serious eye damage/eye irritation

Product:

Based on available data, the classification criteria are not met.

Components:

2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine:

Species

Rabbit

Method

OECD Test Guideline 405

Causes serious eye damage.

Respiratory or skin sensitisation

Product:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Effects on fertility

Based on available data, the classification criteria are

SÜDWEST IsolierSpray

not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Based on available data, the classification criteria are not met.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

Assessment

May cause drowsiness or dizziness.

STOT - repeated exposure

Product:

Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:

May be fatal if swallowed and enters airways.

Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:

May be fatal if swallowed and enters airways.

Experience with human exposure

Product:

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.
Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness. Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

Further information

Product:

SÜDWEST IsolierSpray

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

SECTION 12: ECOLOGICAL INFORMATION**12.1 Toxicity****Product:**

Toxicity to fish	Harmful to fish.
------------------	------------------

Components:

2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine :

Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 0,89 mg/l Exposure time: 96 h Test Type: static test Method: OECD Test Guideline 202
------------------	---

M-Factor (Short-term (acute) aquatic hazard)	1
---	---

12.2 Persistence and degradability**Product:**

Biodegradability	No data available
------------------	-------------------

Components:

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane :

Biodegradability	Result: rapidly degradable
------------------	----------------------------

2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine :

Biodegradability	Result: not rapidly degradable Method: OECD Test Guideline 301B
------------------	--

(2-methoxymethylethoxy) propanol :

Biodegradability	Biodegradation: 75 % Exposure time: 28 d Method: OECD Test Guideline 301 rapidly biodegradable
------------------	---

12.3 Bioaccumulative potential**Product:**

Bioaccumulation	No data available
-----------------	-------------------

SÜDWEST IsolierSpray

Components:

dimethyl ether :

Partition coefficient: n-octanol/water log Pow: 0,1

propane :

Partition coefficient: n-octanol/water log Pow: 2,36

isobutane :

Partition coefficient: n-octanol/water log Pow: 2,76

(2-methoxymethylethoxy) propanol :

Partition coefficient: n-octanol/water log Pow: -0,35

12.4 Mobility in soil

Product:

Mobility No data available

12.5 Results of PBT and vPvB assessment

Product:

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

12.6 Other adverse effects

Product:

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems. Harmful to aquatic life with long lasting effects.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product The user is responsible for proper coding and marking of any waste.
When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste"

SÜDWEST IsolierSpray



Partial and residual quantities can be reused.
Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.

Contaminated packaging

Packaging that is not properly emptied must be disposed of as the unused product.
Empty packaging should be recycled through disposal systems.

Waste key for the unused product

08 01 11* Paint and varnish waste containing organic solvents or other dangerous substances

(*) hazardous waste in terms of the European directive 91/689/EEC

SECTION 14: TRANSPORT INFORMATION

14.1 UN number

ADR 1950

IMDG 1950

IATA 1950

14.2 UN proper shipping name

ADR AEROSOLS

IMDG AEROSOLS

IATA Aerosols, flammable

14.3 Transport hazard class(es)

ADR 2.1

IMDG 2.1

IATA 2.1

14.4 Packing group

ADR

Packing group Not Assigned

Classification Code 5F

SÜDWEST IsolierSpray

Labels 2.1

Tunnel restriction code (D)

IMDG

Labels 2.1

EmS number F-D, S-U

IATA

Labels 2.1

14.5 Environmental hazards

ADR

Environmentally hazardous no

IMDG

Marine pollutant no

14.6 Special precautions for user

Remarks This information is not available.

14.7 Transport in bulk according to Annex II of Marpol and the IBC Code

Remarks Not applicable

Additional advice

ADR ADR: Up to 1 l per inner package, transport as limited quantity in accordance with ADR 3.4.

IMDG IMDG: Up to 1 l per inner package, transport as limited quantity in accordance with IMDG Code 3.4.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC

SÜDWEST IsolierSpray

Directive 2010/75/EU 57,93 %
648,8 g/l

VOC
Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals Not applicable

Other regulations Comply with the statutory regulations on health and safety at work.
Take note of Dir 94/33/EC on the protection of young people at work.
Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin.

The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

Full text of H-Statements

H220 : Extremely flammable gas.
H226 : Flammable liquid and vapour.
H280 : Contains gas under pressure; may explode if heated.
H304 : May be fatal if swallowed and enters airways.

SÜDWEST IsolierSpray

H315	: Causes skin irritation.
H318	: Causes serious eye damage.
H336	: May cause drowsiness or dizziness.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.
H413	: May cause long lasting harmful effects to aquatic life.

Full text of other abbreviations

Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Dam.	: Serious eye damage
Flam. Gas	: Flammable gases
Flam. Liq.	: Flammable liquids
Press. Gas	: Gases under pressure
Skin Irrit.	: Skin irritation
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic

SÜDWEST IsolierSpray

Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing
MSDS
REG_EU / EN

sdb@suedwest.de

SÜDWEST IsolierSpray