



**SÜDWEST Holz-Öl****2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms



Signal word

Danger

Hazard statements

H226  
H304Flammable liquid and vapour.  
May be fatal if swallowed and enters  
airways.Supplemental Hazard  
Statements

EUH066

Repeated exposure may cause skin  
dryness or cracking.Precautionary  
statements

P102

Keep out of reach of children.

**Prevention:**

P210

Keep away from heat, hot surfaces,  
sparks, open flames and other ignition  
sources. No smoking.**Response:**P303 + P361 + P353 IF ON SKIN (or hair): Take off  
immediately all contaminated clothing.  
Rinse skin with water or shower.

P301 + P310

IF SWALLOWED: Immediately call a  
POISON CENTER/doctor.

P331

Do NOT induce vomiting.

**Storage:**

P405

Store locked up.

**Disposal:**

P501

Contents/container to be disposed of  
through approved disposal contractor or  
taken to municipal collection point.Hazardous components  
which must be listed on  
the label:Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics,  
<2% aromatics**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

**SÜDWEST Holz-Öl****SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2 Mixtures****Hazardous components**

Chemical name	CAS-No. EC-No. Registration number	Classification (REGULATION (EC) No 1272/2008)	Concentration (% w/w)
Hydrocarbons, C10- C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9  01-2119457273-39- XXXX	Asp. Tox.1; H304  The CAS number is no longer specified in REACH registration, but still serves as identification in other areas.	≥ 50 - < 75
Substances with a workplace exposure limit :			
(2- methoxymethylethoxy ) propanol	34590-94-8 252-104-2 01-2119450011-60- XXXX	WEL substance, Not a dangerous substance according to GHS.	≥ 3 - < 5

For explanation of abbreviations see section 16.

**SECTION 4: FIRST AID MEASURES****4.1 Description of first aid measures**

General advice	When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for

# SÜDWEST Holz-Öl

at least 15 minutes.  
Seek medical advice.

Ingestion  
Rinse mouth with water.  
If swallowed, seek medical advice immediately and show this container or label.  
Keep at rest.  
Do NOT induce vomiting.

## 4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

## 4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.  
No information available.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Suitable extinguishing media CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable extinguishing media High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.

### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus. Fight fire with normal precautions from a reasonable distance.

Additional advice

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.  
Ensure adequate ventilation.  
Do not breathe vapour.  
Prevent unauthorized access.

### 6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.

# SÜDWEST Holz-Öl

If the product contaminates rivers and lakes or drains inform respective authorities.

## 6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Clean with detergents. Avoid solvents.  
Clean contaminated surface thoroughly.  
Dispose of contaminated material as waste according to item 13.

## 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

#### Advice on safe handling

Comply with the statutory regulations on health and safety at work.  
Avoid formation of aerosol.  
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
All metal parts of the mixing and processing equipment must be earthed.  
Operators should wear antistatic footwear and clothing. No sparking tools should be used.  
Risk of self-combustion from drying oils on used towels/rags.

#### Hygiene measures

Do not breathe spray, vapour.  
Take off immediately all contaminated clothing.  
Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
After washing hands, replenish lost skin oil by means of oily skin ointment.  
When using do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for

Store in original container.

**SÜDWEST Holz-Öl**

storage areas and containers	Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nosmoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a well-ventilated place. Protect from frost, heat and sunlight.
Advice on protection against fire and explosion	Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.
Advice on common storage	Keep away from combustible materials. Keep away from food, drink and animal feedingstuffs. Keep away from oxidizing agents and strongly acid or alkaline materials.
<b>7.3 Specific end use(s)</b>	For further information, see also Technical Data Sheet for the product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters****Exposure limit(s)**

Components		CAS-No.
Basis	Type:	Control parameters
(2-methoxymethylethoxy) propanol		34590-94-8
2000/39/EC	Limit Value - eight hours	308 mg/m <sup>3</sup>
2000/39/EC	Limit Value - eight hours	50 ppm
Additional advice:		Identifies the possibility of significant uptake through the skin Indicative

The lists that were valid during the creation were used as basis.

**8.2 Exposure controls****Appropriate engineering controls**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn. Washing facilities / water for rinsing eyes and skin should be available.

**Individual protection measures, such as personal protective equipment**

# SÜDWEST Holz-Öl

a) Eye/face protection Safety glasses with side-shields conforming to EN166

b) Skin protection  
Hand protection

Recommended preventive skin protection  
Before starting work, apply water-resistant skincare preparations to exposed skin areas.  
Protective gloves should be worn in case of skin contact during preparation and application.

Break through time: 480 min  
Minimum thickness: 0,4 mm  
Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent.  
Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.  
The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Body Protection

Preventive skin protection  
Long sleeved clothing  
Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

c) Respiratory protection

When workers are facing concentrations above the occupational exposure limit values they must use appropriate certified respirators.  
Breathing protection equipment required in inadequately ventilated places and during spraying.  
In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.  
Combination filter A-P2  
Respiratory protection complying with EN 14387.

## Environmental exposure controls

General advice

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**SÜDWEST Holz-Öl****SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

Appearance	liquid
Colour	colourless
Odour	characteristic
Odour Threshold	No data available
pH	No data available
Melting point/freezing point	No data available
Initial boiling point and boiling range	ca. 185 °C
Flash point	60 °C Method: closed cup
Evaporation rate	not applicable
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	10,4 %(V) Upper explosion limit
Lower explosion limit / Lower flammability limit	0,6 %(V) Lower explosion limit
Vapour pressure	0,7 hPa (20 °C)
Vapour density	No data available
Density	ca. 0,85 g/cm <sup>3</sup> (20 °C)
Solubility(ies) Water solubility	No data available
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available



# SÜDWEST Holz-Öl

Viscosity	
Viscosity, dynamic	No data available
Explosive properties	Not explosive In use may form flammable/explosive vapour-air mixture.
Oxidizing properties	Not applicable

## 9.2 Other information

Flow time	ca. 13 - 15 s Cross section: 4 mm
-----------	--------------------------------------

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	No dangerous reaction known under conditions of normal use. Vapours may form explosive mixture with air.
---------------------	---

### 10.4 Conditions to avoid

Conditions to avoid	Direct sources of heat. Strong sunlight for prolonged periods.
---------------------	---

### 10.5 Incompatible materials

Materials to avoid	Strong acids and strong bases Strong oxidizing agents
--------------------	--

### 10.6 Hazardous decomposition products

Hazardous decomposition products	No decomposition if stored and applied as directed.
Decomposition temperature	No data available

## SECTION 11: TOXICOLOGICAL INFORMATION

# SÜDWEST Holz-Öl

## 11.1 Information on toxicological effects

### Acute toxicity

#### Product:

Acute oral toxicity                      Based on available data, the classification criteria are not met.

Acute inhalation toxicity              Based on available data, the classification criteria are not met.

Acute dermal toxicity                    Based on available data, the classification criteria are not met.

### Skin corrosion/irritation

#### Product:

Repeated exposure may cause skin dryness or cracking.

### Components:

#### **Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Repeated exposure may cause skin dryness or cracking.

### Serious eye damage/eye irritation

#### Product:

Based on available data, the classification criteria are not met.

### Respiratory or skin sensitisation

#### Product:

Based on available data, the classification criteria are not met.

### Germ cell mutagenicity

#### Product:

Genotoxicity in vitro                    Based on available data, the classification criteria are not met.

### Carcinogenicity

#### Product:

Based on available data, the classification criteria are not met.

### Reproductive toxicity

#### Product:

Effects on fertility                        Based on available data, the classification criteria are not met.

Developmental Toxicity                Based on available data, the classification criteria are not met.

### STOT - single exposure

#### Product:

Based on available data, the classification criteria are not met.

# SÜDWEST Holz-Öl

## STOT - repeated exposure

### Product:

Based on available data, the classification criteria are not met.

## Aspiration toxicity

### Product:

May be fatal if swallowed and enters airways.

## Components:

**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

May be fatal if swallowed and enters airways.

## Experience with human exposure

### Product:

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness. Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

## Further information

### Product:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### Product:

Toxicity to fish

No data available

### 12.2 Persistence and degradability

#### Product:

# SÜDWEST Holz-Öl

Biodegradability No data available

**Components:****(2-methoxymethylethoxy) propanol :**

Biodegradability Biodegradation: 75 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301  
rapidly biodegradable

## 12.3 Bioaccumulative potential

**Product:**

Bioaccumulation No data available

**Components:****(2-methoxymethylethoxy) propanol :**

Partition coefficient: n- log Pow: -0,35  
octanol/water

## 12.4 Mobility in soil

**Product:**

Mobility No data available

## 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

## 12.6 Other adverse effects

**Product:**

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Product The user is responsible for proper coding and marking of any waste.  
When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste"  
Partial and residual quantities can be reused.  
Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a



**SÜDWEST Holz-Öl**

Labels 3  
Tunnel restriction code (D/E)

**IMDG**

Packaging group III  
Labels 3  
EmS number F-E, S-E

**IATA**

Packaging group III  
Labels 3

**14.5 Environmental hazards****ADR**

Environmentally hazardous no

**IMDG**

Marine pollutant no

**14.6 Special precautions for user**

Remarks This information is not available.

**14.7 Transport in bulk according to Annex II of Marpol and the IBC Code**

Remarks Not applicable

**Additional advice**

ADR ADR: Up to 5 l per inner package, transport as limited quantity in accordance with ADR 3.4.  
IMDG IMDG: Up to 5 l per inner package, transport as limited quantity in accordance with IMDG Code 3.4.

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

# SÜDWEST Holz-Öl

VOC  
Directive 2010/75/EU 64,7 %

VOC  
Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals Not applicable

Other regulations Comply with the statutory regulations on health and safety at work.  
Take note of Dir 94/33/EC on the protection of young people at work.  
Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

## 15.2 Chemical safety assessment

This information is not available.

### SECTION 16: OTHER INFORMATION

**Changes from the previous version are indicated by markings in the left-hand margin.**

**The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.**

# SÜDWEST Holz-Öl

## Full text of H-Statements

H304 : May be fatal if swallowed and enters airways.

## Full text of other abbreviations

Asp. Tox. : Aspiration hazard

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AICS - Australian Inventory of Chemical Substances; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## Further information

Other information : The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.



# SÜDWEST Holz-Öl

Department issuing  
MSDS  
REG\_EU / EN

sdb@suedwest.de