

## SAFETY DATA SHEET

# SÜDWEST 2K-Acryl- Seidenglanzlack

Ref.	130000006272/
Rev. no.	1.4
Revision Date	02.12.2021
Print Date	04.01.2022

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Trade name SÜDWEST 2K-Acryl-Seidenglanzlack

Unique Formula Identifier (UFI) DG01-3006-800F-U9M5

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Coating

Reserved for industrial and professional use.

Uses advised against This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG  
Iggelheimer Str. 13  
D - 67459 Böhl-Iggelheim  
Telephone: +49 6324/709-0  
Telefax: +49 6324/709-175  
[www.suedwest.de](http://www.suedwest.de)

E-mail address of person responsible for the SDS European Union [sdb@suedwest.de](mailto:sdb@suedwest.de)

1.4 Emergency telephone number European Union Phone: +44 (0)1235 239 670

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

# SÜDWEST 2K-Acryl- Seidenglanzlack

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word	: Warning
Hazard statements	: H226 Flammable liquid and vapour. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	: <b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe vapours. P280 Wear protective gloves/ protective clothing/ eye protection/ face protection. P284 Wear respiratory protection. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor.

# SÜDWEST 2K-Acryl- Seidenglanzlack

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

**Disposal:**

P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

**Hazardous components which must be listed on the label:**

xylene  
Hydrocarbons, C9, aromatics  
maleic anhydride

**Additional Labelling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	≥ 20 - < 30
Hydrocarbons, C9, aromatics	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35-XXXX	Asp. Tox. 1; H304 Flam. Liq. 3; H226 STOT SE 3; H335, H336 Aquatic Chronic 2; H411  EUH066	≥ 10 - < 20
n-butyl acetate	123-86-4 204-658-1 607-025-00-1	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous)	≥ 1 - < 10

# SÜDWEST 2K-Acryl- Seidenglanzlack

	01-2119485493-29-XXXX	system) EUH066	
ethylbenzene	100-41-4 202-849-4 601-023-00-4 01-2119489370-35-XXXX	Flam. Liq. 2; H225 Asp. Tox. 1; H304 Acute Tox. 4; H332 STOT RE 2; H373 Aquatic Chronic 3; H412	≥ 1 - < 2,5
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17-XXXX	Carc. 2; H351, Note V, Note W, Note 10	≥ 1 - < 10
Fatty acids, C14-18 and C16-18-unsatd., maleated	85711-46-2 288-306-2 01-2119976378-19-XXXX	Skin Irrit. 2; H315 Skin Sens. 1; H317	≥ 0,1 - < 1
maleic anhydride	108-31-6 203-571-6 607-096-00-9 01-2119472428-31-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system) EUH071  _____ specific concentration limit Skin Sens. 1A; H317 ≥ 0,001 %  _____ Acute toxicity estimate  Acute oral toxicity: 500,0 mg/kg	≥ 0,001 - < 0,1

For explanation of abbreviations see section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

General advice	When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately.

# SÜDWEST 2K-Acryl- Seidenglanzlack

Eye contact	Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Ingestion	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice. Rinse mouth with water. If swallowed, seek medical advice immediately and show this container or label. Keep at rest. Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms	Liver disorders Kidney disorders Damage Nervous system Inhalation may provoke the following symptoms: irritant effects Headache Vertigo Drowsiness Unconsciousness
----------	---

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	Treat symptomatically. No information available.
-----------	---

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

Suitable extinguishing media	CO <sub>2</sub> , extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Unsuitable extinguishing media	High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.

#### 5.3 Advice for firefighters

Additional advice	In the event of fire, wear self-contained breathing apparatus. Fight fire with normal precautions from a reasonable distance. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
-------------------	---

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.  
Ensure adequate ventilation.  
Do not breathe vapour.  
Prevent unauthorized access.

#### 6.2 Environmental

The product should not be allowed to enter drains, water courses

# SÜDWEST 2K-Acryl- Seidenglanzlack

## precautions

or the soil.

If the product contaminates rivers and lakes or drains inform respective authorities.

## 6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Clean with detergents. Avoid solvents.

Clean contaminated surface thoroughly.

Dispose of contaminated material as waste according to item 13.

Refer to protective measures listed in sections 7 and 8.

## 6.4 Reference to other sections

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

#### Advice on safe handling

Comply with the statutory regulations on health and safety at work. Avoid formation of aerosol.

Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values.

The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.

All metal parts of the mixing and processing equipment must be earthed.

Operators should wear antistatic footwear and clothing. No sparking tools should be used.

#### Hygiene measures

Do not breathe spray, vapour.

Take off immediately all contaminated clothing.

Avoid contact with skin, eyes and clothing.

Wash hands before breaks and immediately after handling the product.

After washing hands, replenish lost skin oil by means of oily skin ointment.

When using do not eat, drink or smoke.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Requirements for storage areas and containers

Store in original container.

Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nosmoking.

Prevent unauthorized access.

Containers which are opened must be carefully resealed and kept upright to prevent leakage.

Protect from frost, heat and sunlight.

#### Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors.

Vapours may form explosive mixtures with air.

Take measures to prevent the build up of electrostatic charge.

#### Advice on common storage

Keep away from combustible materials.

Keep away from food, drink and animal feedingstuffs.

Keep away from oxidizing agents and strongly acid or alkaline

# SÜDWEST 2K-Acryl- Seidenglanzlack

materials.

## 7.3 Specific end use(s)

For further information, see also Technical Data Sheet for the product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure limit(s)

Components	CAS-No.
Basis	Control parameters
Type:	
xylene	1330-20-7
2000/39/EC	Limit Value - eight hours 221 mg/m <sup>3</sup>
2000/39/EC	Limit Value - eight hours 50 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative
2000/39/EC	Short term exposure limit 442 mg/m <sup>3</sup>
2000/39/EC	Short term exposure limit 100 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative
n-butyl acetate	123-86-4
2019/1831/EU	Short term exposure limit 723 mg/m <sup>3</sup>
2019/1831/EU	Short term exposure limit 150 ppm
Additional advice:	Indicative
2019/1831/EU	Limit Value - eight hours 241 mg/m <sup>3</sup>
2019/1831/EU	Limit Value - eight hours 50 ppm
Additional advice:	Indicative
ethylbenzene	100-41-4
2000/39/EC	Limit Value - eight hours 442 mg/m <sup>3</sup>
2000/39/EC	Limit Value - eight hours 100 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative
2000/39/EC	Short term exposure limit 884 mg/m <sup>3</sup>
2000/39/EC	Short term exposure limit 200 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative

The lists that were valid during the creation were used as basis.

### 8.2 Exposure controls

#### Appropriate engineering controls

# SÜDWEST 2K-Acryl- Seidenglanzlack

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn.

Washing facilities / water for rinsing eyes and skin should be available.

## Individual protection measures, such as personal protective equipment

a) Eye/face protection	Safety glasses with side-shields conforming to EN166
b) Skin protection	Recommended preventive skin protection
Hand protection	Before starting work, apply water-resistant skincare preparations to exposed skin areas. Protective gloves should be worn in case of skin contact during preparation and application.  Break through time: 480 min Minimum thickness: 0,4 mm Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent. Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.
Body Protection	The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. Preventive skin protection Long sleeved clothing Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.
c) Respiratory protection	For brief exposure or low level concentrations use a respiratory filter; for more intense or longer exposure use a self-contained respiratory protective device. Respiratory filter for brief exposure: Combination filter A-P2 Respiratory protection complying with EN 14387.

## Environmental exposure controls

General advice	The product should not be allowed to enter drains, water courses or the soil. If the product contaminates rivers and lakes or drains inform respective authorities.
----------------	--

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	liquid
------------	--------



# SÜDWEST 2K-Acryl- Seidenglanzlack

Colour	various
Odour	characteristic
Odour Threshold	No data available
pH	substance/mixture is non-soluble (in water)
Melting point/freezing point	No data available
Initial boiling point and boiling range	127 °C
Flash point	25 °C
Evaporation rate	not determined
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	7,0 %(V) Upper explosion limit
Lower explosion limit / Lower flammability limit	0,6 %(V) Lower explosion limit
Vapour pressure	5 hPa (20 °C)
Vapour density	No data available
Density	ca. 1,12 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	insoluble
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity	
Viscosity, dynamic	ca. 130 mPa.s (40 °C)
Viscosity, kinematic	ca. 116,1 mm <sup>2</sup> /s (40 °C)
Explosive properties	Not explosive In use may form flammable/explosive vapour-air mixture.
Oxidizing properties	Not applicable

## 9.2 Other information

Flow time	> 90 s at 20 °C Cross section: 4 mm Method: ISO 2431
-----------	--

# SÜDWEST 2K-Acryl- Seidenglanzlack

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions                      No dangerous reaction known under conditions of normal use.  
Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid                      Direct sources of heat.  
Strong sunlight for prolonged periods.

### 10.5 Incompatible materials

Materials to avoid                      Strong acids and strong bases  
Strong oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity                      Based on available data, the classification criteria are not met.

Acute inhalation toxicity              Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity                    Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### xylene:

Acute inhalation toxicity              LC50 (Rat): 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity                    Harmful in contact with skin.

##### ethylbenzene:

Acute inhalation toxicity              Harmful if inhaled.

# SÜDWEST 2K-Acryl- Seidenglanzlack

**maleic anhydride:**

Acute oral toxicity

Acute toxicity estimate: 500,0 mg/kg

Method: Converted acute toxicity point estimate

**Skin corrosion/irritation****Product:**

Causes skin irritation.

**Components:****xylene:**

Causes skin irritation.

**Hydrocarbons, C9, aromatics:**

Repeated exposure may cause skin dryness or cracking.

**n-butyl acetate:**

Repeated exposure may cause skin dryness or cracking.

**Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Causes skin irritation.

**maleic anhydride:**

Causes severe skin burns and eye damage.

**Serious eye damage/eye irritation****Product:**

Causes serious eye irritation.

**Components:****xylene:**

Causes serious eye irritation.

**Fatty acids, C14-18 and C16-18-unsatd., maleated:**

Causes serious eye irritation.

**maleic anhydride:**

Causes serious eye damage.

**Respiratory or skin sensitisation****Product:**

May cause an allergic skin reaction.

Does not cause respiratory sensitisation.

**Components:****Fatty acids, C14-18 and C16-18-unsatd., maleated:**

May cause an allergic skin reaction.

**maleic anhydride:**

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# SÜDWEST 2K-Acryl- Seidenglanzlack

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

**Carcinogenicity****Product:**

Based on available data, the classification criteria are not met.

**Components:****titanium dioxide:**

Suspected of causing cancer.

**Reproductive toxicity****Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

**STOT - single exposure****Product:**

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

**Components:****xylene:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation.

**Hydrocarbons, C9, aromatics:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

**n-butyl acetate:**

Exposure routes

inhalation (vapour)

Assessment

May cause drowsiness or dizziness.

**STOT - repeated exposure****Product:**

Assessment

May cause damage to organs through prolonged or repeated exposure.

**Components:****xylene:**

Assessment

May cause damage to organs through prolonged or repeated exposure.

**ethylbenzene:**

Assessment

May cause damage to organs through prolonged or repeated exposure.

# SÜDWEST 2K-Acryl- Seidenglanzlack

**maleic anhydride:**

Assessment

Causes damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Product:**

Based on available data, the classification criteria are not met.

**Components:****xylene:**

May be fatal if swallowed and enters airways.

**Hydrocarbons, C9, aromatics:**

May be fatal if swallowed and enters airways.

**ethylbenzene:**

May be fatal if swallowed and enters airways.

**Toxicology, Metabolism, Distribution****Further information****Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

**11.2 Information on other hazards****Endocrine disrupting properties****Product:**

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Experience with human exposure****Product:**

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

**Further information****Product:**

Remarks

: The product itself has not been tested. The mixture is

# SÜDWEST 2K-Acryl- Seidenglanzlack

classified in accordance with Annex I to EC Directive  
1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

**Product:**

Toxicity to fish No data available

**Components:**

**Hydrocarbons, C9, aromatics:**

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 9,22 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other  
aquatic invertebrates EC50 (Daphnia magna (Water flea)): 6,14 mg/l  
Exposure time: 48 h

### 12.2 Persistence and degradability

**Product:**

Biodegradability No data available

**Components:**

**Hydrocarbons, C9, aromatics:**

Biodegradability rapidly degradable

**n-butyl acetate:**

Biodegradability rapidly degradable  
Biodegradation: > 90 %  
Exposure time: 28 d

### 12.3 Bioaccumulative potential

**Product:**

Bioaccumulation No data available

**Components:**

**xylene:**

Partition coefficient: n-  
octanol/water log Pow: > 3

**n-butyl acetate:**

Partition coefficient: n-  
octanol/water log Pow: 2,3  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

**Product:**

Mobility No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment This substance/mixture contains no components considered  
to be either persistent, bioaccumulative and toxic (PBT), or  
very persistent and very bioaccumulative (vPvB) at levels of  
0.1% or higher..

# SÜDWEST 2K-Acryl- Seidenglanzlack

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### Product:

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.  
Harmful to aquatic life with long lasting effects.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Product	The user is responsible for proper coding and marking of any waste. When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste" Partial and residual quantities can be reused. Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.
Contaminated packaging Waste key for the unused product	Empty packaging should be recycled through disposal systems. 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances (* ) hazardous waste in terms of the European directive 2008/98/EG

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number or ID number

ADR	1263
IMDG	1263
IATA	1263

### 14.2 UN proper shipping name

ADR	PAINT
IMDG	PAINT
IATA	Paint

### 14.3 Transport hazard class(es)

# SÜDWEST 2K-Acryl- Seidenglanzlack

ADR	3
IMDG	3
IATA	3

## 14.4 Packing group

### ADR

Packing group	III
Classification Code	F1
Hazard Identification Number	30
Labels	3
Tunnel restriction code	(D/E)

### IMDG

Packaging group	III
Labels	3
EmS number	F-E, <u>S-E</u>

### IATA

Packaging group	III
Labels	3

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

Remarks This information is not available.

## 14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

## Additional advice

ADR ADR: Packages < 450l: No dangerous goods (ADR 2.2.3.1.5)



# SÜDWEST 2K-Acryl- Seidenglanzlack

IMDG

IMDG: Packages &lt; 450l: No dangerous goods (IMDG 2.3.2.5).

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC  
Directive 2010/75/EU                      50,7 %

VOC  
Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EC) No 649/2012      Not applicable  
of the European Parliament  
and the Council concerning the  
export and import of dangerous  
chemicals

Other regulations                      Comply with the statutory regulations on health and safety at work.  
Take note of Dir 94/33/EC on the protection of young people at  
work.  
Take note of Dir 92/85/EEC on the safety and health at work of  
pregnant workers.

### 15.2 Chemical safety assessment

This information is not available.

## SECTION 16: OTHER INFORMATION

**Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.**

### Full text of H-Statements

H225                                      : Highly flammable liquid and vapour.  
H226                                      : Flammable liquid and vapour.  
H302                                      : Harmful if swallowed.  
H304                                      : May be fatal if swallowed and enters airways.  
H312                                      : Harmful in contact with skin.

# SÜDWEST 2K-Acryl- Seidenglanzlack

H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H351	: Suspected of causing cancer if inhaled.
H372	: Causes damage to organs through prolonged or repeated exposure if inhaled.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

## Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitisation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic

# SÜDWEST 2K-Acryl- Seidenglanzlack

Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## Further information

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de

# **SÜDWEST 2K-Acryl- Seidenglanzlack**