

SAFETY DATA SHEET

SÜDWEST Flächen-Lasur

Ref.	130000006122/
Rev. no.	1.6
Revision Date	28.09.2021
Print Date	16.11.2021

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Trade name SÜDWEST Flächen-Lasur

Unique Formula Identifier (UFI) R8S2-00CF-P006-V3DA

1.2 Relevant identified uses of the substance or mixture and uses advised against

Wood coating
Glazing

Uses advised against This information is not available.

1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG
Iggelheimer Str. 13
D - 67459 Böhl-Iggelheim
Telephone: +49 6324/709-0
Telefax: +49 6324/709-175
www.suedwest.de

E-mail address of person responsible for the SDS European Union sdb@suedwest.de

1.4 Emergency telephone number European Union Phone: +44 (0)1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

SÜDWEST Flächen-Lasur

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

Supplemental Hazard Statements : EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : P102 Keep out of reach of children.

Prevention:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Response:

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

Disposal:

P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

Additional Labelling

EUH208 Contains maleic anhydride. May produce an allergic reaction.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9 649-327-00-6 01-2119457273-39-	Asp. Tox. 1; H304 EUH066	≥ 30 - < 50

SÜDWEST Flächen-Lasur

	XXXX		
Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9 01-2119463258-33-XXXX	Asp. Tox. 1; H304 Flam. Liq. 3; H226 STOT SE 3; H336 EUH066	≥ 1 - < 10
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17-XXXX	Carc. 2; H351, Note V, Note W, Note 10	≥ 1 - < 10
maleic anhydride	108-31-6 203-571-6 607-096-00-9 01-2119472428-31-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Resp. Sens. 1; H334 Skin Sens. 1A; H317 STOT RE 1; H372 (Respiratory system) EUH071 _____ specific concentration limit Skin Sens. 1A; H317 ≥ 0,001 % _____ Acute toxicity estimate Acute oral toxicity: 500,0 mg/kg	< 0,001

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

General advice	When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Eye contact	If skin irritation persists, call a physician. In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.

SÜDWEST Flächen-Lasur

Ingestion
 Seek medical advice.
 Rinse mouth with water.
 If swallowed, seek medical advice immediately and show this container or label.
 Keep at rest.
 Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.
 No information available.

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media**

Suitable extinguishing media CO₂, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
 Unsuitable extinguishing media High volume water jet

5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:
 Carbon monoxide
 Carbon dioxide (CO₂)
 Nitrogen oxides (NO_x)
 Exposure to decomposition products may be a hazard to health.
 Cool closed containers exposed to fire with water spray.

5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.
 Fight fire with normal precautions from a reasonable distance.
 Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

Additional advice

SECTION 6: ACCIDENTAL RELEASE MEASURES**6.1 Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition.
 Ensure adequate ventilation.
 Do not breathe vapour.
 Prevent unauthorized access.

6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.
 If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Clean with detergents. Avoid solvents.

Clean contaminated surface thoroughly.

Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

SÜDWEST Flächen-Lasur

Advice on safe handling	Comply with the statutory regulations on health and safety at work. Avoid formation of aerosol. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. All metal parts of the mixing and processing equipment must be earthed. Operators should wear antistatic footwear and clothing. No sparking tools should be used.
Hygiene measures	Do not breathe spray, vapour. Take off all contaminated clothing immediately. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. After washing hands, replenish lost skin oil by means of oily skin ointment. When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	Store in original container. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nosmoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a well-ventilated place. Protect from frost, heat and sunlight.
Advice on protection against fire and explosion	Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from sources of ignition - No smoking.
Advice on common storage	Take measures to prevent the build up of electrostatic charge. Keep away from combustible materials. Keep away from food, drink and animal feedingstuffs. Keep away from oxidizing agents and strongly acid or alkaline materials.

7.3 Specific end use(s)	For further information, see also Technical Data Sheet for the product.
--------------------------------	---

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Contains no substances with occupational exposure limit values. The lists that were valid during the creation were used as basis.

8.2 Exposure controls

Appropriate engineering controls

SÜDWEST Flächen-Lasur

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn.

Washing facilities / water for rinsing eyes and skin should be available.

Individual protection measures, such as personal protective equipment

a) Eye/face protection	Safety glasses with side-shields conforming to EN166
b) Skin protection	Recommended preventive skin protection
Hand protection	<p>Before starting work, apply water-resistant skincare preparations to exposed skin areas.</p> <p>Protective gloves should be worn in case of skin contact during preparation and application.</p> <p>Break through time: 480 min Minimum thickness: 0,4 mm Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent.</p> <p>Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.</p> <p>The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.</p> <p>The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.</p>
Body Protection	<p>Preventive skin protection</p> <p>Long sleeved clothing</p> <p>Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.</p>
c) Respiratory protection	<p>When workers are facing concentrations above the occupational exposure limit values they must use appropriate certified respirators.</p> <p>Breathing protection equipment required in inadequately ventilated places and during spraying.</p> <p>In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.</p> <p>Combination filter A-P2 Respiratory protection complying with EN 14387.</p>
Environmental exposure controls	
General advice	<p>The product should not be allowed to enter drains, water courses or the soil.</p> <p>If the product contaminates rivers and lakes or drains inform respective authorities.</p>

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

SÜDWEST Flächen-Lasur

Appearance	liquid
Colour	various
Odour	characteristic
Odour Threshold	No data available
pH	5,5 - 8,5 Concentration: 100 %
Melting point/freezing point	No data available
Initial boiling point and boiling range	162 °C
Flash point	57,6 °C Method: closed cup
Evaporation rate	not determined
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	8,0 %(V) Upper explosion limit
Lower explosion limit / Lower flammability limit	0,6 %(V) Lower explosion limit
Vapour pressure	1 hPa (20 °C)
Vapour density	No data available
Density	ca. 0,924 g/cm ³
Solubility(ies)	
Water solubility	insoluble
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity	
Viscosity, dynamic	No data available
Viscosity, kinematic	ca. 86,6 mm ² /s (40 °C)
Explosive properties	Not explosive
Oxidizing properties	Not applicable

9.2 Other information

Solvent separation	<3 %(V)
Flow time	> 90 s at 20 °C Cross section: 4 mm

SÜDWEST Flächen-Lasur

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid Direct sources of heat.
Strong sunlight for prolonged periods.

10.5 Incompatible materials

Materials to avoid Strong acids and strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity Based on available data, the classification criteria are not met.

Acute inhalation toxicity Based on available data, the classification criteria are not met.

Acute dermal toxicity Based on available data, the classification criteria are not met.

Components:

maleic anhydride:

Acute oral toxicity Acute toxicity estimate: 500,0 mg/kg
Method: Converted acute toxicity point estimate

Skin corrosion/irritation

Product:

Repeated exposure may cause skin dryness or cracking.

Components:

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Repeated exposure may cause skin dryness or cracking.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

Method OECD Test Guideline 404
Repeated exposure may cause skin dryness or cracking.

SÜDWEST Flächen-Lasur

maleic anhydride:

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation**Product:**

Based on available data, the classification criteria are not met.

Components:**maleic anhydride:**

Causes serious eye damage.

Respiratory or skin sensitisation**Product:**

Based on available data, the classification criteria are not met.

Components:**maleic anhydride:**

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

Carcinogenicity**Product:**

Based on available data, the classification criteria are not met.

Components:**titanium dioxide:**

Suspected of causing cancer.

Reproductive toxicity**Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure**Product:**

Based on available data, the classification criteria are not met.

Components:**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Assessment

May cause drowsiness or dizziness.

STOT - repeated exposure**Product:**

Based on available data, the classification criteria are not met.

SÜDWEST Flächen-Lasur

Components:**maleic anhydride:**

Assessment

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity**Product:**

Based on available data, the classification criteria are not met.

Components:**Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

May be fatal if swallowed and enters airways.

Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:

May be fatal if swallowed and enters airways.

Toxicology, Metabolism, Distribution**Further information****Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

11.2 Information on other hazards**Endocrine disrupting properties****Product:**

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Experience with human exposure**Product:**

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

Further information**Product:**

Remarks

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

SÜDWEST Flächen-Lasur**SECTION 12: ECOLOGICAL INFORMATION****12.1 Toxicity****Product:**

Toxicity to fish No data available

12.2 Persistence and degradability**Product:**

Biodegradability No data available

Components:**Hydrocarbons, C9-C11, n-alkanes, isoalkanes, cyclics, <2% aromatics:**Biodegradability rapidly degradable
Biodegradation: 80 %
Exposure time: 28 d**12.3 Bioaccumulative potential****Product:**

Bioaccumulation No data available

12.4 Mobility in soil**Product:**

Mobility No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects**Product:**

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.

SECTION 13: DISPOSAL CONSIDERATIONS**13.1 Waste treatment methods**Product The user is responsible for proper coding and marking of any waste.
When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste"
Partial and residual quantities can be reused.

SÜDWEST Flächen-Lasur

Contaminated packaging	Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site. Packaging that is not properly emptied must be disposed of as the unused product.
Waste key for the unused product	Empty packaging should be recycled through disposal systems. 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances (*) hazardous waste in terms of the European directive 2008/98/EG

SECTION 14: TRANSPORT INFORMATION**14.1 UN number or ID number**

ADR	1263
IMDG	1263
IATA	1263

14.2 UN proper shipping name

ADR	PAINT
IMDG	PAINT
IATA	Paint

14.3 Transport hazard class(es)

ADR	3
IMDG	3
IATA	3

14.4 Packing group

ADR	
Packing group	III
Classification Code	F1
Hazard Identification Number	30
Labels	3
Tunnel restriction code	(D/E)
IMDG	
Packaging group	III
Labels	3
EmS number	F-E, <u>S-E</u>
IATA	

SÜDWEST Flächen-Lasur

Packaging group III

Labels 3

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks This information is not available.

14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

Additional advice

ADR ADR: Packages < 450l: No dangerous goods (ADR 2.2.3.1.5)

IMDG IMDG: Packages < 450l: No dangerous goods (IMDG 2.3.2.5).

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC
Directive 2010/75/EU 37,6 %

VOC
Directive 2004/42/EC 37,6 %
346,9 g/l

EU limit value for this product (cat. A/e) :400 g/l
This product contains max400 g/lVOC.

Regulation (EC) No 649/2012
of the European Parliament
and the Council concerning the
export and import of dangerous
chemicals Not applicable

Other regulations Comply with the statutory regulations on health and safety at work.
Take note of Dir 94/33/EC on the protection of young people at

SÜDWEST Flächen-Lasur

work.

Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

Full text of H-Statements

H226	: Flammable liquid and vapour.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H314	: Causes severe skin burns and eye damage.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H336	: May cause drowsiness or dizziness.
H351	: Suspected of causing cancer if inhaled.
H372	: Causes damage to organs through prolonged or repeated exposure.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitisation
Skin Corr.	: Skin corrosion
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA -

SÜDWEST Flächen-Lasur

International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS
REG_EU / EN

sdb@suedwest.de

SÜDWEST Flächen-Lasur