

## SAFETY DATA SHEET

# SÜDWEST 2K-Acryl-Lack Mattierungs-Zusatz

Ref.	130000006161/
Rev. no.	1.4
Revision Date	15.12.2021
Print Date	04.01.2022

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Trade name SÜDWEST 2K-Acryl-Lack Mattierungs-Zusatz

Unique Formula Identifier (UFI) WMS0-K0SE-R00V-W000

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Flatting agent, Matting agent

Reserved for industrial and professional use.

Uses advised against This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG  
Iggelheimer Str. 13  
D - 67459 Böhl-Iggelheim  
Telephone: +49 6324/709-0  
Telefax: +49 6324/709-175  
[www.suedwest.de](http://www.suedwest.de)

E-mail address of person responsible for the SDS European Union [sdb@suedwest.de](mailto:sdb@suedwest.de)

1.4 Emergency telephone number European Union Phone: +44 (0)1235 239 670

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

# SÜDWEST 2K-Acryl-Lack

## Mattierungs-Zusatz

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word	: Warning
Hazard statements	: H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	: <b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P280 Wear protective gloves/ eye protection/ face protection. P284 Wear respiratory protection. <b>Response:</b> P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P304 + P340 + P310 IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER/ doctor. <b>Disposal:</b> P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

# SÜDWEST 2K-Acryl-Lack

## Mattierungs-Zusatz

### Hazardous components which must be listed on the label:

xylene  
Hydrocarbons, C9, aromatics

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	≥ 20 - < 30
Hydrocarbons, C9, aromatics	64742-95-6 265-199-0 649-356-00-4 01-2119455851-35-XXXX	Asp. Tox. 1; H304 Flam. Liq. 3; H226 STOT SE 3; H335, H336 Aquatic Chronic 2; H411  EUH066	≥ 20 - < 25
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	≥ 1 - < 10
propan-2-ol	67-63-0 200-661-7 603-117-00-0 01-2119457558-25-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336	≥ 1 - < 10

For explanation of abbreviations see section 16.

# SÜDWEST 2K-Acryl-Lack

## Mattierungs-Zusatz

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures

General advice	When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Eye contact	If skin irritation persists, call a physician. In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Ingestion	Seek medical advice. Rinse mouth with water. If swallowed, seek medical advice immediately and show this container or label. Keep at rest. Do NOT induce vomiting.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.  
No information available.

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

Suitable extinguishing media	CO <sub>2</sub> , extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Unsuitable extinguishing media	High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.

#### 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.  
Fight fire with normal precautions from a reasonable distance.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

# SÜDWEST 2K-Acryl-Lack

## Mattierungs-Zusatz

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.  
Ensure adequate ventilation.  
Do not breathe vapour.  
Prevent unauthorized access.

#### 6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Clean with detergents. Avoid solvents.  
Clean contaminated surface thoroughly.

#### 6.4 Reference to other sections

Dispose of contaminated material as waste according to item 13.  
Refer to protective measures listed in sections 7 and 8.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

##### Advice on safe handling

Comply with the statutory regulations on health and safety at work.  
Avoid formation of aerosol.  
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
All metal parts of the mixing and processing equipment must be earthed.

##### Hygiene measures

Operators should wear antistatic footwear and clothing. No sparking tools should be used.  
Do not breathe spray, vapour.  
Take off immediately all contaminated clothing.  
Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
After washing hands, replenish lost skin oil by means of oily skin ointment.  
When using do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

##### Requirements for storage areas and containers

Store in original container.  
Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nosmoking.  
Prevent unauthorized access.  
Containers which are opened must be carefully resealed and kept

# SÜDWEST 2K-Acryl-Lack

## Mattierungs-Zusatz

Advice on protection against fire and explosion	upright to prevent leakage. Protect from frost, heat and sunlight. Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air.
Advice on common storage	Take measures to prevent the build up of electrostatic charge. Keep away from combustible materials. Keep away from food, drink and animal feedingstuffs. Keep away from oxidizing agents and strongly acid or alkaline materials.
<b>7.3 Specific end use(s)</b>	For further information, see also Technical Data Sheet for the product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

xylene		1330-20-7
2000/39/EC	Limit Value - eight hours	221 mg/m <sup>3</sup>
2000/39/EC	Limit Value - eight hours	50 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	
2000/39/EC	Short term exposure limit	442 mg/m <sup>3</sup>
2000/39/EC	Short term exposure limit	100 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	
n-butyl acetate		123-86-4
2019/1831/EU	Short term exposure limit	723 mg/m <sup>3</sup>
2019/1831/EU	Short term exposure limit	150 ppm
Additional advice:	Indicative	
2019/1831/EU	Limit Value - eight hours	241 mg/m <sup>3</sup>
2019/1831/EU	Limit Value - eight hours	50 ppm
Additional advice:	Indicative	

The lists that were valid during the creation were used as basis.

#### 8.2 Exposure controls

##### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn.

Washing facilities / water for rinsing eyes and skin should be available.

##### Individual protection measures, such as personal protective equipment

- a) Eye/face protection                      Safety glasses with side-shields conforming to EN166  
b) Skin protection

# SÜDWEST 2K-Acryl-Lack

## Mattierungs-Zusatz

Hand protection	<p>Recommended preventive skin protection Before starting work, apply water-resistant skincare preparations to exposed skin areas. Protective gloves should be worn in case of skin contact during preparation and application.</p> <p>Break through time: 480 min Minimum thickness: 0,4 mm Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent. Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.</p> <p>The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.</p>
Body Protection	<p>Preventive skin protection Long sleeved clothing Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthehic fiber. All parts of the body should be washed after contact.</p>
c) Respiratory protection	<p>For brief exposure or low level concentrations use a respiratory filter; for more intense or longer exposure use a self-contained respiratory protective device. Respiratory filter for brief exposure: Combination filter A-P2 Respiratory protection complying with EN 14387.</p>
<b>Environmental exposure controls</b>	
General advice	<p>The product should not be allowed to enter drains, water courses or the soil. If the product contaminates rivers and lakes or drains inform respective authorities.</p>

### SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

#### 9.1 Information on basic physical and chemical properties

Appearance	liquid
Colour	off-white
Odour	characteristic
Odour Threshold	No data available
pH	Not applicable
Melting point/freezing point	No data available
Initial boiling point and boiling range	127 °C
Flash point	30 °C

# SÜDWEST 2K-Acryl-Lack

## Mattierungs-Zusatz

Evaporation rate	not determined
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	7,0 %(V) Upper explosion limit
Lower explosion limit / Lower flammability limit	0,6 %(V) Lower explosion limit
Vapour pressure	5 hPa (20 °C)
Vapour density	No data available
Density	ca. 1,030 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	insoluble
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity	
Viscosity, dynamic	ca. 1.250 mPa.s (20 °C)
Viscosity, kinematic	ca. 99,0 mm <sup>2</sup> /s (40 °C)
Explosive properties	Not explosive In use may form flammable/explosive vapour-air mixture.
Oxidizing properties	Not applicable

### 9.2 Other information

Flow time	> 90 s at 20 °C Cross section: 4 mm
-----------	--

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	No dangerous reaction known under conditions of normal use. Vapours may form explosive mixture with air.
---------------------	---



# SÜDWEST 2K-Acryl-Lack Mattierungs-Zusatz

## 10.4 Conditions to avoid

Conditions to avoid                      Direct sources of heat.  
Strong sunlight for prolonged periods.

## 10.5 Incompatible materials

Materials to avoid                      Strong acids and strong bases  
Strong oxidizing agents

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity                      Based on available data, the classification criteria are not met.

Acute inhalation toxicity              Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity                  Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### xylene:

Acute inhalation toxicity              LC50 (Rat): 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity                  Harmful in contact with skin.

#### Skin corrosion/irritation

##### Product:

Causes skin irritation.

#### Components:

##### xylene:

Causes skin irritation.

#### Hydrocarbons, C9, aromatics:

Repeated exposure may cause skin dryness or cracking.

#### n-butyl acetate:

Repeated exposure may cause skin dryness or cracking.

# SÜDWEST 2K-Acryl-Lack

## Mattierungs-Zusatz

**Serious eye damage/eye irritation****Product:**

Causes serious eye irritation.

**Components:****xylene:**

Causes serious eye irritation.

**propan-2-ol:**

Causes serious eye irritation.

**Respiratory or skin sensitisation****Product:**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

**Carcinogenicity****Product:**

Based on available data, the classification criteria are not met.

**Reproductive toxicity****Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

**STOT - single exposure****Product:**

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

**Components:****xylene:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation.

**Hydrocarbons, C9, aromatics:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

**n-butyl acetate:**

Exposure routes

inhalation (vapour)

Assessment

May cause drowsiness or dizziness.

**propan-2-ol:**

Assessment

May cause drowsiness or dizziness.

# SÜDWEST 2K-Acryl-Lack Mattierungs-Zusatz

**STOT - repeated exposure****Product:**

Assessment

May cause damage to organs through prolonged or repeated exposure.

**Components:****xylene:**

Assessment

May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Product:**

Based on available data, the classification criteria are not met.

**Components:****xylene:**

May be fatal if swallowed and enters airways.

**Hydrocarbons, C9, aromatics:**

May be fatal if swallowed and enters airways.

**Toxicology, Metabolism, Distribution****Further information****Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

**11.2 Information on other hazards****Endocrine disrupting properties****Product:**

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Experience with human exposure****Product:**

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

# SÜDWEST 2K-Acryl-Lack Mattierungs-Zusatz

## Further information

### Product:

Remarks

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### Product:

Toxicity to fish

No data available

#### Components:

##### **Hydrocarbons, C9, aromatics:**

Toxicity to fish

LC50 (Oncorhynchus mykiss (rainbow trout)): 9,22 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other  
aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 6,14 mg/l  
Exposure time: 48 h

### 12.2 Persistence and degradability

#### Product:

Biodegradability

No data available

#### Components:

##### **Hydrocarbons, C9, aromatics:**

Biodegradability

rapidly degradable

##### **n-butyl acetate:**

Biodegradability

rapidly degradable  
Biodegradation: > 90 %  
Exposure time: 28 d

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation

No data available

#### Components:

##### **xylene:**

Partition coefficient: n-  
octanol/water

log Pow: > 3

##### **n-butyl acetate:**

Partition coefficient: n-  
octanol/water

log Pow: 2,3  
Method: OECD Test Guideline 117

### 12.4 Mobility in soil

#### Product:

Mobility

No data available

### 12.5 Results of PBT and vPvB assessment

#### Product:

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or

# SÜDWEST 2K-Acryl-Lack

## Mattierungs-Zusatz

very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.  
Harmful to aquatic life with long lasting effects.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Product	The user is responsible for proper coding and marking of any waste. When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste" Partial and residual quantities can be reused. Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.
Contaminated packaging Waste key for the unused product	Empty packaging should be recycled through disposal systems. 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances (* ) hazardous waste in terms of the European directive 2008/98/EG

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number or ID number

ADR	1263
IMDG	1263
IATA	1263

### 14.2 UN proper shipping name

ADR	PAINT
IMDG	PAINT

# SÜDWEST 2K-Acryl-Lack Mattierungs-Zusatz

IATA Paint

## 14.3 Transport hazard class(es)

ADR 3  
IMDG 3  
IATA 3

## 14.4 Packing group

### ADR

Packing group III  
Classification Code F1  
Hazard Identification Number 30  
Labels 3  
Tunnel restriction code (D/E)

### IMDG

Packaging group III  
Labels 3  
EmS number F-E, S-E

### IATA

Packaging group III  
Labels 3

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

Remarks This information is not available.

## 14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

## Additional advice

# SÜDWEST 2K-Acryl-Lack Mattierungs-Zusatz

ADR ADR: Packages < 450l: No dangerous goods (ADR 2.2.3.1.5)  
IMDG IMDG: Packages < 450l: No dangerous goods (IMDG 2.3.2.5).

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC  
Directive 2010/75/EU 56,9 %

VOC  
Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EC) No 649/2012  
of the European Parliament  
and the Council concerning the  
export and import of dangerous  
chemicals Not applicable

Other regulations Comply with the statutory regulations on health and safety at work.  
Take note of Dir 94/33/EC on the protection of young people at  
work.  
Take note of Dir 92/85/EEC on the safety and health at work of  
pregnant workers.

### 15.2 Chemical safety assessment

This information is not available.

## SECTION 16: OTHER INFORMATION

**Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.**

### Full text of H-Statements

H225 : Highly flammable liquid and vapour.  
H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.





# SÜDWEST 2K-Acryl-Lack Mattierungs-Zusatz

(5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de