

SAFETY DATA SHEET

SÜDWEST Dach-Farbe

Ref.	130000006191/
Rev. no.	1.7
Revision Date	25.10.2021
Print Date	05.01.2022

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Trade name SÜDWEST Dach-Farbe

1.2 Relevant identified uses of the substance or mixture and uses advised against

Coating

Uses advised against This information is not available.

1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG
Iggelheimer Str. 13
D - 67459 Böhl-Iggelheim
Telephone: +49 6324/709-0
Telefax: +49 6324/709-175
www.suedwest.de

E-mail address of person responsible for the SDS
European Union
sdb@suedwest.de

1.4 Emergency telephone number European Union Phone: +44 (0)1235 239 670

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Long-term (chronic) aquatic hazard, Category 3 H412: Harmful to aquatic life with long lasting effects.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard statements : H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**
P273 Avoid release to the environment.

SÜDWEST Dach-Farbe**Disposal:**

P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

Additional Labelling

EUH208 Contains 1,2-benzisothiazol-3(2H)-one, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1). May produce an allergic reaction.

These are preservatives.
Avoid contact with the skin and the eyes.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Regulation concerning biocidal products (528/2012):

Contains Terbutryn
. As active agents for coating protection in accordance with Biocidal Product Regulation (528/2012), Article 58(3)

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS**3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17-XXXX	Carc. 2; H351, Note V, Note W, Note 10	≥ 1 - < 10
Terbutryn	886-50-0 212-950-5	Acute Tox. 4; H302 Skin Sens. 1B; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410	≥ 0,0025 - < 0,025

SÜDWEST Dach-Farbe

		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	
1,2-benzisothiazol-3(2H)-one	2634-33-5 220-120-9 613-088-00-6	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Skin Sens. 1; H317 Aquatic Acute 1; H400 M-Factor (Acute aquatic toxicity): 1 specific concentration limit Skin Sens. 1; H317 ≥ 0,05 %	≥ 0,0025 - < 0,025
pyrithione zinc	13463-41-7 236-671-3	Repr. 1B; H360D Acute Tox. 2; H330 Acute Tox. 3; H301 STOT RE 1; H372 Eye Dam. 1; H318 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 M-Factor (Acute aquatic toxicity): 1.000 M-Factor (Chronic aquatic toxicity): 10 Acute toxicity estimate Acute oral toxicity: 221 mg/kg Acute inhalation toxicity: 0,14 mg/l	≥ 0,0025 - < 0,025
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1)	55965-84-9 613-167-00-5	Acute Tox. 2; H330 Acute Tox. 2; H310 Acute Tox. 3; H301 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Eye Dam. 1; H318 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C; H314 ≥ 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 %	≥ 0,0002 - < 0,0015

SÜDWEST Dach-Farbe

		Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 ≥ 0,0015 % Eye Dam. 1 ≥ 0,6 %	
--	--	--	--

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES**4.1 Description of first aid measures**

General advice	In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Eye contact	If skin irritation persists, call a physician. In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention. Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	Treat symptomatically. No information available.
-----------	---

SECTION 5: FIREFIGHTING MEASURES**5.1 Extinguishing media**

Suitable extinguishing media	Alcohol-resistant foam Carbon dioxide (CO ₂) Dry chemical Water spray
Unsuitable extinguishing media	High volume water jet

5.2 Special hazards

Fire may cause evolution of:

SÜDWEST Dach-Farbe

arising from the substance or mixture	Carbon monoxide Carbon dioxide (CO ₂) Nitrogen oxides (NO _x) Exposure to decomposition products may be a hazard to health.
5.3 Advice for firefighters	Wear self-contained breathing apparatus for firefighting if necessary.
Additional advice	Use water spray to cool unopened containers. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures	Ensure adequate ventilation. Do not breathe vapour.
6.2 Environmental precautions	The product should not be allowed to enter drains, water courses or the soil. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents. Dispose of contaminated material as waste according to item 13. Clean contaminated surface thoroughly.
6.4 Reference to other sections	Refer to protective measures listed in sections 7 and 8.

SECTION 7: HANDLING AND STORAGE**7.1 Precautions for safe handling**

Advice on safe handling	Avoid contact with skin and eyes. Prevent unauthorized access. Provide sufficient air exchange and/or exhaust in work rooms. Comply with the statutory regulations on health and safety at work.
Hygiene measures	Wash hands before breaks and at the end of workday. When using do not eat, drink or smoke. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Observe label precautions. Protect from frost, heat and sunlight.
Advice on common storage	Keep away from oxidizing agents and strongly acid or alkaline materials.

7.3 Specific end use(s)	For further information, see also Technical Data Sheet for the product.
--------------------------------	---

SÜDWEST Dach-Farbe**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters**

Contains no substances with occupational exposure limit values. The lists that were valid during the creation were used as basis.

8.2 Exposure controls**Appropriate engineering controls**

Provide adequate ventilation.

Individual protection measures, such as personal protective equipment

- | | |
|---------------------------------------|---|
| a) Eye/face protection | Wear protective goggles for protection against splashed liquid.

Safety glasses with side-shields conforming to EN166 |
| b) Skin protection
Hand protection | Recommended preventive skin protection
Before starting work, apply water-resistant skincare preparations to exposed skin areas.
Protective gloves should be worn in case of skin contact during preparation and application.

Break through time: 480 min
Minimum thickness: 0,4 mm
Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent.
Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other. |
| Body Protection | Work clothes
Skin should be washed after contact.
Do NOT use solvents or thinners. |
| c) Respiratory protection | No personal respiratory protective equipment normally required.
In case of insufficient ventilation, wear suitable respiratory equipment.
Employees involved in spraying work or in the immediate vicinity of such work should use a P2 particle filter against spray fog.
Respiratory protection complying with EN 143. |

Environmental exposure controls

- | | |
|----------------|--|
| General advice | The product should not be allowed to enter drains, water courses or the soil.
If the product contaminates rivers and lakes or drains inform respective authorities. |
|----------------|--|

SÜDWEST Dach-Farbe**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

Appearance	liquid
Colour	various
Odour	characteristic
Odour Threshold	No data available
pH	ca. 8,7
Melting point/freezing point	No data available
Initial boiling point and boiling range	100 °C
Flash point	Not applicable
Evaporation rate	not determined
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	No data available
Lower explosion limit / Lower flammability limit	No data available
Vapour pressure	23 hPa (20 °C)
Vapour density	No data available
Density	ca. 1,267 g/cm ³
Solubility(ies)	
Water solubility	partly miscible
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity	
Viscosity, dynamic	ca. 5.057 mPa.s (20 °C)
Viscosity, kinematic	ca. 5,4 mm ² /s (40 °C)
Explosive properties	Not explosive
Oxidizing properties	Not applicable

9.2 Other information

Flow time	No data available
-----------	-------------------

SÜDWEST Dach-Farbe**SECTION 10: STABILITY AND REACTIVITY****10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions This information is not available.

10.4 Conditions to avoid

Conditions to avoid Stable under recommended storage and handling conditions
(see section 7).

10.5 Incompatible materials

Materials to avoid Strong acids and strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: TOXICOLOGICAL INFORMATION**11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity****Product:**

Acute oral toxicity Based on available data, the classification criteria are not met.

Acute inhalation toxicity Based on available data, the classification criteria are not met.

Acute dermal toxicity Based on available data, the classification criteria are not met.

Components:**Terbutryn:**

Acute oral toxicity Harmful if swallowed.

1,2-benzisothiazol-3(2H)-one:

Acute oral toxicity Harmful if swallowed.

pyrithione zinc:

Acute oral toxicity Acute toxicity estimate: 221 mg/kg
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

Acute inhalation toxicity Acute toxicity estimate: 0,14 mg/l
Test atmosphere: dust/mist
Method: Acute toxicity estimate according to Regulation (EC)
No. 1272/2008

SÜDWEST Dach-Farbe

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Acute oral toxicity Toxic if swallowed.

Acute inhalation toxicity Fatal if inhaled.

Acute dermal toxicity Fatal in contact with skin.

Skin corrosion/irritation

Product:

Based on available data, the classification criteria are not met.

Components:

1,2-benzisothiazol-3(2H)-one:

Causes skin irritation.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation

Product:

Based on available data, the classification criteria are not met.

Components:

1,2-benzisothiazol-3(2H)-one:

Causes serious eye damage.

pyrithione zinc:

Causes serious eye damage.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes serious eye damage.

Respiratory or skin sensitisation

Product:

May cause an allergic skin reaction.
Does not cause respiratory sensitisation.

Components:

Terbutryn:

Species

Mouse

Method

OECD Test Guideline 429

May cause an allergic skin reaction.

1,2-benzisothiazol-3(2H)-one:

May cause an allergic skin reaction.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

May cause an allergic skin reaction.

Germ cell mutagenicity

Product:

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

SÜDWEST Dach-Farbe

Carcinogenicity**Product:**

Based on available data, the classification criteria are not met.

Components:**titanium dioxide:**

Suspected of causing cancer.

Reproductive toxicity**Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

Components:**pyrithione zinc:**

Developmental Toxicity

May damage the unborn child.

STOT - single exposure**Product:**

Based on available data, the classification criteria are not met.

STOT - repeated exposure**Product:**

Based on available data, the classification criteria are not met.

Components:**pyrithione zinc:**

Assessment

Causes damage to organs through prolonged or repeated exposure.

Aspiration toxicity**Product:**

Based on available data, the classification criteria are not met.

Further information**Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

11.2 Information on other hazards**Endocrine disrupting properties****Product:**

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information**Product:**

Remarks

: The product itself has not been tested. The mixture is

SÜDWEST Dach-Farbe

classified in accordance with Annex I to EC Directive
1272/2008. (See sections 2 and 3 for details).

SECTION 12: ECOLOGICAL INFORMATION**12.1 Toxicity****Product:**

Toxicity to fish No data available

Components:**Terbutryn:**

M-Factor (Acute aquatic toxicity) 100

Toxicity to microorganisms EC20 (activated sludge): > 100 mg/l
Exposure time: 3 h
Method: OECD Test Guideline 209

M-Factor (Chronic aquatic toxicity) 100

1,2-benzisothiazol-3(2H)-one:

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 1,6 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates EC50 (Daphnia (water flea)): 2,94 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants EC50 (Selenastrum capricornutum (green algae)): 0,11 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity) 1

Toxicity to microorganisms EC50 (Pseudomonas putida): 0,4 mg/l
Exposure time: 16 h

pyrithione zinc:

Toxicity to fish LC50 (Danio rerio (zebra fish)): 0,0104 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates EC50 (Daphnia (water flea)): 0,051 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants EC50 (Skeletonema costatum (marine diatom)): 0,0013 mg/l
Exposure time: 72 h

NOEC (Skeletonema costatum (marine diatom)): 0,00046 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 201

SÜDWEST Dach-Farbe

M-Factor (Acute aquatic toxicity)	1.000
Toxicity to fish (Chronic toxicity)	NOEC: 0,00125 mg/l Exposure time: 28 d Species: Danio rerio (zebra fish)
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC: 0,0022 mg/l Exposure time: 21 d Species: Daphnia (water flea) Method: OECD Test Guideline 211
M-Factor (Chronic aquatic toxicity)	10
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):	
Toxicity to fish	LC50 (Oncorhynchus mykiss (rainbow trout)): 0,19 mg/l Exposure time: 96 h
Toxicity to daphnia and other aquatic invertebrates	EC50 (Daphnia (water flea)): 0,12 mg/l Exposure time: 48 h
Toxicity to algae/aquatic plants	EC50 (Skeletonema costatum (marine diatom)): 0,0052 mg/l Exposure time: 48 h NOEC (Skeletonema costatum (marine diatom)): 0,00049 mg/l Exposure time: 48 h
M-Factor (Acute aquatic toxicity)	100
Toxicity to fish (Chronic toxicity)	NOEC: 0,098 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC: 0,004 mg/l Exposure time: 21 d Species: Daphnia (water flea)
M-Factor (Chronic aquatic toxicity)	100
12.2 Persistence and degradability	
Product:	
Biodegradability	No data available
Components:	
Terbutryn:	
Biodegradability	Inoculum: activated sludge not rapidly degradable Biodegradation: 0 % Method: OECD Test Guideline 301F
1,2-benzisothiazol-3(2H)-one:	
Biodegradability	rapidly degradable Biodegradation: > 90 % Method: OECD Test Guideline 303A

SÜDWEST Dach-Farbe

pyrithione zinc:

Biodegradability

Inoculum: activated sludge
rapidly degradable
Biodegradation: > 85 %
Method: OECD Test Guideline 303A

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Biodegradability

not rapidly degradable

12.3 Bioaccumulative potential**Product:**

Bioaccumulation

No data available

Components:**Terbutryn:**

Bioaccumulation

Bioconcentration factor (BCF): 103
Method: Calculation method

Partition coefficient: n-
octanol/water

log Pow: 3,19
Method: OECD Test Guideline 117

1,2-benzisothiazol-3(2H)-one:

Partition coefficient: n-
octanol/water

log Pow: 0,4

pyrithione zinc:

Partition coefficient: n-
octanol/water

log Pow: 1,21
Method: OECD Test Guideline 107

12.4 Mobility in soil**Product:**

Mobility

No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties**Product:**

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects**Product:**

Additional ecological information

Do not allow product to enter into ground water, bodies of water or sewage systems.
Harmful to aquatic life with long lasting effects.

SÜDWEST Dach-Farbe

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product	The user is responsible for proper coding and marking of any waste. Dispose of as special waste in compliance with local and national regulations.
Contaminated packaging	Partial and residual quantities can be reused. Packaging that is not properly emptied must be disposed of as the unused product.
Waste key for the unused product	Empty packaging should be recycled through disposal systems. 08 01 11* waste paint and varnish containing organic solvents or other hazardous substances (*) hazardous waste in terms of the European directive 2008/98/EG

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

14.6 Special precautions for user

Remarks This information is not available.

14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC
Directive 2010/75/EU 0,7 %

SÜDWEST Dach-Farbe

VOC
Directive 2004/42/EC 1,2 %
15,6 g/l

EU limit value for this product (cat. A/i) :140 g/l This product
contains max140 g/lVOC.

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals Not applicable

Other regulations Comply with the statutory regulations on health and safety at work.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.
H310 : Fatal in contact with skin.
H314 : Causes severe skin burns and eye damage.
H315 : Causes skin irritation.
H317 : May cause an allergic skin reaction.
H318 : Causes serious eye damage.
H330 : Fatal if inhaled.
H351 : Suspected of causing cancer if inhaled.
H360D : May damage the unborn child.
H372 : Causes damage to organs through prolonged or repeated exposure.
H400 : Very toxic to aquatic life.
H410 : Very toxic to aquatic life with long lasting effects.

Full text of other abbreviations

Acute Tox. : Acute toxicity
Aquatic Acute : Short-term (acute) aquatic hazard
Aquatic Chronic : Long-term (chronic) aquatic hazard
Carc. : Carcinogenicity
Eye Dam. : Serious eye damage
Repr. : Reproductive toxicity

SÜDWEST Dach-Farbe

Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information	It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.
-------------------	---

Department issuing MSDS REG_EU / EN	sdb@suedwest.de
--	-----------------

SÜDWEST Dach-Farbe