



# SÜDWEST AquaVision Holz- Siegel satin

EUH208 Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1), adipohydrazide. May produce an allergic reaction.

These are preservatives.  
Avoid contact with the skin and the eyes.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
2-butoxyethanol	111-76-2 203-905-0 603-014-00-0 01-2119475108-36-XXXX	Acute Tox. 4; H332 Acute Tox. 4; H312 Acute Tox. 4; H302 Eye Irrit. 2; H319 Skin Irrit. 2; H315  Acute toxicity estimate  Acute oral toxicity: 1.200 mg/kg	≥ 1 - ≤ 2,5
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 01-2119475104-44-XXXX	Eye Irrit. 2; H319	≥ 1 - ≤ 2,5
adipohydrazide	1071-93-8 213-999-5 01-2119962900-36-XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	≥ 0,25 - < 1
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1)	55965-84-9  613-167-00-5	Acute Tox. 2; H330 Acute Tox. 2; H310 Acute Tox. 3; H301 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Eye Dam. 1; H318 EUH071	≥ 0,0002 - < 0,0015

# SÜDWEST AquaVision Holz- Siegel satin

		M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Corr. 1C; H314 ≥ 0,6 % Skin Irrit. 2; H315 0,06 - < 0,6 % Eye Irrit. 2; H319 0,06 - < 0,6 % Skin Sens. 1A; H317 ≥ 0,0015 % Eye Dam. 1 ≥ 0,6 %
--	--	---

For explanation of abbreviations see section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

General advice	In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners.
Eye contact	If skin irritation persists, call a physician. In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.
Ingestion	Seek medical advice. Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention. Keep at rest.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms No information available.

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.

# SÜDWEST AquaVision Holz- Siegel satin

No information available.

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Suitable extinguishing media	Alcohol-resistant foam Carbon dioxide (CO <sub>2</sub> ) Dry chemical Water spray
Unsuitable extinguishing media	High volume water jet

### 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)

### 5.3 Advice for firefighters

Exposure to decomposition products may be a hazard to health.  
Wear self-contained breathing apparatus for firefighting if necessary.

### Additional advice

Use water spray to cool unopened containers.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.  
Do not breathe vapour.

### 6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Clean with detergents. Avoid solvents.  
Dispose of contaminated material as waste according to item 13.  
Clean contaminated surface thoroughly.

### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

#### Advice on safe handling

Avoid contact with skin and eyes.  
Prevent unauthorized access.  
Provide sufficient air exchange and/or exhaust in work rooms.  
Comply with the statutory regulations on health and safety at work.

#### Hygiene measures

Wash hands before breaks and at the end of workday.  
When using do not eat, drink or smoke.  
Remove and wash contaminated clothing and gloves, including

# SÜDWEST AquaVision Holz- Siegel satin

the inside, before re-use.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Observe label precautions.
Advice on common storage	Protect from frost, heat and sunlight. Keep away from oxidizing agents and strongly acid or alkaline materials. Keep away from food, drink and animal feedingstuffs.

**7.3 Specific end use(s)** For further information, see also Technical Data Sheet for the product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### Exposure limit(s)

Components		CAS-No.
Basis	Type:	Control parameters
<b>2-butoxyethanol</b>		
2000/39/EC	Limit Value - eight hours	98 mg/m <sup>3</sup>
2000/39/EC	Limit Value - eight hours	20 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	
2000/39/EC	Short term exposure limit	246 mg/m <sup>3</sup>
2000/39/EC	Short term exposure limit	50 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	
<b>2-(2-butoxyethoxy)ethanol</b>		
2006/15/EC	Limit Value - eight hours	67,5 mg/m <sup>3</sup>
2006/15/EC	Limit Value - eight hours	10 ppm
Additional advice:	Indicative	
2006/15/EC	Short term exposure limit	101,2 mg/m <sup>3</sup>
2006/15/EC	Short term exposure limit	15 ppm
Additional advice:	Indicative	

The lists that were valid during the creation were used as basis.

### 8.2 Exposure controls

#### Appropriate engineering controls

Ensure good ventilation; if possible, use / install internal extractor equipment.



# SÜDWEST AquaVision Holz- Siegel satin

Melting point/freezing point	No data available
Initial boiling point and boiling range	100 °C
Flash point	Not applicable
Evaporation rate	not determined
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	No data available
Lower explosion limit / Lower flammability limit	No data available
Vapour pressure	No data available
Vapour density	No data available
Density	ca. 1,05 g/cm <sup>3</sup>
Solubility(ies)	
Water solubility	miscible
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity	
Viscosity, dynamic	ca. 1.295 mPa.s
Explosive properties	Not explosive
Oxidizing properties	Not applicable

## 9.2 Other information

Flow time	No data available
-----------	-------------------

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	This information is not available.
---------------------	------------------------------------

# SÜDWEST AquaVision Holz- Siegel satin

## 10.4 Conditions to avoid

Conditions to avoid Stable under recommended storage and handling conditions (see section 7).

## 10.5 Incompatible materials

Materials to avoid Strong acids and strong bases  
Strong oxidizing agents

## 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

Acute inhalation toxicity Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

#### Components:

##### **2-butoxyethanol:**

Acute oral toxicity Acute toxicity estimate: 1.200 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC)  
No. 1272/2008

Acute inhalation toxicity Harmful if inhaled.

Acute dermal toxicity Harmful in contact with skin.

#### **reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

Acute oral toxicity Toxic if swallowed.

Acute inhalation toxicity Fatal if inhaled.

Acute dermal toxicity Fatal in contact with skin.

#### **Skin corrosion/irritation**

##### Product:

Based on available data, the classification criteria are not met.

#### Components:

##### **2-butoxyethanol:**



# SÜDWEST AquaVision Holz- Siegel satin

Causes skin irritation.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes severe skin burns and eye damage.

## Serious eye damage/eye irritation

### Product:

Based on available data, the classification criteria are not met.

### Components:

#### 2-butoxyethanol:

Causes serious eye irritation.

#### 2-(2-butoxyethoxy)ethanol:

Causes serious eye irritation.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes serious eye damage.

## Respiratory or skin sensitisation

### Product:

Based on available data, the classification criteria are not met.

### Components:

#### adipohydrazide:

May cause an allergic skin reaction.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

May cause an allergic skin reaction.

## Germ cell mutagenicity

### Product:

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

## Carcinogenicity

### Product:

Based on available data, the classification criteria are not met.

## Reproductive toxicity

### Product:

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

## STOT - single exposure

### Product:

Based on available data, the classification criteria are not met.

# SÜDWEST AquaVision Holz- Siegel satin

## STOT - repeated exposure

### Product:

Based on available data, the classification criteria are not met.

## Aspiration toxicity

### Product:

Based on available data, the classification criteria are not met.

## Further information

### Product:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## Further information

### Product:

Remarks : The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### Product:

Toxicity to fish No data available

#### Components:

##### adipohydrazide:

Toxicity to algae/aquatic plants EC50 (Pseudokirchneriella subcapitata (green algae)): 9,6 mg/l  
Exposure time: 72 h

##### reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0,19 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates EC50 (Daphnia (water flea)): 0,12 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants EC50 (Skeletonema costatum (marine diatom)): 0,0052 mg/l  
Exposure time: 48 h

# SÜDWEST AquaVision Holz- Siegel satin

NOEC (Skeletonema costatum (marine diatom)): 0,00049 mg/l  
Exposure time: 48 h

M-Factor (Acute aquatic toxicity) 100

Toxicity to fish (Chronic toxicity) NOEC: 0,098 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)  
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) NOEC: 0,004 mg/l  
Exposure time: 21 d  
Species: Daphnia (water flea)

M-Factor (Chronic aquatic toxicity) 100

## 12.2 Persistence and degradability

### Product:

Biodegradability No data available

### Components:

#### adipohydrazide:

Biodegradability Biodegradation: 60 %  
Exposure time: 28 d  
Method: OECD Test Guideline 302B

**reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

Biodegradability not rapidly degradable

## 12.3 Bioaccumulative potential

### Product:

Bioaccumulation No data available

### Components:

#### 2-(2-butoxyethoxy)ethanol:

Partition coefficient: n-octanol/water log Pow: 0,56

## 12.4 Mobility in soil

### Product:

Mobility No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation

# SÜDWEST AquaVision Holz- Siegel satin

(EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### Product:

Additional ecological information

Do not allow product to enter into ground water, bodies of water or sewage systems.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Product	The user is responsible for proper coding and marking of any waste. Dispose of as special waste in compliance with local and national regulations. Partial and residual quantities can be reused.
Contaminated packaging	Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.
Waste key for the unused product	08 01 12 Waste paint and varnish other than those covered by 08 01 11

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number or ID number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

### 14.5 Environmental hazards

### 14.6 Special precautions for user

Remarks This information is not available.

### 14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

# SÜDWEST AquaVision Holz- Siegel satin

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC  
Directive 2010/75/EU 4,2 %

VOC  
Directive 2004/42/EC 5,2 %  
54,0 g/l

EU limit value for this product (cat. A/i) :140 g/l This product contains max140 g/lVOC.

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals Not applicable

Other regulations Comply with the statutory regulations on health and safety at work.

### 15.2 Chemical safety assessment

This information is not available.

## SECTION 16: OTHER INFORMATION

**Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.**

### Full text of H-Statements

H301 : Toxic if swallowed.  
H302 : Harmful if swallowed.  
H310 : Fatal in contact with skin.  
H312 : Harmful in contact with skin.  
H314 : Causes severe skin burns and eye damage.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H318 : Causes serious eye damage.  
H319 : Causes serious eye irritation.  
H330 : Fatal if inhaled.

# SÜDWEST AquaVision Holz- Siegel satin

H332	: Harmful if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

## Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - European Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## Further information

Other information	It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.
-------------------	---

# SÜDWEST AquaVision Holz- Siegel satin

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de