



# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Skin sensitisation, Category 1	H317: May cause an allergic skin reaction.
Specific target organ toxicity - single exposure, Category 3, Central nervous system	H336: May cause drowsiness or dizziness.
Specific target organ toxicity - single exposure, Category 3, Respiratory system	H335: May cause respiratory irritation.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Aspiration hazard, Category 1	H304: May be fatal if swallowed and enters airways.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

### 2.2 Label elements

#### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H373 May cause damage to organs through prolonged or

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

repeated exposure.

H412 Harmful to aquatic life with long lasting effects.

Precautionary statements : **Prevention:**  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
 P280 Wear protective gloves/ eye protection/ face protection.  
 P284 Wear respiratory protection.  
**Response:**  
 P301 + P312 + P330 IF SWALLOWED: Call a POISON CENTER/ doctor if you feel unwell. Rinse mouth.  
 P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
 P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
**Disposal:**  
 P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

### Hazardous components which must be listed on the label:

n-butyl acetate

Hydrocarbons, C9, aromatics

xylene

Hexamethylene diisocyanate, homopolymer

### 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	≥ 30 - < 50
Hydrocarbons, C9, aromatics	64742-95-6	Asp. Tox. 1; H304	≥ 20 - < 25

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

	265-199-0 649-356-00-4 01-2119455851-35-XXXX	Flam. Liq. 3; H226 STOT SE 3; H335, H336 Aquatic Chronic 2; H411  EUH066	
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	≥ 20 - < 30
Hexamethylene diisocyanate, homopolymer	Not Assigned 500-060-2 01-2119485796-17-XXXX	Acute Tox. 4; H332 Skin Sens. 1; H317 STOT SE 3; H335	≥ 10 - < 20
4-isocyanatosulphonyltoluene	4083-64-1 223-810-8 615-012-00-7 01-2119980050-47-XXXX	Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 EUH014  specific concentration limit Eye Irrit. 2 ≥ 5 % STOT SE 3 ≥ 5 % Skin Irrit. 2 ≥ 5 %	≥ 0,1 - < 1

For explanation of abbreviations see section 16.

### SECTION 4: FIRST AID MEASURES

#### 4.1 Description of first aid measures

General advice	When symptoms persist or in all cases of doubt seek medical advice. First aider needs to protect himself.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Consult a physician after significant exposure.
Skin contact	Take off contaminated clothing and shoes immediately. Take off contaminated clothing and wash it before reuse. Wash skin thoroughly with soap and water or use recognized skin cleanser.

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

Do NOT use solvents or thinners.  
If symptoms persist, call a physician.

Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician. Eye rinsing bottle must be kept immediately to hand.
Ingestion	Never give anything by mouth to an unconscious person. Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention.

#### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms	Contact with eyes or skin causes irritation. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
----------	--

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	Treat symptomatically. When symptoms persist or in all cases of doubt seek medical advice.
-----------	---

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

Suitable extinguishing media	CO <sub>2</sub> , extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
------------------------------	---

Unsuitable extinguishing media	High volume water jet
--------------------------------	-----------------------

<b>5.2 Special hazards arising from the substance or mixture</b>	Fire may cause evolution of: Carbon monoxide Carbon dioxide (CO <sub>2</sub> ) Nitrogen oxides (NO <sub>x</sub> )
--	--

<b>5.3 Advice for firefighters</b>	In the event of fire, wear self-contained breathing apparatus. Complete suit protecting against chemicals
------------------------------------	--

Additional advice	Use water spray to cool unopened containers. Water for fire fighting must not be emptied into drains, earth or waters. Contaminated water and earth must be disposed of according to official local regulations.
-------------------	---

### SECTION 6: ACCIDENTAL RELEASE MEASURES

<b>6.1 Personal precautions, protective equipment and emergency procedures</b>	Do not breathe fumes / aerosol Do not get in eyes, on skin, or on clothing. Use personal protective equipment. Ensure adequate ventilation.
--	--

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

	Prevent unauthorized access.
<b>6.2 Environmental precautions</b>	Prevent seepage into sewage system, workpits and cellars. Do not allow contact with soil, surface or ground water. If the product contaminates rivers and lakes or drains inform respective authorities.
<b>6.3 Methods and material for containment and cleaning up</b>	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Subsequently put in the waste container. Do not seal ( CO <sub>2</sub> may be given off ) Clean contaminated surface thoroughly. Suitable cleaning agents Water Should not be released into the environment.
<b>6.4 Reference to other sections</b>	Refer to protective measures listed in sections 7 and 8.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Advice on safe handling	Avoid contact with skin and eyes. Do not breathe vapours or spray mist. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Comply with the statutory regulations on health and safety at work. Do not re-use empty containers.
Hygiene measures	Take off all contaminated clothing immediately. Keep working clothes separately. Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash hands before breaks and immediately after handling the product. After washing hands, replenish lost skin oil by means of oily skin ointment. When using do not eat, drink or smoke.

#### 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	Keep out of reach of children. Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Protect from frost, heat and sunlight. Keep in a dry place.
---	---

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

Advice on common storage      Keep away from oxidizing agents, strongly acid or alkaline materials, as well as of amines, alcohols and water.

**7.3 Specific end use(s)**      For further information, see also Technical Data Sheet for the product.

### SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

#### 8.1 Control parameters

##### Exposure limit(s)

Components		CAS-No.
Basis	Type:	Control parameters
n-butyl acetate		123-86-4
2019/1831/EU	Short term exposure limit	723 mg/m <sup>3</sup>
2019/1831/EU	Short term exposure limit	150 ppm
Additional advice:	Indicative	
2019/1831/EU	Limit Value - eight hours	241 mg/m <sup>3</sup>
2019/1831/EU	Limit Value - eight hours	50 ppm
Additional advice:	Indicative	
xylene		1330-20-7
2000/39/EC	Limit Value - eight hours	221 mg/m <sup>3</sup>
2000/39/EC	Limit Value - eight hours	50 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	
2000/39/EC	Short term exposure limit	442 mg/m <sup>3</sup>
2000/39/EC	Short term exposure limit	100 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	

The lists that were valid during the creation were used as basis.

#### 8.2 Exposure controls

##### Appropriate engineering controls

Ensure good ventilation; if possible, use / install internal extractor equipment.  
Washing facilities / water for rinsing eyes and skin should be available.

##### Individual protection measures, such as personal protective equipment

- a) Eye/face protection      Safety glasses with side-shields conforming to EN166
- b) Skin protection  
Hand protection      Wearing time: < 60 min  
Minimum thickness: 0,4 mm

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

Gloves made of the following materials are suitable as protection from splashes:

Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent.

Wetted gloves must be disposed of immediately!

Wearing time: > 480 min

Minimum thickness: 0,7 mm

Gloves in the following material can be used for prolonged contact up to max. 8 hours:

Fluorocarbon rubber gloves eg. KCL 890 Vitoject® (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equal.

Dispose of wetted gloves at the end of the shift!

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.

Cotton undergloves are recommendable when wearing protective gloves!

To avoid skin problems reduce the wearing of gloves to the required minimum.

Only use chemical-protective gloves with CE-labelling of category III.

### Body Protection

Impervious clothing

If splashes are likely to occur, wear:

Solvent-resistant apron and boots

### c) Respiratory protection

For brief exposure or low level concentrations use a respiratory filter; for more intense or longer exposure use a self-contained respiratory protective device.

Respiratory filter for brief exposure:

Combination filter A-P2

Respiratory protection complying with EN 14387.

### General precautions and other information

The instructions for the personal protective equipment apply to the handling of both individual components and of the ready-to-use mixture.

### Environmental exposure controls

#### General advice

Prevent seepage into sewage system, workpits and cellars.

Do not allow contact with soil, surface or ground water.

If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

# SÜDWEST 2K-All-Grund Streichlack-Zusatz

Appearance	liquid
Colour	Yellowish
Odour	characteristic
Odour Threshold	No data available
pH	8 - 9,9 (23 °C) Concentration: 1 % hydrolyses
Melting point/freezing point	No data available
Initial boiling point and boiling range	> 124 °C
Flash point	32 °C
Evaporation rate	not determined
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	7,5 %(V) Upper explosion limit
Lower explosion limit / Lower flammability limit	0,6 %(V) Lower explosion limit
Vapour pressure	13 hPa (20 °C)
Vapour density	No data available
Density	ca. 0,9 - 0,95 g/cm <sup>3</sup>
Solubility(ies) Water solubility	insoluble
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity Viscosity, dynamic	ca. 80 mPa.s (20 °C)
Viscosity, kinematic	ca. 86,2 mm <sup>2</sup> /s (40 °C)
Explosive properties	Not explosive In use may form flammable/explosive vapour-air mixture.
Oxidizing properties	Not applicable

# SÜDWEST 2K-All-Grund Streichlack-Zusatz

## 9.2 Other information

Flow time No data available

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions Amines and alcohols cause exothermic reactions.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.  
With water (moisture): CO<sub>2</sub> is produced; pressure may build up inside closed containers (danger of bursting)

### 10.4 Conditions to avoid

Conditions to avoid Direct sources of heat.  
Strong sunlight for prolonged periods.

### 10.5 Incompatible materials

Materials to avoid Acids and bases  
Amines and alcohols cause exothermic reactions.

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.  
In case of fire hazardous decomposition products may be produced such as:  
Isocyanates  
Hydrogen cyanide (hydrocyanic acid)

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity Based on available data, the classification criteria are not met.

Acute inhalation toxicity Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

Acute dermal toxicity

Acute toxicity estimate: > 2.000 mg/kg  
Method: Calculation method

**Components:**

**xylene:**

Acute inhalation toxicity

LC50 (Rat): 11 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity

Harmful in contact with skin.

**Hexamethylene diisocyanate, homopolymer:**

Acute inhalation toxicity

LC50 (Rat): 0,1 - 0,5 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403

**Skin corrosion/irritation**

**Product:**

Causes skin irritation.

**Components:**

**n-butyl acetate:**

Repeated exposure may cause skin dryness or cracking.

**Hydrocarbons, C9, aromatics:**

Repeated exposure may cause skin dryness or cracking.

**xylene:**

Causes skin irritation.

**4-isocyanatosulphonyltoluene:**

Causes skin irritation.

**Serious eye damage/eye irritation**

**Product:**

Causes serious eye irritation.

**Components:**

**xylene:**

Causes serious eye irritation.

**4-isocyanatosulphonyltoluene:**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

**Product:**

May cause an allergic skin reaction.  
Does not cause respiratory sensitisation.

**Components:**

**Hexamethylene diisocyanate, homopolymer:**

Species

Mouse

Method

OECD Test Guideline 429

May cause an allergic skin reaction.

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

**4-isocyanatosulphonyltoluene:**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

**Carcinogenicity****Product:**

Based on available data, the classification criteria are not met.

**Reproductive toxicity****Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

**STOT - single exposure****Product:**

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

**Components:****n-butyl acetate:**

Exposure routes

inhalation (vapour)

Assessment

May cause drowsiness or dizziness.

**Hydrocarbons, C9, aromatics:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

**xylene:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation.

**Hexamethylene diisocyanate, homopolymer:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation.

**4-isocyanatosulphonyltoluene:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation.

**STOT - repeated exposure****Product:**

Assessment

May cause damage to organs through prolonged or repeated exposure.

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

**Components:****xylene:**

Assessment

May cause damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Product:**

May be fatal if swallowed and enters airways.

**Components:****Hydrocarbons, C9, aromatics:**

May be fatal if swallowed and enters airways.

**xylene:**

May be fatal if swallowed and enters airways.

**Toxicology, Metabolism, Distribution****Further information****Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

**11.2 Information on other hazards****Endocrine disrupting properties****Product:**

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Experience with human exposure****Product:**

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

**Further information****Product:**

Remarks

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive

# SÜDWEST 2K-All-Grund Streichlack-Zusatz

1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

**Product:**

Toxicity to fish No data available

**Components:**

**Hydrocarbons, C9, aromatics:**

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 9,22 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other  
aquatic invertebrates

EC50 (Daphnia magna (Water flea)): 6,14 mg/l  
Exposure time: 48 h

### 12.2 Persistence and degradability

**Product:**

Biodegradability No data available

**Components:**

**n-butyl acetate:**

Biodegradability rapidly degradable  
Biodegradation: > 90 %  
Exposure time: 28 d

**Hydrocarbons, C9, aromatics:**

Biodegradability rapidly degradable

### 12.3 Bioaccumulative potential

**Product:**

Bioaccumulation No data available

**Components:**

**n-butyl acetate:**

Partition coefficient: n-  
octanol/water log Pow: 2,3  
Method: OECD Test Guideline 117

**xylene:**

Partition coefficient: n-  
octanol/water log Pow: > 3

### 12.4 Mobility in soil

**Product:**

Mobility No data available

### 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

### 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### 12.7 Other adverse effects

**Product:**

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.  
Harmful to aquatic life with long lasting effects.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Product	The user is responsible for proper coding and marking of any waste. When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste" Unhardened product residues should be disposed of under the recommended waste code number.
Contaminated packaging	Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.
Waste key for the unused product	08 01 11* waste paint and varnish containing organic solvents or other hazardous substances  (* ) hazardous waste in terms of the European directive 2008/98/EG

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number or ID number

ADR	1866
IMDG	1866
IATA	1866

### 14.2 UN proper shipping name

ADR	RESIN SOLUTION
IMDG	RESIN SOLUTION

# SÜDWEST 2K-All-Grund Streichlack-Zusatz

IATA Resin solution

## 14.3 Transport hazard class(es)

ADR 3  
IMDG 3  
IATA 3

## 14.4 Packing group

### ADR

Packing group III  
Classification Code F1  
Hazard Identification Number 30  
Labels 3  
Tunnel restriction code (D/E)

### IMDG

Packaging group III  
Labels 3  
EmS number F-E, S-E

### IATA

Packaging group III  
Labels 3

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

Remarks This information is not available.

## 14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

## SECTION 15: REGULATORY INFORMATION

# SÜDWEST 2K-All-Grund Streichlack-Zusatz

## 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC  
Directive 2010/75/EU 81,4 %

VOC  
Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EC) No 649/2012  
of the European Parliament  
and the Council concerning the  
export and import of dangerous  
chemicals Not applicable

Further notes For further information, see also Technical Data Sheet for the product.

## 15.2 Chemical safety assessment

The results of the chemical safety assessment are documented in the safety data sheet.

## SECTION 16: OTHER INFORMATION

**Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.**

### Full text of H-Statements

H226 : Flammable liquid and vapour.  
H304 : May be fatal if swallowed and enters airways.  
H312 : Harmful in contact with skin.  
H315 : Causes skin irritation.  
H317 : May cause an allergic skin reaction.  
H319 : Causes serious eye irritation.  
H332 : Harmful if inhaled.  
H334 : May cause allergy or asthma symptoms or breathing difficulties if inhaled.

# SÜDWEST 2K-All-Grund

## Streichlack-Zusatz

H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.
H411	: Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitisation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

### Further information

Other information	It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your
-------------------	---

# SÜDWEST 2K-All-Grund Streichlack-Zusatz

understanding in this matter.

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de