



# SÜDWEST 2K-Polyester- Füllspachtel

Skin irritation, Category 2	H315: Causes skin irritation.
Eye irritation, Category 2	H319: Causes serious eye irritation.
Reproductive toxicity, Category 2	H361d: Suspected of damaging the unborn child.
Specific target organ toxicity - repeated exposure, Category 2	H373: May cause damage to organs through prolonged or repeated exposure.
Long-term (chronic) aquatic hazard, Category 3	H412: Harmful to aquatic life with long lasting effects.

## 2.2 Label elements

### Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour. H315 Causes skin irritation. H319 Causes serious eye irritation. H361d Suspected of damaging the unborn child. H373 May cause damage to organs through prolonged or repeated exposure. H412 Harmful to aquatic life with long lasting effects.
Precautionary statements	:	P101 If medical advice is needed, have product container or label at hand. P102 Keep out of reach of children. <b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P260 Do not breathe vapours. P280 Wear protective gloves/ eye protection/ face protection. <b>Response:</b> P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. P314 Get medical advice/ attention if you feel unwell. P303 + P361 + P353 IF ON SKIN (or hair): Take off

# SÜDWEST 2K-Polyester- Füllspachtel

immediately all contaminated clothing. Rinse skin with water or shower.

**Disposal:**

P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

**Hazardous components which must be listed on the label:**

styrene

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

**3.2 Mixtures**

**Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
styrene	100-42-5 202-851-5 601-026-00-0 01-2119457861-32-XXXX	Flam. Liq. 3; H226 STOT RE 1; H372 Asp. Tox. 1; H304 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 Repr. 2; H361d Aquatic Chronic 3; H412	< 10
vinyltoluene	25013-15-4 246-562-2 01-2119622074-50-XXXX	Flam. Liq. 3; H226 Asp. Tox. 1; H304 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319	≥ 1 - < 5
trizinc bis(orthophosphate)	7779-90-0 231-944-3 030-011-00-6 01-2119485044-40-XXXX	Aquatic Acute 1; H400 Aquatic Chronic 1; H410  M-Factor (Acute aquatic toxicity): 1 M-Factor (Chronic aquatic toxicity): 1	≥ 1 - < 5

For explanation of abbreviations see section 16.

# SÜDWEST 2K-Polyester- Füllspachtel

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

General advice	When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Rinse mouth with water. If swallowed, seek medical advice immediately and show this container or label. Keep at rest. Do NOT induce vomiting.

### 4.2 Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
----------	---------------------------

### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment	Treat symptomatically. If ingested, irrigate the stomach using activated charcoal in addition.
-----------	---

## SECTION 5: FIREFIGHTING MEASURES

### 5.1 Extinguishing media

Suitable extinguishing media	CO <sub>2</sub> , extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Unsuitable extinguishing	High volume water jet

# SÜDWEST 2K-Polyester- Füllspachtel

media

## 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.

## 5.3 Advice for firefighters

In the event of fire, wear self-contained breathing apparatus.  
Full protective suit  
Fight fire with normal precautions from a reasonable distance.

Additional advice

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1 Personal precautions, protective equipment and emergency procedures

Remove all sources of ignition.  
Ensure adequate ventilation.  
Do not breathe vapour.  
Prevent unauthorized access.

### 6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

### 6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Clean with detergents. Avoid solvents.  
Clean contaminated surface thoroughly.  
Dispose of contaminated material as waste according to item 13.

### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

## SECTION 7: HANDLING AND STORAGE

### 7.1 Precautions for safe handling

Advice on safe handling

Comply with the statutory regulations on health and safety at work.  
Avoid formation of aerosol.  
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
All metal parts of the mixing and processing equipment must be earthed.  
Operators should wear antistatic footwear and clothing. No

# SÜDWEST 2K-Polyester- Füllspachtel

sparking tools should be used.

## Hygiene measures

Do not breathe spray, vapour.  
Take off immediately all contaminated clothing.  
Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
After washing hands, replenish lost skin oil by means of oily skin ointment.  
When using do not eat, drink or smoke.

## 7.2 Conditions for safe storage, including any incompatibilities

### Requirements for storage areas and containers

Store in original container.  
Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nonsmoking.  
Prevent unauthorized access.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Protect from frost, heat and sunlight.

### Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Take measures to prevent the build up of electrostatic charge.

### Advice on common storage

Keep away from combustible materials.  
Keep away from food, drink and animal feedingstuffs.  
Keep away from oxidizing agents and strongly acid or alkaline materials.

## 7.3 Specific end use(s)

For further information, see also Technical Data Sheet for the product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

The lists that were valid during the creation were used as basis. Contains no substances with occupational exposure limit values.

### 8.2 Exposure controls

#### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory protection must be worn.

Washing facilities / water for rinsing eyes and skin should be available.

# SÜDWEST 2K-Polyester- Füllspachtel

## Individual protection measures, such as personal protective equipment

- a) Eye/face protection                      Safety glasses with side-shields conforming to EN166
- b) Skin protection  
Hand protection                              Wearing time: < 60 min  
Minimum thickness: 0,4 mm  
Gloves made of the following materials are suitable as protection from splashes:  
Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent.  
Wetted gloves must be disposed of immediately!
- Wearing time: > 480 min  
Minimum thickness: 0,7 mm  
Gloves in the following material can be used for prolonged contact up to max. 8 hours:  
  
Fluorocarbon rubber gloves eg. KCL 890 Vitoject® (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equal.  
Dispose of wetted gloves at the end of the shift!
- The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.  
Cotton undergloves are recommendable when wearing protective gloves!  
To avoid skin problems reduce the wearing of gloves to the required minimum.  
Only use chemical-protective gloves with CE-labelling of category III.
- Body Protection                              Preventive skin protection  
Long sleeved clothing  
Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.
- c) Respiratory protection                      When workers are facing concentrations above the occupational exposure limit values they must use appropriate certified respirators.  
In case of inadequate ventilation wear respiratory protection.  
Do not breathe in dust when grinding.  
Combination filter A-P2  
Respiratory protection complying with EN 14387.

## Environmental exposure controls

- General advice                              The product should not be allowed to enter drains, water courses or the soil.

# SÜDWEST 2K-Polyester- Füllspachtel

If the product contaminates rivers and lakes or drains inform respective authorities.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Appearance	viscous
Colour	white
Odour	solvent-like
Odour Threshold	No data available
pH	Not applicable
Melting point/freezing point	No data available
Initial boiling point and boiling range	145 °C
Flash point	31 °C
Evaporation rate	not applicable
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	8,9 %(V) Upper explosion limit
Lower explosion limit / Lower flammability limit	1,2 %(V) Lower explosion limit
Vapour pressure	6 hPa (20 °C)
Vapour density	No data available
Density	ca. 1,98 g/cm <sup>3</sup> (20 °C)
Solubility(ies) Water solubility	immiscible
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity Viscosity, dynamic	No data available

# SÜDWEST 2K-Polyester- Füllspachtel

Viscosity, kinematic	No data available
Explosive properties	In use may form flammable/explosive vapour-air mixture.
Oxidizing properties	Not applicable

## 9.2 Other information

Ignition temperature	480 °C
Flow time	No data available

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions	No dangerous reaction known under conditions of normal use. Polymerisation can occur. Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions. Exothermic reaction with peroxides
---------------------	--

### 10.4 Conditions to avoid

Conditions to avoid	Direct sources of heat. Strong sunlight for prolonged periods.
---------------------	---

### 10.5 Incompatible materials

Materials to avoid	Strong acids and strong bases Strong oxidizing agents
--------------------	--

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity	Based on available data, the classification criteria are not met.
---------------------	---

Acute inhalation toxicity	Acute toxicity estimate: > 20 mg/l
---------------------------	------------------------------------

# SÜDWEST 2K-Polyester- Füllspachtel

Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity

Based on available data, the classification criteria are not met.

**Components:**

**styrene:**

Acute inhalation toxicity

LC50 (Rat): 11,8 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

**vinyltoluene:**

Acute inhalation toxicity

Harmful if inhaled.

**Skin corrosion/irritation**

**Product:**

Causes skin irritation.

**Components:**

**styrene:**

Causes skin irritation.

**Serious eye damage/eye irritation**

**Product:**

Causes serious eye irritation.

**Components:**

**styrene:**

Causes serious eye irritation.

**Respiratory or skin sensitisation**

**Product:**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity**

**Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

**Carcinogenicity**

**Product:**

Based on available data, the classification criteria are not met.

**Reproductive toxicity**

**Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Suspected of damaging the unborn child.

**Components:**

**styrene:**

Developmental Toxicity

Suspected of damaging the unborn child.

# SÜDWEST 2K-Polyester- Füllspachtel

**STOT - single exposure****Product:**

Based on available data, the classification criteria are not met.

**Components:****styrene:**

Assessment

May cause respiratory irritation.

**STOT - repeated exposure****Product:**

Assessment

May cause damage to organs through prolonged or repeated exposure.

**Components:****styrene:**

Assessment

Causes damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Product:**

Based on available data, the classification criteria are not met.

**Components:****styrene:**

May be fatal if swallowed and enters airways.

**Toxicology, Metabolism, Distribution****Further information****Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

**11.2 Information on other hazards****Endocrine disrupting properties****Product:**

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Experience with human exposure****Product:**

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Long-term or repeated contact with the product leads to

# SÜDWEST 2K-Polyester- Füllspachtel

degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

## Further information

### Product:

Remarks

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### Product:

Toxicity to fish

No data available

#### Components:

#### trizinc bis(orthophosphate):

Toxicity to fish

LC50 (Oncorhynchus mykiss (rainbow trout)): 0,33 - 6,06 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 2,34 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants

EC50 (Scenedesmus capricornutum (fresh water algae)): 0,32 mg/l  
Exposure time: 72 h

M-Factor (Acute aquatic toxicity)

1

M-Factor (Chronic aquatic toxicity)

1

### 12.2 Persistence and degradability

#### Product:

Biodegradability

No data available

### 12.3 Bioaccumulative potential

#### Product:

Bioaccumulation

No data available

#### Components:

#### trizinc bis(orthophosphate):

Bioaccumulation

Does not bioaccumulate.

### 12.4 Mobility in soil

#### Product:

Mobility

No data available

# SÜDWEST 2K-Polyester- Füllspachtel

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Endocrine disrupting properties

### Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### Product:

Additional ecological information

Do not allow product to enter into ground water, bodies of water or sewage systems.  
Harmful to aquatic life with long lasting effects.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Product

The user is responsible for proper coding and marking of any waste.  
When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste"  
Partial and residual quantities can be reused.  
Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.

Contaminated packaging

Empty packaging should be recycled through disposal systems.

Waste key for the unused product

20 01 27\* paint, inks, adhesives and resins containing hazardous substances

(\* ) hazardous waste in terms of the European directive 2008/98/EG

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number or ID number

ADR 3269

IMDG 3269

# SÜDWEST 2K-Polyester- Füllspachtel

IATA 3269

## 14.2 UN proper shipping name

ADR POLYESTER RESIN KIT

IMDG POLYESTER RESIN KIT

IATA Polyester resin kit

## 14.3 Transport hazard class(es)

ADR 3

IMDG 3

IATA 3

## 14.4 Packing group

### ADR

Packing group III

Classification Code F3

Labels 3

Tunnel restriction code (E)

### IMDG

Packaging group III

Labels 3

EmS number F-E, S-D

### IATA

Packaging group III

Labels 3

## 14.5 Environmental hazards

### ADR

Environmentally hazardous : no

### IMDG

Marine pollutant : no

## 14.6 Special precautions for user

Remarks This information is not available.

# SÜDWEST 2K-Polyester- Füllspachtel

## 14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

### SECTION 15: REGULATORY INFORMATION

#### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC  
Directive 2004/42/EC  
150 g/l

VOC  
Directive 2010/75/EU  
238 g/l

EU limit value for this product (cat. B/b) :250 g/lThis product contains max250 g/lVOC.

Regulation (EC) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals Not applicable

Other regulations Comply with the statutory regulations on health and safety at work.  
Take note of Dir 94/33/EC on the protection of young people at work.  
Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

#### 15.2 Chemical safety assessment

This information is not available.

### SECTION 16: OTHER INFORMATION

**Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.**

# SÜDWEST 2K-Polyester- Füllspachtel

## Full text of H-Statements

H226	: Flammable liquid and vapour.
H304	: May be fatal if swallowed and enters airways.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H361d	: Suspected of damaging the unborn child.
H372	: Causes damage to organs through prolonged or repeated exposure.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H412	: Harmful to aquatic life with long lasting effects.

## Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Repr.	: Reproductive toxicity
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very

# SÜDWEST 2K-Polyester- Füllspachtel

High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## Further information

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de

# SÜDWEST 2K-Polyester- Füllspachtel