

## SAFETY DATA SHEET

# SÜDWEST AquaVision Holz-Siegel glänzend

Ref.	130000007278/D
Rev. no.	1.9
Revision Date	04.03.2026
Print Date	14.03.2026

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Trade name SÜDWEST AquaVision Holz-Siegel glänzend

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Wood coating  
Clear coating material, Varnish

Uses advised against This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG  
Iggelheimer Str. 13  
D - 67459 Böhl-Iggelheim  
Telephone: +49 6324/709-0  
info@suedwest.de  
www.suedwest.de

E-mail address of person responsible for the SDS European Union sdb@suedwest.de

#### 1.4 Emergency telephone number European Union

Phone: +44 (0) 1865 407333

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

**||** No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

**||** Precautionary statements : **Prevention:**  
P273 Avoid release to the environment.

##### Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains adipohydrazide, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1), 3-aminomethyl-

# SÜDWEST AquaVision Holz- Siegel glänzend

3,5,5-trimethylcyclohexylamine. May produce an allergic reaction.

These are preservatives.  
Avoid contact with the skin and the eyes.

## 2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.2 Mixtures

#### Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
3-butoxypropan-2-ol	5131-66-8 225-878-4 603-052-00-8 01-2119475527-28-XXXX	Eye Irrit. 2; H319 Skin Irrit. 2; H315	≥ 1 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 01-2119475104-44-XXXX	Eye Irrit. 2; H319	≥ 1 - < 10
adipohydrazide	1071-93-8 213-999-5 01-2119962900-36-XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	≥ 0,25 - < 1
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1)	55965-84-9  613-167-00-5 01-2120764691-48-XXXX	Acute Tox. 2; H330 Acute Tox. 2; H310 Acute Tox. 3; H301 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Eye Dam. 1; H318 EUH071  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100  specific concentration limit Skin Corr. 1C ≥ 0,6 %	≥ 0,0002 - < 0,0015

# SÜDWEST AquaVision Holz- Siegel glänzend

		Skin Irrit. 2 0,06 - < 0,6 % Eye Irrit. 2 0,06 - < 0,6 % Skin Sens. 1A ≥ 0,0015 % Eye Dam. 1 ≥ 0,6 %	
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 612-067-00-9 01-2119514687-32-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317  <hr/> specific concentration limit Skin Sens. 1A ≥ 0,001 %  <hr/> Acute toxicity estimate  Acute oral toxicity: 1.030 mg/kg	< 0,001

For explanation of abbreviations see section 16.

## SECTION 4: FIRST AID MEASURES

### 4.1 Description of first aid measures

General advice	In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention. Keep at rest.

### 4.2 Most important symptoms and effects, both acute and delayed

# SÜDWEST AquaVision Holz- Siegel glänzend

Symptoms No information available.

#### 4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.  
No information available.

### SECTION 5: FIREFIGHTING MEASURES

#### 5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical  
Water spray

Unsuitable extinguishing media High volume water jet

#### 5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
Exposure to decomposition products may be a hazard to health.

#### 5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

#### Additional advice

Use water spray to cool unopened containers.  
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.  
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

### SECTION 6: ACCIDENTAL RELEASE MEASURES

#### 6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.  
Do not breathe vapour.

#### 6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

#### 6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Clean with detergents. Avoid solvents.  
Clean contaminated surface thoroughly.  
Dispose of contaminated material as waste according to item 13.

#### 6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

### SECTION 7: HANDLING AND STORAGE

#### 7.1 Precautions for safe handling

Advice on safe handling Avoid contact with skin and eyes.

# SÜDWEST AquaVision Holz- Siegel glänzend

	Prevent unauthorized access. Provide sufficient air exchange and/or exhaust in work rooms. Comply with the statutory regulations on health and safety at work.
Hygiene measures	Wash hands before breaks and at the end of workday. When using do not eat, drink or smoke. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

## 7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Observe label precautions. Protect from frost, heat and sunlight.
Advice on common storage	Keep away from oxidizing agents and strongly acid or alkaline materials. Keep away from food, drink and animal feedingstuffs.

**7.3 Specific end use(s)** For further information, see also Technical Data Sheet for the product.

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1 Control parameters

#### Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-(2-butoxyethoxy)ethanol	112-34-5	TWA	10 ppm 67,5 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative			
		STEL	15 ppm 101,2 mg/m <sup>3</sup>	2006/15/EC
	Further information: Indicative			

The lists that were valid during the creation were used as basis.

|| Monitoring procedures for the assessment of workplace exposure: standard EN 482

### 8.2 Exposure controls

#### Engineering measures

Ensure good ventilation; if possible, use / install internal extractor equipment.

#### Personal protective equipment

Eye/face protection : Wear protective goggles for protection against splashed liquid.

Safety glasses with side-shields conforming to EN166

# SÜDWEST AquaVision Holz- Siegel glänzend

## Hand protection

Material	:	Nitrile rubber
Break through time	:	480 min
Glove thickness	:	0,4 mm

Remarks : Recommended preventive skin protection Before starting work, apply water-resistant skincare preparations to exposed skin areas. Protective gloves should be worn in case of skin contact during preparation and application.

Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent. Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Skin and body protection : Work clothes  
Skin should be washed after contact.  
Do NOT use solvents or thinners.

Respiratory protection : No personal respiratory protective equipment normally required.  
In case of inadequate ventilation wear respiratory protection.  
Employees involved in spraying work or in the immediate vicinity of such work should use a P2 particle filter against spray fog.  
Respiratory protection complying with EN 143.

## Environmental exposure controls

Air	:	Avoid release to the environment.
Soil	:	Avoid subsoil penetration.
Water	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

# SÜDWEST AquaVision Holz- Siegel glänzend

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	clear
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	Not applicable
Decomposition temperature	:	No data available

# SÜDWEST AquaVision Holz- Siegel glänzend

pH : ca. 8,2

Viscosity  
Viscosity, dynamic : ca. 470 mPa.s (20 °C)

Flow time : No data available

Solubility(ies)  
Water solubility : miscible

Partition coefficient: n-  
octanol/water : not determined

Vapour pressure : No data available

Density : ca. 1,04 g/cm<sup>3</sup>

Relative vapour density : No data available

## 9.2 Other information

Explosives : Not explosive

Oxidizing properties : Not applicable

# SÜDWEST AquaVision Holz- Siegel glänzend

Flammability (liquids) : Not applicable

Self-ignition : not auto-flammable

Evaporation rate : not applicable

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions : This information is not available.

### 10.4 Conditions to avoid

Conditions to avoid : Stable under recommended storage and handling conditions (see section 7).

### 10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases  
Strong oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity : Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Based on available data, the classification criteria are not met.

Acute dermal toxicity : Based on available data, the classification criteria are not met.

# SÜDWEST AquaVision Holz- Siegel glänzend

**Components:**

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Acute oral toxicity Toxic if swallowed.

Acute inhalation toxicity Assessment: Corrosive to the respiratory tract.  
Fatal if inhaled.

Acute dermal toxicity Fatal in contact with skin.

**3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Acute oral toxicity Acute toxicity estimate: 1.030 mg/kg  
Method: Acute toxicity estimate according to Regulation (EC) No.  
1272/2008

**Skin corrosion/irritation****Product:**

Based on available data, the classification criteria are not met.

**Components:****3-butoxypropan-2-ol:**

Causes skin irritation.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes severe skin burns and eye damage.

**3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Causes severe skin burns and eye damage.

**Serious eye damage/eye irritation****Product:**

Based on available data, the classification criteria are not met.

**Components:****3-butoxypropan-2-ol:**

Causes serious eye irritation.

**2-(2-butoxyethoxy)ethanol:**

Causes serious eye irritation.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes serious eye damage.

**3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Causes serious eye damage.

**Respiratory or skin sensitisation****Product:**

Based on available data, the classification criteria are not met.

**Components:****adipohydrazide:**

May cause an allergic skin reaction.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

May cause an allergic skin reaction.

**3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Test Type Magnusson-Kligman-Test

# SÜDWEST AquaVision Holz- Siegel glänzend

Species Guinea pig  
Method OECD Test Guideline 406  
May cause an allergic skin reaction.

## Germ cell mutagenicity

### Product:

Genotoxicity in vitro Based on available data, the classification criteria are not met.

## Carcinogenicity

### Product:

Based on available data, the classification criteria are not met.

## Reproductive toxicity

### Product:

Effects on fertility Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

## STOT - single exposure

### Product:

Based on available data, the classification criteria are not met.

## STOT - repeated exposure

### Product:

Based on available data, the classification criteria are not met.

## Aspiration toxicity

### Product:

Based on available data, the classification criteria are not met.

## Further information

### Product:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Further information

#### Product:

Remarks : The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### Product:

Toxicity to fish No data available

#### Components:

##### adipohydrazide:

Toxicity to algae/aquatic plants EC50 (Pseudokirchneriella subcapitata (green algae)): 9,6 mg/l

# SÜDWEST AquaVision Holz- Siegel glänzend

Exposure time: 72 h

**reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0,19 mg/l  
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates EC50 (Daphnia (water flea)): 0,12 mg/l  
Exposure time: 48 h

Toxicity to algae/aquatic plants EC50 (Skeletonema costatum (marine diatom)): 0,0052 mg/l  
Exposure time: 48 h

NOEC (Skeletonema costatum (marine diatom)): 0,00049 mg/l  
Exposure time: 48 h

M-Factor (Acute aquatic toxicity) 100

Toxicity to fish (Chronic toxicity) NOEC: 0,098 mg/l  
Exposure time: 28 d  
Species: Oncorhynchus mykiss (rainbow trout)  
Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) NOEC: 0,004 mg/l  
Exposure time: 21 d  
Species: Daphnia (water flea)

M-Factor (Chronic aquatic toxicity) 100

## 12.2 Persistence and degradability

### Product:

Biodegradability No data available

### Components:

#### **adipohydrazide:**

Biodegradability Biodegradation: 60 %  
Exposure time: 28 d  
Method: OECD Test Guideline 302B

**reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

Biodegradability not rapidly degradable

#### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Biodegradability Test Type: aerobic  
not rapidly degradable  
Biodegradation: 8 %  
Exposure time: 28 d  
Method: Tested according to Directive 92/69/EEC.

## 12.3 Bioaccumulative potential

### Product:

Bioaccumulation No data available

### Components:

#### **2-(2-butoxyethoxy)ethanol:**

Partition coefficient: n-octanol/water log Pow: 0,56

#### **3-aminomethyl-3,5,5-trimethylcyclohexylamine:**

Bioaccumulation Bioconcentration factor (BCF): < 100

# SÜDWEST AquaVision Holz- Siegel glänzend

Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

## 12.4 Mobility in soil

### Product:

Mobility No data available

## 12.5 Results of PBT and vPvB assessment

### Product:

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Endocrine disrupting properties

### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

### Product:

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1 Waste treatment methods

Product	The user is responsible for proper coding and marking of any waste. Dispose of as special waste in compliance with local and national regulations. Partial and residual quantities can be reused.
Contaminated packaging	Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.
Waste key for the unused product	08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

(\*) hazardous waste in terms of the European directive 2008/98/EG

## SECTION 14: TRANSPORT INFORMATION

### 14.1 UN number or ID number

Not regulated as a dangerous good

### 14.2 UN proper shipping name

Not regulated as a dangerous good

### 14.3 Transport hazard class(es)

Not regulated as a dangerous good

### 14.4 Packing group

Not regulated as a dangerous good

# SÜDWEST AquaVision Holz- Siegel glänzend

## 14.5 Environmental hazards

## 14.6 Special precautions for user

Remarks This information is not available.

## 14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

## SECTION 15: REGULATORY INFORMATION

### 15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC  
Directive 2010/75/EU 4,1 %

VOC  
Directive 2004/42/EC 5,1 %  
52,9 g/l

EU limit value for this product (cat. A/i) :140 g/l This product contains  
max140 g/lVOC.

Regulation (EU) No 649/2012 of  
the European Parliament and the  
Council concerning the export and  
import of dangerous chemicals Not applicable

REACH - Restrictions on the  
manufacture, placing on the  
market and use of certain  
dangerous substances, mixtures  
and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:  
(78, 75)

REACH - Restrictions on the  
manufacture, placing on the  
market and use of certain  
dangerous substances, mixtures  
and articles (Annex XVII)

3-butoxypropan-2-ol  
2-(2-butoxyethoxy)ethanol (55)  
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-  
7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1)

Other regulations Comply with the statutory regulations on health and safety at work.

### 15.2 Chemical safety assessment

This information is not available.

# SÜDWEST AquaVision Holz- Siegel glänzend

## SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

### Full text of H-Statements

H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H310	: Fatal in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

### Full text of other abbreviations

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonised System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organisation; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardisation; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organisation for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI -

# SÜDWEST AquaVision Holz- Siegel glänzend

Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

## Further information

Other information

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de

# **SÜDWEST AquaVision Holz- Siegel glänzend**