

SAFETY DATA SHEET

SÜDWEST AquaVision PU-Klarlack matt

Ref.	130000007615/D
Rev. no.	1.8
Revision Date	30.03.2026
Print Date	05.04.2026

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier

Trade name SÜDWEST AquaVision PU-Klarlack matt

1.2 Relevant identified uses of the substance or mixture and uses advised against

Coating compound/ Surface coating/ paint

Uses advised against This information is not available.

1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG
 Iggelheimer Str. 13
 D - 67459 Böhl-Iggelheim
 Telephone: +49 6324/709-0
 info@suedwest.de
 www.suedwest.de

E-mail address of person responsible for the SDS sdb@suedwest.de
 European Union

1.4 Emergency telephone number European Union Phone: +44 (0) 1865 407333

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture

Classification (REGULATION (EC) No 1272/2008)

Not a hazardous substance or mixture.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

|| No hazard pictogram, no signal word, no hazard statement(s), no precautionary statement(s) required.

|| Precautionary statements : **Prevention:**
 P273 Avoid release to the environment.

Additional Labelling

EUH210 Safety data sheet available on request.

EUH208 Contains adipohydrazide, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1), 3-aminomethyl-3,5,5-trimethylcyclohexylamine. May produce an allergic reaction.

SÜDWEST AquaVision PU- Klarlack matt

These are preservatives.
Avoid contact with the skin and the eyes.

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
3-butoxypropan-2-ol	5131-66-8 225-878-4 603-052-00-8 01-2119475527-28-XXXX	Eye Irrit. 2; H319 Skin Irrit. 2; H315	≥ 1 - < 10
2-(2-butoxyethoxy)ethanol	112-34-5 203-961-6 01-2119475104-44-XXXX	Eye Irrit. 2; H319	≥ 1 - < 10
adipohydrazide	1071-93-8 213-999-5 01-2119962900-36-XXXX	Skin Sens. 1; H317 Aquatic Chronic 2; H411	≥ 0,25 - < 1
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1)	55965-84-9 613-167-00-5 01-2120764691-48-XXXX	Acute Tox. 2; H330 Acute Tox. 2; H310 Acute Tox. 3; H301 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Eye Dam. 1; H318 EUH071 M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100 specific concentration limit Skin Corr. 1C ≥ 0,6 % Skin Irrit. 2	≥ 0,0002 - < 0,0015

SÜDWEST AquaVision PU- Klarlack matt

		0,06 - < 0,6 % Eye Irrit. 2 0,06 - < 0,6 % Skin Sens. 1A ≥ 0,0015 % Eye Dam. 1 ≥ 0,6 %	
3-aminomethyl-3,5,5-trimethylcyclohexylamine	2855-13-2 220-666-8 612-067-00-9 01-2119514687-32-XXXX	Acute Tox. 4; H302 Skin Corr. 1B; H314 Eye Dam. 1; H318 Skin Sens. 1A; H317 specific concentration limit Skin Sens. 1A ≥ 0,001 % Acute toxicity estimate Acute oral toxicity: 1.030 mg/kg	< 0,001

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice	In the case of accident or if you feel unwell, seek medical advice immediately (show the label where possible). Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Remove to fresh air. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off all contaminated clothing immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention. Keep at rest.

4.2 Most important symptoms and effects, both acute and delayed

SÜDWEST AquaVision PU- Klarlack matt

Symptoms No information available.

4.3 Indication of any immediate medical attention and special treatment needed

Treatment Treat symptomatically.
No information available.

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

Suitable extinguishing media Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
Water spray

Unsuitable extinguishing media High volume water jet

5.2 Special hazards arising from the substance or mixture

Fire may cause evolution of:
Carbon monoxide
Carbon dioxide (CO₂)
Nitrogen oxides (NO_x)
Exposure to decomposition products may be a hazard to health.

5.3 Advice for firefighters

Wear self-contained breathing apparatus for firefighting if necessary.

Additional advice

Use water spray to cool unopened containers.
Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Ensure adequate ventilation.
Do not breathe vapour.

6.2 Environmental precautions

The product should not be allowed to enter drains, water courses or the soil.
If the product contaminates rivers and lakes or drains inform respective authorities.

6.3 Methods and material for containment and cleaning up

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
Clean with detergents. Avoid solvents.
Clean contaminated surface thoroughly.
Dispose of contaminated material as waste according to item 13.

6.4 Reference to other sections

Refer to protective measures listed in sections 7 and 8.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling Avoid contact with skin and eyes.

SÜDWEST AquaVision PU- Klarlack matt

	Prevent unauthorized access. Provide sufficient air exchange and/or exhaust in work rooms. Comply with the statutory regulations on health and safety at work.
Hygiene measures	Wash hands before breaks and at the end of workday. When using do not eat, drink or smoke. Remove and wash contaminated clothing and gloves, including the inside, before re-use.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers	Containers which are opened must be carefully resealed and kept upright to prevent leakage. Store in original container. Observe label precautions. Protect from frost, heat and sunlight.
Advice on common storage	Keep away from oxidizing agents and strongly acid or alkaline materials. Keep away from food, drink and animal feedingstuffs.

7.3 Specific end use(s) For further information, see also Technical Data Sheet for the product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Occupational Exposure Limits

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
2-(2-butoxyethoxy)ethanol	112-34-5	TWA	10 ppm 67,5 mg/m ³	2006/15/EC
	Further information: Indicative			
		STEL	15 ppm 101,2 mg/m ³	2006/15/EC
	Further information: Indicative			

The lists that were valid during the creation were used as basis.

Monitoring procedures for the assessment of workplace exposure: standard EN 482

8.2 Exposure controls

Engineering measures

Ensure good ventilation; if possible, use / install internal extractor equipment.

Personal protective equipment

Eye/face protection : Wear protective goggles for protection against splashed liquid.

Safety glasses with side-shields conforming to EN166

SÜDWEST AquaVision PU- Klarlack matt

Hand protection

Material	:	Nitrile rubber
Break through time	:	480 min
Glove thickness	:	0,4 mm

Remarks	:	<p>Recommended preventive skin protection Before starting work, apply water-resistant skincare preparations to exposed skin areas. Protective gloves should be worn in case of skin contact during preparation and application.</p> <p>Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent. Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.</p> <p>The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.</p>
---------	---	--

Skin and body protection	:	Work clothes
		Skin should be washed after contact.
		Do NOT use solvents or thinners.

Respiratory protection	:	No personal respiratory protective equipment normally required.
		In case of inadequate ventilation wear respiratory protection.
		Employees involved in spraying work or in the immediate vicinity of such work should use a P2 particle filter against spray fog.
		Respiratory protection complying with EN 143.

Environmental exposure controls

Air	:	Avoid release to the environment.
Soil	:	Avoid subsoil penetration.
Water	:	Do not flush into surface water or sanitary sewer system. If the product contaminates rivers and lakes or drains inform respective authorities.

SÜDWEST AquaVision PU- Klarlack matt

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Physical state	:	liquid
Colour	:	colourless
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	No data available
Upper explosion limit / Upper flammability limit	:	No data available
Lower explosion limit / Lower flammability limit	:	No data available
Flash point	:	> 100 °C
Decomposition temperature	:	No data available

SÜDWEST AquaVision PU- Klarlack matt

pH	:	ca. 5
Viscosity Viscosity, dynamic	:	ca. 1.500 mPa.s
Flow time	:	No data available
Solubility(ies) Water solubility	:	completely miscible
Partition coefficient: n- octanol/water	:	not determined
Vapour pressure	:	No data available
Density	:	ca. 1,023 g/cm ³
Relative vapour density	:	No data available
9.2 Other information		
Explosives	:	Not explosive
Oxidizing properties	:	Not applicable

SÜDWEST AquaVision PU- Klarlack matt

Flammability (liquids) : Not applicable

Self-ignition : not auto-flammable

Evaporation rate : not applicable

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions : This information is not available.

10.4 Conditions to avoid

Conditions to avoid : Stable under recommended storage and handling conditions (see section 7).

10.5 Incompatible materials

Materials to avoid : Strong acids and strong bases
Strong oxidizing agents

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Components:

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Acute oral toxicity : Toxic if swallowed.

Acute inhalation toxicity : Assessment: Corrosive to the respiratory tract.
Fatal if inhaled.

Acute dermal toxicity : Fatal in contact with skin.

SÜDWEST AquaVision PU- Klarlack matt

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Acute oral toxicity

Acute toxicity estimate: 1.030 mg/kg

Method: Acute toxicity estimate according to Regulation (EC) No.
1272/2008**Skin corrosion/irritation****Product:**

Based on available data, the classification criteria are not met.

Components:**3-butoxypropan-2-ol:**

Causes skin irritation.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes severe skin burns and eye damage.

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Causes severe skin burns and eye damage.

Serious eye damage/eye irritation**Product:**

Based on available data, the classification criteria are not met.

Components:**3-butoxypropan-2-ol:**

Causes serious eye irritation.

2-(2-butoxyethoxy)ethanol:

Causes serious eye irritation.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Causes serious eye damage.

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Causes serious eye damage.

Respiratory or skin sensitisation**Product:**

Based on available data, the classification criteria are not met.

Components:**adipohydrazide:**

May cause an allergic skin reaction.

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

May cause an allergic skin reaction.

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Test Type

Magnusson-Kligman-Test

Species

Guinea pig

Method

OECD Test Guideline 406

May cause an allergic skin reaction.

Germ cell mutagenicity**Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

SÜDWEST AquaVision PU- Klarlack matt

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

STOT - single exposure

Product:

Based on available data, the classification criteria are not met.

STOT - repeated exposure

Product:

Based on available data, the classification criteria are not met.

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Further information

Product:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Further information

Product:

Remarks

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Product:

Toxicity to fish

No data available

Components:

adipohydrazide:

Toxicity to algae/aquatic plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 9,6 mg/l
Exposure time: 72 h

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Toxicity to fish

LC50 (Oncorhynchus mykiss (rainbow trout)): 0,19 mg/l
Exposure time: 96 h

Toxicity to daphnia and other

EC50 (Daphnia (water flea)): 0,12 mg/l

SÜDWEST AquaVision PU- Klarlack matt

aquatic invertebrates	Exposure time: 48 h
Toxicity to algae/aquatic plants	EC50 (Skeletonema costatum (marine diatom)): 0,0052 mg/l Exposure time: 48 h NOEC (Skeletonema costatum (marine diatom)): 0,00049 mg/l Exposure time: 48 h
M-Factor (Acute aquatic toxicity)	100
Toxicity to fish (Chronic toxicity)	NOEC: 0,098 mg/l Exposure time: 28 d Species: Oncorhynchus mykiss (rainbow trout) Method: OECD Test Guideline 210
Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)	NOEC: 0,004 mg/l Exposure time: 21 d Species: Daphnia (water flea)
M-Factor (Chronic aquatic toxicity)	100

12.2 Persistence and degradability

Product:

Biodegradability No data available

Components:

adipohydrazide:

Biodegradability Biodegradation: 60 %
Exposure time: 28 d
Method: OECD Test Guideline 302B

reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):

Biodegradability not rapidly degradable

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Biodegradability Test Type: aerobic
not rapidly degradable
Biodegradation: 8 %
Exposure time: 28 d
Method: Tested according to Directive 92/69/EEC.

12.3 Bioaccumulative potential

Product:

Bioaccumulation No data available

Components:

2-(2-butoxyethoxy)ethanol:

Partition coefficient: n-octanol/water log Pow: 0,56

3-aminomethyl-3,5,5-trimethylcyclohexylamine:

Bioaccumulation Bioconcentration factor (BCF): < 100
Due to the distribution coefficient n-octanol/water, accumulation in organisms is not expected.

12.4 Mobility in soil

Product:

Mobility No data available

SÜDWEST AquaVision PU- Klarlack matt

12.5 Results of PBT and vPvB assessment

Product:

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties

Product:

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects

Product:

Additional ecological information

Do not allow product to enter into ground water, bodies of water or sewage systems.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods

Product

The user is responsible for proper coding and marking of any waste. Dispose of as special waste in compliance with local and national regulations. Partial and residual quantities can be reused.

Contaminated packaging

Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.

Waste key for the unused product

08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

(*) hazardous waste in terms of the European directive 2008/98/EG

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

Not regulated as a dangerous good

14.2 UN proper shipping name

Not regulated as a dangerous good

14.3 Transport hazard class(es)

Not regulated as a dangerous good

14.4 Packing group

Not regulated as a dangerous good

14.5 Environmental hazards

14.6 Special precautions for user

SÜDWEST AquaVision PU- Klarlack matt

Remarks This information is not available.

14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC
Directive 2010/75/EU 4,1 %

VOC
Directive 2004/42/EC 5,1 %
51,9 g/l

EU limit value for this product (cat. A/i) :140 g/l This product contains
max140 g/lVOC.

Regulation (EU) No 649/2012 of
the European Parliament and the
Council concerning the export and
import of dangerous chemicals Not applicable

REACH - Restrictions on the
manufacture, placing on the
market and use of certain
dangerous substances, mixtures
and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:
(78, 75)3-butoxypropan-2-ol
2-(2-butoxyethoxy)ethanol (55)

Other regulations Comply with the statutory regulations on health and safety at work.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin.
The information in this Safety Data Sheet corresponds to our present state of knowledge and
conforms to both national and EU legislation. The user's working conditions are, however,
beyond our knowledge and control. The user is responsible for complying with all necessary
legal requirements. The information in this Safety Data Sheet describes the safety requirements
of our product and does not constitute any assurance of product properties.

Full text of H-Statements

H301 : Toxic if swallowed.
H302 : Harmful if swallowed.

SÜDWEST AquaVision PU- Klarlack matt