

SAFETY DATA SHEET**SÜDWEST Eloxier-Effekt-Spray**

Ref. 130000006083/D
Rev. no. 1.4
Revision Date 23.06.2023
Print Date 28.05.2024

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**1.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008**

Trade name SÜDWEST Eloxier-Effekt-Spray

Unique Formula Identifier (UFI) DD21-705X-000A-DTEK

1.2 Relevant identified uses of the substance or mixture and uses advised against
Coating

Uses advised against This information is not available.

1.3 Details of the supplier of the safety data sheet
SÜDWEST Lacke + Farben GmbH & Co.KG
Iggelheimer Str. 13
D - 67459 Böhl-Iggelheim
Telephone: +49 6324/709-0
Telefax: +49 6324/709-175
www.suedwest.de

E-mail address of person responsible for the SDS European Union
sdb@suedwest.de

1.4 Emergency telephone number European Union
Phone: +44 (0) 1865 407333

SECTION 2: HAZARDS IDENTIFICATION**2.1 Classification of the substance or mixture****Classification (REGULATION (EC) No 1272/2008)**

Aerosols, Category 1 H222: Extremely flammable aerosol.

H229: Pressurised container: May burst if heated.

SÜDWEST Eloxier-Effekt-Spray

Eye irritation, Category 2

H319: Causes serious eye irritation.

Specific target organ toxicity - single exposure, Category 3, Central nervous system

H336: May cause drowsiness or dizziness.

2.2 Label elements

Labelling (REGULATION (EC) No 1272/2008)

Hazard pictograms



Signal word

: Danger

Hazard statements

: H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements

EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements

: P102 Keep out of reach of children.
Prevention:
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P211 Do not spray on an open flame or other ignition source.
P251 Do not pierce or burn, even after use.
P260 Do not breathe spray.
Storage:
P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.
Disposal:
P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.**Hazardous components which must be listed on the label:**

acetone

2.3 Other hazards

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

ÜDWEST Eloxier-Effekt-Spray

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.2 Mixtures

Components

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
acetone	67-64-1 200-662-2 606-001-00-8 01-2119471330-49-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319 STOT SE 3; H336 EUH066	≥ 25 - < 50
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	≥ 10 - < 12,5
2-methoxy-1-methylethyl acetate	108-65-6 203-603-9 607-195-00-7 01-2119475791-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336	≥ 5 - < 10
ethanol	64-17-5 200-578-6 603-002-00-5 01-2119457610-43-XXXX	Flam. Liq. 2; H225 Eye Irrit. 2; H319	< 2,5
xylene	1330-20-7 215-535-7 601-022-00-9 01-2119488216-32-XXXX	Flam. Liq. 3; H226 Acute Tox. 4; H332 Acute Tox. 4; H312 Skin Irrit. 2; H315 Eye Irrit. 2; H319 STOT SE 3; H335 STOT RE 2; H373 Asp. Tox. 1; H304	< 2,5
Substances with a workplace exposure limit :			
dimethyl ether	115-10-6 204-065-8 603-019-00-8 01-2119472128-37-XXXX	Flam. Gas 1; H220 Press. GasH280	≥ 12,5 - < 20
propane	74-98-6 200-827-9 601-003-00-5 01-2119486944-21-XXXX	Flam. Gas 1; H220 Press. GasH280	≥ 10 - ≤ 12,5
butane (containing < 0.1% butadiene (203-450-8))	106-97-8 203-448-7 601-004-01-8 01-2119474691-32-XXXX	Flam. Gas 1; H220 Press. GasH280	≥ 5 - ≤ 10
isobutane	75-28-5 200-857-2	Flam. Gas 1; H220 Press. GasH280	≥ 2,5 - ≤ 5

ÜDWEST Eloxier-Effekt-Spray

601-004-00-0
01-2119485395-27-
XXXX

For explanation of abbreviations see section 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures

General advice	When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Rinse mouth with water. If swallowed, seek medical advice immediately and show this container or label. Keep at rest. Do NOT induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed

Symptoms	No information available.
----------	---------------------------

4.3 Indication of any immediate medical attention and special treatment needed

Treatment	Treat symptomatically. No information available.
-----------	---

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media

SÜDWEST Eloxier-Effekt-Spray

Suitable extinguishing media	CO ₂ , extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
Unsuitable extinguishing media	High volume water jet
5.2 Special hazards arising from the substance or mixture	Fire may cause evolution of: Carbon monoxide Carbon dioxide (CO ₂) Nitrogen oxides (NO _x) Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray.
5.3 Advice for firefighters	In the event of fire, wear self-contained breathing apparatus. Fight fire with normal precautions from a reasonable distance.
Additional advice	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures	Remove all sources of ignition. Ensure adequate ventilation. Do not breathe vapour. Prevent unauthorized access.
6.2 Environmental precautions	The product should not be allowed to enter drains, water courses or the soil. If the product contaminates rivers and lakes or drains inform respective authorities.
6.3 Methods and material for containment and cleaning up	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents. Clean contaminated surface thoroughly. Dispose of contaminated material as waste according to item 13.
6.4 Reference to other sections	Refer to protective measures listed in sections 7 and 8.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling

Advice on safe handling	Comply with the statutory regulations on health and safety at work. Avoid formation of aerosol. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.
-------------------------	---

SÜDWEST Eloxier-Effekt-Spray

All metal parts of the mixing and processing equipment must be earthed.

Operators should wear antistatic footwear and clothing. No sparking tools should be used.

Hygiene measures

Do not breathe spray, vapour.
Take off all contaminated clothing immediately.
Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product.
After washing hands, replenish lost skin oil by means of oily skin ointment.
When using do not eat, drink or smoke.

7.2 Conditions for safe storage, including any incompatibilities

Requirements for storage areas and containers

Store in original container.
Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nosmoking.
Prevent unauthorized access.
Containers which are opened must be carefully resealed and kept upright to prevent leakage.
Keep in a well-ventilated place.
Protect from frost, heat and sunlight.

Advice on protection against fire and explosion

Vapours are heavier than air and may spread along floors.
Vapours may form explosive mixtures with air.
Keep away from sources of ignition - No smoking.
Take measures to prevent the build up of electrostatic charge.

Advice on common storage

Keep away from combustible materials.
Keep away from food, drink and animal feedingstuffs.
Keep away from oxidizing agents and strongly acid or alkaline materials.

7.3 Specific end use(s)

For further information, see also Technical Data Sheet for the product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure limit(s)

Components	CAS-No.
Basis	Type: Control parameters
acetone	67-64-1
2000/39/EC	Limit Value - eight hours 1.210 mg/m ³
2000/39/EC	Limit Value - eight hours 500 ppm
Additional advice:	Indicative
n-butyl acetate	123-86-4

ÜDWEST Eloxier-Effekt-Spray

2019/1831/EU	Short term exposure limit	723 mg/m ³
2019/1831/EU	Short term exposure limit	150 ppm
Additional advice:	Indicative	
2019/1831/EU	Limit Value - eight hours	241 mg/m ³
2019/1831/EU	Limit Value - eight hours	50 ppm
Additional advice:	Indicative	
dimethyl ether		115-10-6
2000/39/EC	Limit Value - eight hours	1.920 mg/m ³
2000/39/EC	Limit Value - eight hours	1.000 ppm
Additional advice:	Indicative	
2-methoxy-1-methylethyl acetate		108-65-6
2000/39/EC	Short term exposure limit	550 mg/m ³
2000/39/EC	Short term exposure limit	100 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	
2000/39/EC	Limit Value - eight hours	275 mg/m ³
2000/39/EC	Limit Value - eight hours	50 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	
ethanol		64-17-5

Remarks:

Contains no substances with occupational exposure limit values.

xylene		1330-20-7
2000/39/EC	Limit Value - eight hours	221 mg/m ³
2000/39/EC	Limit Value - eight hours	50 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	
2000/39/EC	Short term exposure limit	442 mg/m ³
2000/39/EC	Short term exposure limit	100 ppm
Additional advice:	Identifies the possibility of significant uptake through the skin Indicative	

The lists that were valid during the creation were used as basis.

8.2 Exposure controls

Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn.

Washing facilities / water for rinsing eyes and skin should be available.

ÜDWEST Eloxier-Effekt-Spray

Individual protection measures, such as personal protective equipment

a) Eye/face protection Safety glasses with side-shields conforming to EN166

b) Skin protection
Hand protection Break through time: 60 min
Minimum thickness: 0,7 mm
e.g. KCL 898 "Butoject®" - butyl rubber protective glove -
(Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de) or equal.

Dispose of wetted gloves at the end of the shift!

Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.
The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.

Body Protection Preventive skin protection
Long sleeved clothing
Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.

c) Respiratory protection When workers are facing concentrations above the occupational exposure limit values they must use appropriate certified respirators.
Breathing protection equipment required in inadequately ventilated places and during spraying.
In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.
Combination filter A-P2
Respiratory protection complying with EN 14387.

Environmental exposure controls

General advice The product should not be allowed to enter drains, water courses or the soil.
If the product contaminates rivers and lakes or drains inform respective authorities.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties

Appearance aerosol

SÜDWEST Eloxier-Effekt-Spray

Colour	various
Odour	characteristic
Odour Threshold	No data available
pH	substance/mixture is non-soluble (in water)
Melting point/freezing point	not determined
Initial boiling point and boiling range	Not applicable
Flash point	Not applicable, as aerosol.
Evaporation rate	Not applicable
Flammability (solid, gas)	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	26,2 % (V) Upper explosion limit
Lower explosion limit / Lower flammability limit	1,2 % (V) Lower explosion limit
Vapour pressure	8.300 hPa (20 °C)
Vapour density	No data available
Density	ca. 0,8 g/cm³ (20 °C)
Solubility(ies)	
Water solubility	completely miscible
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity	
Viscosity, dynamic	No data available
Explosive properties	In use may form flammable/explosive vapour-air mixture.
Oxidizing properties	Not applicable

9.2 Other information

Ignition temperature	240 °C
Flow time	45 s at 20 °C

SÜDWEST Eloxier-Effekt-Spray

Cross section: 4 mm
Method: DIN 53211

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity

No dangerous reaction known under conditions of normal use.

10.2 Chemical stability

Stable under normal conditions.

10.3 Possibility of hazardous reactions

Hazardous reactions No dangerous reaction known under conditions of normal use.
Vapours may form explosive mixture with air.

10.4 Conditions to avoid

Conditions to avoid	Direct sources of heat. Strong sunlight for prolonged periods. Avoid heating over 50 °C. Risk of bursting.
---------------------	---

10.5 Incompatible materials

10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity

Product:

Acute oral toxicity Based on available data, the classification criteria are not met.

Acute inhalation toxicity Acute toxicity estimate: > 20 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Calculation method

Components:

xylene:

Acute inhalation toxicity
LC50 (Rat): 11 mg/l
Exposure time: 4 h

ÜDWEST Eloxier-Effekt-Spray

Test atmosphere: vapour

Acute dermal toxicity Harmful in contact with skin.

Skin corrosion/irritation

Product:

Repeated exposure may cause skin dryness or cracking.

Components:

acetone:

Repeated exposure may cause skin dryness or cracking.

n-butyl acetate:

Repeated exposure may cause skin dryness or cracking.

xylene:

Causes skin irritation.

Serious eye damage/eye irritation

Product:

Causes serious eye irritation.

Components:

acetone:

Causes serious eye irritation.

ethanol:

Species

Method

Rabbit

OECD Test Guideline 405

Causes serious eye irritation.

xylene:

Causes serious eye irritation.

Respiratory or skin sensitisation

Product:

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

Product:

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

Carcinogenicity

Product:

Based on available data, the classification criteria are not met.

Reproductive toxicity

Product:

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

ÜDWEST Eloxier-Effekt-Spray

STOT - single exposure

Product:

Assessment May cause drowsiness or dizziness.

Components:

acetone:

Exposure routes Inhalation
Assessment May cause drowsiness or dizziness.

n-butyl acetate:

Exposure routes Inhalation (vapour)
Assessment May cause drowsiness or dizziness.

2-methoxy-1-methylethyl acetate:

Assessment May cause drowsiness or dizziness.

xylene:

Exposure routes Inhalation
Assessment May cause respiratory irritation.

STOT - repeated exposure

Product:

Based on available data, the classification criteria are not met.

Components:

xylene:

Assessment May cause damage to organs through prolonged or repeated exposure.

Aspiration toxicity

Product:

Based on available data, the classification criteria are not met.

Components:

xylene:

May be fatal if swallowed and enters airways.

Toxicology, Metabolism, Distribution

Further information

Product:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

11.2 Information on other hazards

Endocrine disrupting properties

Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

ÜDWEST Eloxier-Effekt-Spray

Experience with human exposure

Product:

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

Further information

Product:

Remarks

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

SECTION 12: ECOLOGICAL INFORMATION

12.1 Toxicity

Product:

Toxicity to fish

No data available

12.2 Persistence and degradability

Product:

Biodegradability

No data available

Components:

n-butyl acetate:

Biodegradability

rapidly degradable

Biodegradation: > 90 %

Exposure time: 28 d

12.3 Bioaccumulative potential

Product:

Bioaccumulation

No data available

Components:

n-butyl acetate:

Partition coefficient: n-octanol/water

log Pow: 2,3

Method: OECD Test Guideline 117

2-methoxy-1-methylethyl acetate:

Partition coefficient: n-octanol/water

log Pow: 0,43 (20 °C)

ÜDWEST Eloxier-Effekt-Spray

xylene:

Partition coefficient: n-octanol/water log Pow: > 3

dimethyl ether:

Partition coefficient: n-octanol/water log Pow: 0,1

propane:

Partition coefficient: n-octanol/water log Pow: 2,36

isobutane:

Partition coefficient: n-octanol/water log Pow: 2,76

12.4 Mobility in soil**Product:**

Mobility No data available

12.5 Results of PBT and vPvB assessment**Product:**

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

12.6 Endocrine disrupting properties**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

12.7 Other adverse effects**Product:**

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods**Product**

The user is responsible for proper coding and marking of any waste.
When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste"
Partial and residual quantities can be reused.
Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.

ÜDWEST Eloxier-Effekt-Spray

Contaminated packaging
Packaging that is not properly emptied must be disposed of as the unused product.
Empty packaging should be recycled through disposal systems.

Waste key for the unused product
08 01 11* waste paint and varnish containing organic solvents or other hazardous substances

(*) hazardous waste in terms of the European directive 2008/98/EG

SECTION 14: TRANSPORT INFORMATION

14.1 UN number or ID number

ADR	1950
IMDG	1950
IATA	1950

14.2 UN proper shipping name

ADR	AEROSOLS
IMDG	AEROSOLS
IATA	Aerosols, flammable

14.3 Transport hazard class(es)

ADR	2.1
IMDG	2.1
IATA	2.1

14.4 Packing group

ADR	
Packing group	Not Assigned
Classification Code	5F
Labels	2.1
Tunnel restriction code	(D)
IMDG	
Labels	2.1
EmS number	F-D, S-U
IATA	

ÜDWEST Eloxier-Effekt-Spray

Labels 2.1

14.5 Environmental hazards

ADR

Environmentally hazardous : no

IMDG

Marine pollutant : no

14.6 Special precautions for user

Remarks This information is not available.

14.7 Maritime transport in bulk according to IMO instruments

Remarks Not applicable

Additional advice

ADR ADR: Up to 1 l per inner package, transport as limited quantity in accordance with ADR 3.4.

IMDG IMDG: Up to 1 l per inner package, transport as limited quantity in accordance with IMDG Code 3.4.

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

VOC Directive 2010/75/EU 90,7 %

VOC Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EC) No 649/2012
of the European Parliament
and the Council concerning the
export and import of dangerous
chemicals

ÜDWEST Eloxier-Effekt-Spray

Other regulations

Comply with the statutory regulations on health and safety at work.
Take note of Dir 94/33/EC on the protection of young people at work.
Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

15.2 Chemical safety assessment

This information is not available.

SECTION 16: OTHER INFORMATION

Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

Full text of H-Statements

H220	: Extremely flammable gas.
H225	: Highly flammable liquid and vapour.
H226	: Flammable liquid and vapour.
H280	: Contains gas under pressure; may explode if heated.
H304	: May be fatal if swallowed and enters airways.
H312	: Harmful in contact with skin.
H315	: Causes skin irritation.
H319	: Causes serious eye irritation.
H332	: Harmful if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H373	: May cause damage to organs through prolonged or repeated exposure.

Full text of other abbreviations

Acute Tox.	: Acute toxicity
Asp. Tox.	: Aspiration hazard
Eye Irrit.	: Eye irritation
Flam. Gas	: Flammable gases
Flam. Liq.	: Flammable liquids
Press. Gas	: Gases under pressure
Skin Irrit.	: Skin irritation
STOT RE	: Specific target organ toxicity - repeated exposure
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation;

ÜDWEST Eloxier-Effekt-Spray

Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

Further information

Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS
REG_EU / EN

sdb@suedwest.de

SÜDWEST Eloxier-Effekt-Spray