



**SÜDWEST Fassaden-Öl****2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.

Supplemental Hazard Statements EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : P102 Keep out of reach of children.

**Prevention:**

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

**Response:**

P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.

**Disposal:**

P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

**Additional Labelling**

EUH208 Contains turpentine, oil, 3-iodo-2-propynyl butylcarbamate, reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1). May produce an allergic reaction.

These are preservatives.

Avoid contact with the skin and the eyes.

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**Regulation concerning biocidal products (528/2012):**

Contains 3-iodo-2-propynyl butylcarbamate  
. As active agents for coating protection in accordance with  
Biocidal Product Regulation (528/2012), Article 58(3)

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SÜDWEST Fassaden-Öl**

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9  649-327-00-6 01-2119457273-39-XXXX	Asp. Tox. 1; H304  EUH066	≥ 25 - < 50
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17-XXXX	Carc. 2; H351, Note V, Note W, Note 10	≥ 3 - < 5
turpentine, oil	8006-64-2 232-350-7 650-002-00-6 01-2119502456-45-XXXX	Flam. Liq. 2; H225 Acute Tox. 4; H302 Acute Tox. 4; H312 Acute Tox. 4; H332 Skin Irrit. 2; H315 Eye Irrit. 2; H319 Skin Sens. 1; H317 Asp. Tox. 1; H304 Aquatic Chronic 2; H411	≥ 0,5 - < 1
3-iodo-2-propynyl butylcarbamate	55406-53-6 259-627-5 616-212-00-7 01-2120762115-60-XXXX	STOT RE 1; H372 (larynx) Eye Dam. 1; H318 Acute Tox. 3; H331 Skin Sens. 1; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Acute Tox. 4; H302  M-Factor (Acute aquatic toxicity): 10 M-Factor (Chronic aquatic toxicity): 1	≥ 0,1 - < 0,3
reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1)	55965-84-9  613-167-00-5 01-2120764691-48-XXXX	Acute Tox. 2; H330 Acute Tox. 2; H310 Acute Tox. 3; H301 Skin Corr. 1C; H314 Skin Sens. 1A; H317 Aquatic Acute 1; H400 Aquatic Chronic 1; H410 Eye Dam. 1; H318 EUH071  M-Factor (Acute aquatic toxicity): 100 M-Factor (Chronic aquatic toxicity): 100	≥ 0,0002 - < 0,0015

**SÜDWEST Fassaden-Öl**

		specific concentration limit Skin Corr. 1C $\geq 0,6 \%$ Skin Irrit. 2 $0,06 - < 0,6 \%$ Eye Irrit. 2 $0,06 - < 0,6 \%$ Skin Sens. 1A $\geq 0,0015 \%$ Eye Dam. 1 $\geq 0,6 \%$	
--	--	--	--

For explanation of abbreviations see section 16.

<b>SECTION 4: FIRST AID MEASURES</b>
--------------------------------------

**4.1 Description of first aid measures**

General advice	<p>When symptoms persist or in all cases of doubt seek medical advice.          Never give anything by mouth to an unconscious person.          If unconscious, place in recovery position and seek medical advice.</p>
Inhalation	<p>Move to fresh air in case of accidental inhalation of vapours or decomposition products.          Keep patient warm and at rest.          If breathing is irregular or stopped, administer artificial respiration.          If symptoms persist, call a physician.</p>
Skin contact	<p>Take off contaminated clothing and shoes immediately.          Wash skin thoroughly with soap and water or use recognized skin cleanser.          Do NOT use solvents or thinners.          If skin irritation persists, call a physician.</p>
Eye contact	<p>In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes.          Seek medical advice.</p>
Ingestion	<p>Rinse mouth with water.          If swallowed, seek medical advice immediately and show this container or label.          Keep at rest.          Do NOT induce vomiting.</p>

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms	No information available.
----------	---------------------------



**SÜDWEST Fassaden-Öl**

Advice on safe handling	<p>Comply with the statutory regulations on health and safety at work. Avoid formation of aerosol. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. All metal parts of the mixing and processing equipment must be earthed. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Risk of self-combustion from drying oils on used towels/rags.</p>
Hygiene measures	<p>Do not breathe spray, vapour. Take off all contaminated clothing immediately. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. After washing hands, replenish lost skin oil by means of oily skin ointment. When using do not eat, drink or smoke.</p>

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers	<p>Store in original container. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. No smoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a well-ventilated place. Protect from frost, heat and sunlight.</p>
Advice on protection against fire and explosion	<p>Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.</p>
Advice on common storage	<p>Keep away from combustible materials. Keep away from food, drink and animal feedingstuffs. Keep away from oxidizing agents and strongly acid or alkaline materials.</p>
Storage temperature	10 - 30 °C

<b>7.3 Specific end use(s)</b>	For further information, see also Technical Data Sheet for the product.
--------------------------------	---

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters**

Contains no substances with occupational exposure limit values. The lists that were valid during

# SÜDWEST Fassaden-Öl

the creation were used as basis.

## 8.2 Exposure controls

### Appropriate engineering controls

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn.

Washing facilities / water for rinsing eyes and skin should be available.

### Individual protection measures, such as personal protective equipment (PPE)

- |                                       |  |
|---------------------------------------|--|
| a) Eye/face protection                | Safety glasses with side-shields conforming to EN166   |
| b) Skin protection<br>Hand protection | <p>Break through time: 480 min<br/>Minimum thickness: 0,4 mm<br/>e.g. KCL 897 "Butoject®" - butyl rubber protective glove -<br/>(Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de) or equal.</p> <p>Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.</p> <p>The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it.<br/>The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.</p> |
| Body Protection                       | <p>Preventive skin protection<br/>Long sleeved clothing<br/>Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthetic fiber. All parts of the body should be washed after contact.</p>  |
| c) Respiratory protection             | <p>When workers are facing concentrations above the occupational exposure limit values they must use appropriate certified respirators.<br/>Breathing protection equipment required in inadequately ventilated places and during spraying.<br/>In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.<br/>Combination filter A-P2<br/>Respiratory protection complying with EN 14387.</p>   |

### Environmental exposure controls

- |                |  |
|----------------|--|
| General advice | <p>The product should not be allowed to enter drains, water courses or the soil.<br/>If the product contaminates rivers and lakes or drains inform respective authorities.</p> |
|----------------|--|

**SÜDWEST Fassaden-Öl****SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

Appearance	liquid
Colour	various
Odour	characteristic
Odour Threshold	No data available
pH	substance/mixture is non-soluble (in water)
Melting point/freezing point	No data available
Initial boiling point and boiling range	100 °C
Flash point	51 °C Method: closed cup
Evaporation rate	not applicable
Flammability (solid, gas)	not applicable
Upper explosion limit / Upper flammability limit	7 %(V) Upper explosion limit
Lower explosion limit / Lower flammability limit	0,6 %(V) Lower explosion limit
Vapour pressure	23 hPa (20 °C)
Vapour density	No data available
Density	ca. 0,94 - 1,04 g/cm <sup>3</sup> (20 °C)
Solubility(ies) Water solubility	No data available
Partition coefficient: n-octanol/water	not determined
Auto-ignition temperature	not auto-flammable
Decomposition temperature	No data available
Viscosity Viscosity, dynamic	No data available
Viscosity, kinematic	ca. 91 mm <sup>2</sup> /s (40 °C)
Explosive properties	Not explosive In use may form flammable/explosive vapour-air mixture.

# SÜDWEST Fassaden-Öl

Oxidizing properties                      Not applicable

## 9.2 Other information

Flow time                                      No data available

## SECTION 10: STABILITY AND REACTIVITY

### 10.1 Reactivity

No dangerous reaction known under conditions of normal use.

### 10.2 Chemical stability

Stable under normal conditions.

### 10.3 Possibility of hazardous reactions

Hazardous reactions                      No dangerous reaction known under conditions of normal use.  
Vapours may form explosive mixture with air.

### 10.4 Conditions to avoid

Conditions to avoid                      Direct sources of heat.  
Strong sunlight for prolonged periods.

### 10.5 Incompatible materials

Materials to avoid                      Strong acids and strong bases  
Strong oxidizing agents

### 10.6 Hazardous decomposition products

No decomposition if stored and applied as directed.

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

#### Acute toxicity

##### Product:

Acute oral toxicity                      Based on available data, the classification criteria are not met.

Acute inhalation toxicity                      Acute toxicity estimate: > 20 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Method: Calculation method

Acute dermal toxicity                      Based on available data, the classification criteria are not met.

##### Components:

##### turpentine, oil:

Acute oral toxicity                      Harmful if swallowed.

# SÜDWEST Fassaden-Öl

Acute inhalation toxicity Harmful if inhaled.  
Acute dermal toxicity Harmful in contact with skin.

**3-iodo-2-propynyl butylcarbamate:**

Acute oral toxicity Harmful if swallowed.

Acute inhalation toxicity LC50 (Rat): 3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

**reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

Acute oral toxicity Toxic if swallowed.

Acute inhalation toxicity Assessment: Corrosive to the respiratory tract.  
Fatal if inhaled.

Acute dermal toxicity Fatal in contact with skin.

**Skin corrosion/irritation****Product:**

Repeated exposure may cause skin dryness or cracking.

**Components:****Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Repeated exposure may cause skin dryness or cracking.

**turpentine, oil:**

Causes skin irritation.

**reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

Causes severe skin burns and eye damage.

**Serious eye damage/eye irritation****Product:**

Based on available data, the classification criteria are not met.

**Components:****turpentine, oil:**

Causes serious eye irritation.

**3-iodo-2-propynyl butylcarbamate:**

Causes serious eye damage.

**reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

Causes serious eye damage.

**Respiratory or skin sensitisation****Product:**

Based on available data, the classification criteria are not met.

**Components:****turpentine, oil:**

# SÜDWEST Fassaden-Öl

May cause an allergic skin reaction.

**3-iodo-2-propynyl butylcarbamate:**

May cause an allergic skin reaction.

**reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

May cause an allergic skin reaction.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

**Carcinogenicity****Product:**

Based on available data, the classification criteria are not met.

**Components:****titanium dioxide:**

Suspected of causing cancer.

**Reproductive toxicity****Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

**STOT - single exposure****Product:**

Based on available data, the classification criteria are not met.

**STOT - repeated exposure****Product:**

Based on available data, the classification criteria are not met.

**Components:****3-iodo-2-propynyl butylcarbamate:**

Exposure routes

Inhalation

Target Organs

larynx

Assessment

Causes damage to organs through prolonged or repeated exposure.

**Aspiration toxicity****Product:**

Based on available data, the classification criteria are not met.

**Components:****Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

May be fatal if swallowed and enters airways.

**turpentine, oil:**

May be fatal if swallowed and enters airways.

# SÜDWEST Fassaden-Öl

## Toxicology, Metabolism, Distribution

### Further information

#### Product:

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## 11.2 Information on other hazards

### Endocrine disrupting properties

#### Product:

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

### Experience with human exposure

#### Product:

##### General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness.

Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

### Further information

#### Product:

##### Remarks

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1 Toxicity

#### Product:

Toxicity to fish No data available

#### Components:

##### **3-iodo-2-propynyl butylcarbamate:**

Toxicity to fish LC50 (Oncorhynchus mykiss (rainbow trout)): 0,067 mg/l  
Exposure time: 96 h  
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates EC50 (Daphnia magna (Water flea)): 0,16 mg/l  
Exposure time: 48 h

**SÜDWEST Fassaden-Öl**

Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants

EC50 (Pseudokirchneriella subcapitata (green algae)): 0,049 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Pseudokirchneriella subcapitata (green algae)): 0,0046 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

M-Factor (Acute aquatic toxicity)

10

Toxicity to fish (Chronic toxicity)

NOEC: 0,0084 mg/l

Exposure time: 35 d

Species: Pimephales promelas (fathead minnow)

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

NOEC: 0,010 mg/l

Exposure time: 21 d

Species: Daphnia (water flea)

Method: OECD Test Guideline 211

M-Factor (Chronic aquatic toxicity)

1

**reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

Toxicity to fish

LC50 (Oncorhynchus mykiss (rainbow trout)): 0,19 mg/l

Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates

EC50 (Daphnia (water flea)): 0,12 mg/l

Exposure time: 48 h

Toxicity to algae/aquatic plants

EC50 (Skeletonema costatum (marine diatom)): 0,0052 mg/l

Exposure time: 48 h

NOEC (Skeletonema costatum (marine diatom)): 0,00049 mg/l

Exposure time: 48 h

M-Factor (Acute aquatic toxicity)

100

Toxicity to fish (Chronic toxicity)

NOEC: 0,098 mg/l

Exposure time: 28 d

Species: Oncorhynchus mykiss (rainbow trout)

Method: OECD Test Guideline 210

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity)

NOEC: 0,004 mg/l

Exposure time: 21 d

Species: Daphnia (water flea)

M-Factor (Chronic aquatic toxicity)

100

# SÜDWEST Fassaden-Öl

## 12.2 Persistence and degradability

**Product:**

Biodegradability No data available

**Components:****turpentine, oil:**Biodegradability rapidly degradable  
Biodegradation: 76 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301D**3-iodo-2-propynyl butylcarbamate:**

Biodegradability rapidly degradable

**reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one[EC no.247-500-7]and 2-methyl-2H-isothiazol-3-one[EC no.220-239-6] (3:1):**

Biodegradability not rapidly degradable

## 12.3 Bioaccumulative potential

**Product:**

Bioaccumulation No data available

**Components:****turpentine, oil:**

Bioaccumulation Due to the distribution coefficient n-octanol/water, accumulation in organisms is possible.

Partition coefficient: n-octanol/water log Pow: &gt; 3

**3-iodo-2-propynyl butylcarbamate:**

Partition coefficient: n-octanol/water log Pow: 2,8

## 12.4 Mobility in soil

**Product:**

Mobility No data available

## 12.5 Results of PBT and vPvB assessment

**Product:**

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

## 12.6 Endocrine disrupting properties

**Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

## 12.7 Other adverse effects

**Product:**

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.

**SÜDWEST Fassaden-Öl****SECTION 13: DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

Product	<p>The user is responsible for proper coding and marking of any waste.</p> <p>When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste"</p> <p>Partial and residual quantities can be reused.</p> <p>Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.</p>
Contaminated packaging	<p>Packaging that is not properly emptied must be disposed of as the unused product.</p> <p>Empty packaging should be recycled through disposal systems.</p>
Waste key for the unused product	<p>08 01 11* waste paint and varnish containing organic solvents or other hazardous substances</p> <p>(*) hazardous waste in terms of the European directive 2008/98/EG</p>

**SECTION 14: TRANSPORT INFORMATION****14.1 UN number or ID number**

ADR	1263
IMDG	1263
IATA	1263

**14.2 UN proper shipping name**

ADR	PAINT
IMDG	PAINT
IATA	Paint

**14.3 Transport hazard class(es)**

ADR	3
IMDG	3
IATA	3

**14.4 Packing group**

ADR

**SÜDWEST Fassaden-Öl**

Packing group	III
Classification Code	F1
Hazard Identification Number	30
Labels	3
Tunnel restriction code	(D/E)

**IMDG**

Packaging group	III
Labels	3
EmS number	F-E, <u>S-E</u>

**IATA**

Packaging group	III
Labels	3

**14.5 Environmental hazards****ADR**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

**14.6 Special precautions for user**

Remarks This information is not available.

**14.7 Maritime transport in bulk according to IMO instruments**

Remarks Not applicable

**Additional advice**

ADR ADR: Packages < 450l: No dangerous goods (ADR 2.2.3.1.5)

IMDG IMDG: Packages < 450l: No dangerous goods (IMDG 2.3.2.5).

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC  
|| Directive 2010/75/EU 36,1 %

**SÜDWEST Fassaden-Öl**

VOC

Directive 2004/42/EC

37,1 %

390 g/l

EU limit value for this product (cat. A/e) :400 g/l This product contains max400 g/lVOC.

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals

Not applicable

Other regulations

Comply with the statutory regulations on health and safety at work.

Take note of Dir 94/33/EC on the protection of young people at work.

Take note of Dir 92/85/EEC on the safety and health at work of pregnant workers.

**15.2 Chemical safety assessment**

This information is not available.

<b>SECTION 16: OTHER INFORMATION</b>
--------------------------------------

**Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.**

**Full text of H-Statements**

H225	: Highly flammable liquid and vapour.
H301	: Toxic if swallowed.
H302	: Harmful if swallowed.
H304	: May be fatal if swallowed and enters airways.
H310	: Fatal in contact with skin.
H312	: Harmful in contact with skin.
H314	: Causes severe skin burns and eye damage.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H318	: Causes serious eye damage.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.

**SÜDWEST Fassaden-Öl**

H331	: Toxic if inhaled.
H332	: Harmful if inhaled.
H351	: Suspected of causing cancer if inhaled.
H372	: Causes damage to organs through prolonged or repeated exposure if inhaled.
H400	: Very toxic to aquatic life.
H410	: Very toxic to aquatic life with long lasting effects.
H411	: Toxic to aquatic life with long lasting effects.

**Full text of other abbreviations**

Acute Tox.	: Acute toxicity
Aquatic Acute	: Short-term (acute) aquatic hazard
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Asp. Tox.	: Aspiration hazard
Carc.	: Carcinogenicity
Eye Dam.	: Serious eye damage
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Skin Corr.	: Skin corrosion
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT RE	: Specific target organ toxicity - repeated exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Further information**

# SÜDWEST Fassaden-Öl

## Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de