

## SAFETY DATA SHEET

# SÜDWEST Holz-Öl

Ref.	130000007309/D
Rev. no.	1.3
Revision Date	25.03.2025
Print Date	08.05.2025

### SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

#### 1.1 Product identifier

Trade name SÜDWEST Holz-Öl

#### 1.2 Relevant identified uses of the substance or mixture and uses advised against

Wood coating

Uses advised against This information is not available.

#### 1.3 Details of the supplier of the safety data sheet

SÜDWEST Lacke + Farben GmbH & Co.KG  
 Iggelheimer Str. 13  
 D - 67459 Böhl-Iggelheim  
 Telephone: +49 6324/709-0  
 info@suedwest.de  
 www.suedwest.de

E-mail address of person responsible for the SDS sdb@suedwest.de  
 European Union

#### 1.4 Emergency telephone number European Union

Phone: +44 (0) 1865 407333

### SECTION 2: HAZARDS IDENTIFICATION

#### 2.1 Classification of the substance or mixture

##### Classification (REGULATION (EC) No 1272/2008)

Flammable liquids, Category 3 H226: Flammable liquid and vapour.

Aspiration hazard, Category 1 H304: May be fatal if swallowed and enters airways.

#### 2.2 Label elements

##### Labelling (REGULATION (EC) No 1272/2008)

**SÜDWEST Holz-Öl**

Hazard pictograms



Signal word	:	Danger
Hazard statements	:	H226 Flammable liquid and vapour. H304 May be fatal if swallowed and enters airways.
Supplemental Hazard Statements		EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	P102 Keep out of reach of children. <b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor. P331 Do NOT induce vomiting. <b>Storage:</b> P405 Store locked up. <b>Disposal:</b> P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

**Hazardous components which must be listed on the label:**

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, &lt;2% aromatics

**Additional Labelling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-48-9  649-327-00-6 01-2119457273-39-XXXX	Asp. Tox. 1; H304  EUH066	≥ 50 - < 70
titanium dioxide	13463-67-7	Carc. 2; H351, Note V,	≥ 1 - < 10

**SÜDWEST Holz-Öl**

	236-675-5 01-2119489379-17-XXXX	Note W, Note 10	
strontium bis(2-ethylhexanoate)	2457-02-5 219-536-3	Acute Tox. 4; H302 Skin Irrit. 2; H315 Eye Dam. 1; H318 Repr. 2; H361d	≥ 0,05 - < 0,3
Substances with a workplace exposure limit :			
(2-methoxymethylethoxy) propanol	34590-94-8 252-104-2 01-2119450011-60-XXXX		≥ 3 - < 5

For explanation of abbreviations see section 16.

**SECTION 4: FIRST AID MEASURES****4.1 Description of first aid measures**

General advice	When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Rinse mouth with water. If swallowed, seek medical advice immediately and show this container or label. Keep at rest. Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms No information available.

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment Treat symptomatically.  
No information available.

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media**

Suitable extinguishing media CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water

**SÜDWEST Holz-Öl**

Unsuitable extinguishing media	spray or alcohol resistant foam.
<b>5.2 Special hazards arising from the substance or mixture</b>	High volume water jet Fire may cause evolution of: Carbon monoxide Carbon dioxide (CO <sub>2</sub> ) Nitrogen oxides (NO <sub>x</sub> ) Exposure to decomposition products may be a hazard to health. Cool closed containers exposed to fire with water spray.
<b>5.3 Advice for firefighters</b>	In the event of fire, wear self-contained breathing apparatus. Fight fire with normal precautions from a reasonable distance.
Additional advice	Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**SECTION 6: ACCIDENTAL RELEASE MEASURES**

<b>6.1 Personal precautions, protective equipment and emergency procedures</b>	Remove all sources of ignition. Ensure adequate ventilation. Do not breathe vapour. Prevent unauthorized access.
<b>6.2 Environmental precautions</b>	The product should not be allowed to enter drains, water courses or the soil. If the product contaminates rivers and lakes or drains inform respective authorities.
<b>6.3 Methods and material for containment and cleaning up</b>	Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13). Clean with detergents. Avoid solvents. Clean contaminated surface thoroughly. Dispose of contaminated material as waste according to item 13.
<b>6.4 Reference to other sections</b>	Refer to protective measures listed in sections 7 and 8.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling**

Advice on safe handling	Comply with the statutory regulations on health and safety at work. Avoid formation of aerosol. Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. All metal parts of the mixing and processing equipment must be earthed. Operators should wear antistatic footwear and clothing. No sparking tools should be used. Risk of self-combustion from drying oils on used towels/rags.
Hygiene measures	Do not breathe spray, vapour. Take off all contaminated clothing immediately. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product.

**SÜDWEST Holz-Öl**

After washing hands, replenish lost skin oil by means of oily skin ointment.

When using do not eat, drink or smoke.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers	Store in original container. Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nosmoking. Prevent unauthorized access. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Keep in a well-ventilated place. Protect from frost, heat and sunlight.
Advice on protection against fire and explosion	Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge.
Advice on common storage	Keep away from combustible materials. Keep away from food, drink and animal feedingstuffs. Keep away from oxidizing agents and strongly acid or alkaline materials.

**7.3 Specific end use(s)** For further information, see also Technical Data Sheet for the product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
(2-methoxymethylethoxy) propanol	34590-94-8	TWA	50 ppm 308 mg/m <sup>3</sup>	2000/39/EC
	Further information: Identifies the possibility of significant uptake through the skin, Indicative			

The lists that were valid during the creation were used as basis.

|| Monitoring procedures for the assessment of workplace exposure: standard EN 482

**8.2 Exposure controls****Engineering measures**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn.

Washing facilities / water for rinsing eyes and skin should be available.

**Personal protective equipment**

Eye/face protection : Safety glasses with side-shields conforming to EN166

Hand protection

**SÜDWEST Holz-Öl**

Material	:	Nitrile rubber
Break through time	:	480 min
Glove thickness	:	0,4 mm
Remarks	:	<p>Recommended preventive skin protection Before starting work, apply water-resistant skincare preparations to exposed skin areas. Protective gloves should be worn in case of skin contact during preparation and application.</p> <p>Gloves made of nitrile rubber,e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent. Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.</p> <p>The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.</p>
Skin and body protection	:	<p>Preventive skin protection</p> <p>Long sleeved clothing</p> <p>Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthehic fiber. All parts of the body should be washed after contact.</p>
Respiratory protection	:	<p>When workers are facing concentrations above the occupational exposure limit values they must use appropriate certified respirators.</p> <p>Breathing protection equipment required in inadequately ventilated places and during spraying.</p> <p>In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.</p> <p>Combination filter A-P2</p> <p>Respiratory protection complying with EN 14387.</p>

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

Physical state : liquid

**SÜDWEST Holz-Öl**

Colour	:	various
Odour	:	characteristic
Odour Threshold	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	ca. 185 °C
Upper explosion limit / Upper flammability limit	:	10,4 %(V) Medium: Upper explosion limit
Lower explosion limit / Lower flammability limit	:	0,6 %(V) Medium: Lower explosion limit
Flash point	:	58,5 °C Method: closed cup
Decomposition temperature	:	No data available
pH	:	substance/mixture is non-soluble (in water)
Viscosity	:	

**SÜDWEST Holz-Öl**

Viscosity, dynamic	:	No data available
Flow time	:	ca. 13 - 15 s Cross section: 4 mm
Solubility(ies) Water solubility	:	No data available
Partition coefficient: n- octanol/water	:	not determined
Vapour pressure	:	0,7 hPa (20 °C)
Density	:	ca. 0,85 g/cm <sup>3</sup> (20 °C)
Relative vapour density	:	No data available

**9.2 Other information**

Explosives	:	Not explosive In use may form flammable/explosive vapour-air mixture.
Oxidizing properties	:	Not applicable
Flammability (liquids)	:	Not applicable
Self-ignition	:	not auto-flammable

**SÜDWEST Holz-Öl**

Evaporation rate : not applicable

**SECTION 10: STABILITY AND REACTIVITY****10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

Hazardous reactions No dangerous reaction known under conditions of normal use.  
Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**

Conditions to avoid Direct sources of heat.  
Strong sunlight for prolonged periods.

**10.5 Incompatible materials**

Materials to avoid Strong acids and strong bases  
Strong oxidizing agents

**10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity****Product:**

Acute oral toxicity Based on available data, the classification criteria are not met.

Acute inhalation toxicity Based on available data, the classification criteria are not met.

Acute dermal toxicity Based on available data, the classification criteria are not met.

**Components:****strontium bis(2-ethylhexanoate):**

Acute oral toxicity Harmful if swallowed.

**Skin corrosion/irritation****Product:**

Repeated exposure may cause skin dryness or cracking.

**Components:****Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Repeated exposure may cause skin dryness or cracking.

**strontium bis(2-ethylhexanoate):**

Causes skin irritation.

**SÜDWEST Holz-Öl****Serious eye damage/eye irritation****Product:**

Based on available data, the classification criteria are not met.

**Components:****strontium bis(2-ethylhexanoate):**

Causes serious eye damage.

**Respiratory or skin sensitisation****Product:**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

**Carcinogenicity****Product:**

Based on available data, the classification criteria are not met.

**Components:****titanium dioxide:**

Suspected of causing cancer.

**Reproductive toxicity****Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

**Components:****strontium bis(2-ethylhexanoate):**

Developmental Toxicity

Suspected of damaging the unborn child.

**STOT - single exposure****Product:**

Based on available data, the classification criteria are not met.

**STOT - repeated exposure****Product:**

Based on available data, the classification criteria are not met.

**Aspiration toxicity****Product:**

May be fatal if swallowed and enters airways.

**Components:****Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

May be fatal if swallowed and enters airways.

**Toxicology, Metabolism, Distribution****Further information****Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

**11.2 Information on other hazards****Endocrine disrupting properties****Product:**

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article

**SÜDWEST Holz-Öl**

57(f) or Commission Delegated regulation (EU) 2017/2100 or  
Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Experience with human exposure****Product:**

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system.

Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness. Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

**Further information****Product:**

Remarks

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

**SECTION 12: ECOLOGICAL INFORMATION****12.1 Toxicity****Product:**

Toxicity to fish

No data available

**12.2 Persistence and degradability****Product:**

Biodegradability

No data available

**Components:****(2-methoxymethylethoxy) propanol:**

Biodegradability

Biodegradation: 75 %

Exposure time: 28 d

Method: OECD Test Guideline 301

rapidly biodegradable

**12.3 Bioaccumulative potential****Product:**

Bioaccumulation

No data available

**Components:****(2-methoxymethylethoxy) propanol:**Partition coefficient: n-  
octanol/water

log Pow: 0,004

Method: OECD Test Guideline 107

**12.4 Mobility in soil****Product:**

Mobility

No data available

**12.5 Results of PBT and vPvB assessment****Product:**

Assessment

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

**SÜDWEST Holz-Öl****12.6 Endocrine disrupting properties****Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**12.7 Other adverse effects****Product:**

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

Product The user is responsible for proper coding and marking of any waste. When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste" Partial and residual quantities can be reused. Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.

Contaminated packaging Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.

Waste key for the unused product 08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

(\*) hazardous waste in terms of the European directive 2008/98/EG

**SECTION 14: TRANSPORT INFORMATION****14.1 UN number or ID number**

ADR	1263
IMDG	1263
IATA	1263

**14.2 UN proper shipping name**

ADR	PAINT
IMDG	PAINT
IATA	Paint

**14.3 Transport hazard class(es)**

ADR	3
IMDG	3
IATA	3

**14.4 Packing group**

**SÜDWEST Holz-Öl****ADR**

Packing group	III
Classification Code	F1
Hazard Identification Number	30
Labels	3
Tunnel restriction code	(D/E)

**IMDG**

Packaging group	III
Labels	3
EmS number	F-E, <u>S-E</u>

**IATA**

Packaging group	III
Labels	3

**14.5 Environmental hazards****ADR**

Environmentally hazardous : no

**IMDG**

Marine pollutant : no

**14.6 Special precautions for user**

Remarks This information is not available.

**14.7 Maritime transport in bulk according to IMO instruments**

Remarks Not applicable

**Additional advice**

ADR ADR: Up to 5 l per inner package, transport as limited quantity in accordance with ADR 3.4.

IMDG IMDG: Up to 5 l per inner package, transport as limited quantity in accordance with IMDG Code 3.4.

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC  
Directive 2010/75/EU 63,5 %

VOC

**SÜDWEST Holz-Öl**

Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EU) No 649/2012 of  
the European Parliament and the  
Council concerning the export and  
import of dangerous chemicals

Not applicable

REACH - Restrictions on the  
manufacture, placing on the  
market and use of certain  
dangerous substances, mixtures  
and articles (Annex XVII)Conditions of restriction for the following entries should be considered:  
(75, 3)REACH - Restrictions on the  
manufacture, placing on the  
market and use of certain  
dangerous substances, mixtures  
and articles (Annex XVII)

strontium bis(2-ethylhexanoate)

Other regulations

Comply with the statutory regulations on health and safety at work.

Take note of Dir 94/33/EC on the protection of young people at work.  
Take note of Dir 92/85/EEC on the safety and health at work of pregnant  
workers.**15.2 Chemical safety assessment**

This information is not available.

**SECTION 16: OTHER INFORMATION**

**Changes from the previous version are indicated by markings in the left-hand margin. The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.**

**Full text of H-Statements**

H302 : Harmful if swallowed.  
H304 : May be fatal if swallowed and enters airways.  
H315 : Causes skin irritation.  
H318 : Causes serious eye damage.  
H351 : Suspected of causing cancer if inhaled.  
H361d : Suspected of damaging the unborn child.

**Full text of other abbreviations**

Acute Tox. : Acute toxicity  
Asp. Tox. : Aspiration hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Repr. : Reproductive toxicity  
Skin Irrit. : Skin irritation

**SÜDWEST Holz-Öl**

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Further information**

## Other information

The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de

# SÜDWEST Holz-Öl