



**SÜDWEST Isolierfarbe L**

Hazard pictograms



Signal word	:	Warning
Hazard statements	:	H226 Flammable liquid and vapour.
Supplemental Hazard Statements		EUH066 Repeated exposure may cause skin dryness or cracking.
Precautionary statements	:	P102 Keep out of reach of children. <b>Prevention:</b> P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. <b>Response:</b> P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower. <b>Disposal:</b> P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

**Additional Labelling**

EUH211 Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Repeated or prolonged exposure may cause skin irritation and dermatitis, due to degreasing properties of the product.

Has a narcotising effect.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2 Mixtures****Components**

Chemical name	CAS-No. EC-No. Index-No. Registration number	Classification	Concentration (% w/w)
titanium dioxide	13463-67-7 236-675-5 01-2119489379-17-XXXX	Carc. 2; H351, Note V, Note W, Note 10	≥ 20 - < 30
Alkanes, C11-13-iso-	246538-78-3 01-2119456810-40-XXXX	Asp. Tox. 1; H304 EUH066	≥ 10 - < 20
Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics	90622-57-4 01-2119472146-39-	Flam. Liq. 3; H226 Aquatic Chronic 4; H413	≥ 2,5 - < 10

**SÜDWEST Isolierfarbe L**

	XXXX	Asp. Tox. 1; H304 EUH066	
2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine	222417-26-7	Skin Irrit. 2; H315 Eye Dam. 1; H318 Aquatic Chronic 1; H410 Aquatic Acute 1; H400  M-Factor (Acute aquatic toxicity): 1	≥ 0,1 - < 0,25
propylidynetrimethanol	77-99-6 201-074-9 01-2119486799-10-XXXX	Repr. 2; H361fd	≥ 0,1 - < 1

For explanation of abbreviations see section 16.

**SECTION 4: FIRST AID MEASURES****4.1 Description of first aid measures**

General advice	When symptoms persist or in all cases of doubt seek medical advice. Never give anything by mouth to an unconscious person. If unconscious, place in recovery position and seek medical advice.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Keep patient warm and at rest. If breathing is irregular or stopped, administer artificial respiration. If symptoms persist, call a physician.
Skin contact	Take off contaminated clothing and shoes immediately. Wash skin thoroughly with soap and water or use recognized skin cleanser. Do NOT use solvents or thinners. If skin irritation persists, call a physician.
Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Seek medical advice.
Ingestion	Rinse mouth with water. If swallowed, seek medical advice immediately and show this container or label. Keep at rest. Do NOT induce vomiting.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms	Inhalation may provoke the following symptoms: Headache Vertigo Drowsiness Unconsciousness
----------	--

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment	Treat symptomatically.
-----------	------------------------

**SÜDWEST Isolierfarbe L**

No information available.

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media**

Suitable extinguishing media      CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Unsuitable extinguishing media      High volume water jet

**5.2 Special hazards arising from the substance or mixture**

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)  
Exposure to decomposition products may be a hazard to health.  
Cool closed containers exposed to fire with water spray.

**5.3 Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus.  
Fight fire with normal precautions from a reasonable distance.

## Additional advice

Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition.  
Ensure adequate ventilation.  
Do not breathe vapour.  
Prevent unauthorized access.

**6.2 Environmental precautions**

The product should not be allowed to enter drains, water courses or the soil.  
If the product contaminates rivers and lakes or drains inform respective authorities.

**6.3 Methods and material for containment and cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).  
Clean with detergents. Avoid solvents.  
Clean contaminated surface thoroughly.  
Dispose of contaminated material as waste according to item 13.

**6.4 Reference to other sections**

Refer to protective measures listed in sections 7 and 8.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling**

## Advice on safe handling

Comply with the statutory regulations on health and safety at work.  
Avoid formation of aerosol.  
Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values.  
The product should only be used in areas from which all naked lights and other sources of ignition have been excluded.  
All metal parts of the mixing and processing equipment must be earthed.  
Operators should wear antistatic footwear and clothing. No sparking tools

**SÜDWEST Isolierfarbe L**

should be used.

**Hygiene measures**

Do not breathe spray, vapour.  
Take off all contaminated clothing immediately.  
Avoid contact with skin, eyes and clothing.  
Wash hands before breaks and immediately after handling the product.  
After washing hands, replenish lost skin oil by means of oily skin ointment.  
When using do not eat, drink or smoke.

**7.2 Conditions for safe storage, including any incompatibilities****Requirements for storage areas and containers**

Store in original container.  
Keep container tightly closed. Never use pressure to empty: container is not a pressure vessel. Nosmoking.  
Prevent unauthorized access.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a well-ventilated place.  
Protect from frost, heat and sunlight.

**Advice on protection against fire and explosion**

Vapours are heavier than air and may spread along floors.  
Vapours may form explosive mixtures with air.  
Keep away from sources of ignition - No smoking.  
Take measures to prevent the build up of electrostatic charge.

**Advice on common storage**

Keep away from combustible materials.  
Keep away from food, drink and animal feedingstuffs.  
Keep away from oxidizing agents and strongly acid or alkaline materials.

**7.3 Specific end use(s)**

For further information, see also Technical Data Sheet for the product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION****8.1 Control parameters****Occupational Exposure Limits**

Contains no substances with occupational exposure limit values.  
The lists that were valid during the creation were used as basis.

|| Monitoring procedures for the assessment of workplace exposure: standard EN 482

**8.2 Exposure controls****Engineering measures**

Provide adequate ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates solvent vapour below the occupational exposure limit values, suitable respiratory - protection must be worn.

Washing facilities / water for rinsing eyes and skin should be available.

**Personal protective equipment**

Eye/face protection : Safety glasses with side-shields conforming to EN166

**Hand protection**

Break through time : 480 min

Glove thickness : 0,4 mm

# SÜDWEST Isolierfarbe L

- Remarks : Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent. Skin that comes into contact with the product should be treated with protective cream. After such contact, the product concerned should under no circumstances be used.
- The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. The choice of an appropriate glove does not only depend on its material but also on other quality features and is different from one producer to the other.
- Skin and body protection : Preventive skin protection
- Long sleeved clothing
- Personal should wear antistatic clothings made of natural fiber or of high temperature resistant synthehic fiber. All parts of the body should be washed after contact.
- Respiratory protection : When workers are facing concentrations above the occupational exposure limit values they must use appropriate certified respirators.
- Breathing protection equipment required in inadequately ventilated places and during spraying.
- In order to avoid inhalation of spray-mist and sanding dust, all spraying and sanding must be done wearing adequate respirator.
- Combination filter A-P2
- Respiratory protection complying with EN 14387.

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1 Information on basic physical and chemical properties

- Physical state : liquid
- Colour : various
- Odour : characteristic

**SÜDWEST Isolierfarbe L**

Odour Threshold : No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : 173 °C

Upper explosion limit / Upper flammability limit : 5,0 %(V)  
Medium: Upper explosion limit

Lower explosion limit / Lower flammability limit : 0,5 %(V)  
Medium: Lower explosion limit

Flash point : 55 °C  
Method: closed cup

Decomposition temperature : No data available

pH : not determined

Viscosity  
Viscosity, dynamic : No data available

Viscosity, kinematic : ca. 346,5 mm<sup>2</sup>/s (40 °C)

Flow time : > 90 s at 20 °C  
Cross section: 4 mm  
Method: ISO 2431

**SÜDWEST Isolierfarbe L**

Solubility(ies)  
Water solubility : insoluble

Partition coefficient: n-  
octanol/water : not determined

Vapour pressure : 0,6 hPa (20 °C)

Density : ca. 1,414 g/cm<sup>3</sup>

Relative vapour density : No data available

**9.2 Other information**

Explosives : Not explosive  
In use may form flammable/explosive vapour-air mixture.

Oxidizing properties : Not applicable

Flammability (liquids) : Not applicable

Self-ignition : not auto-flammable

Evaporation rate : not applicable

**SÜDWEST Isolierfarbe L****SECTION 10: STABILITY AND REACTIVITY****10.1 Reactivity**

No dangerous reaction known under conditions of normal use.

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

Hazardous reactions                      No dangerous reaction known under conditions of normal use.  
Vapours may form explosive mixture with air.

**10.4 Conditions to avoid**

Conditions to avoid                      Direct sources of heat.  
Strong sunlight for prolonged periods.

**10.5 Incompatible materials**

Materials to avoid                      Strong acids and strong bases  
Strong oxidizing agents

**10.6 Hazardous decomposition products**

No decomposition if stored and applied as directed.

**SECTION 11: TOXICOLOGICAL INFORMATION****11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008****Acute toxicity****Product:**

Acute oral toxicity                      Based on available data, the classification criteria are not met.

Acute inhalation toxicity              Based on available data, the classification criteria are not met.

Acute dermal toxicity                  Based on available data, the classification criteria are not met.

**Skin corrosion/irritation****Product:**

Repeated exposure may cause skin dryness or cracking.

**Components:****Alkanes, C11-13-iso-:**

Repeated exposure may cause skin dryness or cracking.

**Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:**

Repeated exposure may cause skin dryness or cracking.

**2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine:****Species**

Rabbit

**Method**

OECD Test Guideline 404

Causes skin irritation.

**Serious eye damage/eye irritation****Product:**

Based on available data, the classification criteria are not met.

**Components:****2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine:**

**SÜDWEST Isolierfarbe L**

Species Rabbit  
Method OECD Test Guideline 405  
Causes serious eye damage.

**Respiratory or skin sensitisation****Product:**

Based on available data, the classification criteria are not met.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

**Carcinogenicity****Product:**

Based on available data, the classification criteria are not met.

**Components:****titanium dioxide:**

Suspected of causing cancer.

**Reproductive toxicity****Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

**Components:****propylidynetrimethanol:**

Effects on fertility

Suspected of damaging fertility.

Developmental Toxicity

Suspected of damaging the unborn child.

**STOT - single exposure****Product:**

Based on available data, the classification criteria are not met.

**STOT - repeated exposure****Product:**

Based on available data, the classification criteria are not met.

**Aspiration toxicity****Product:**

Based on available data, the classification criteria are not met.

**Components:****Alkanes, C11-13-iso-:**

May be fatal if swallowed and enters airways.

**Hydrocarbons, C11-C12, isoalkanes, < 2% aromatics:**

May be fatal if swallowed and enters airways.

**Toxicology, Metabolism, Distribution****Further information****Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

**11.2 Information on other hazards****Endocrine disrupting properties****Product:**

Assessment

: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article

**SÜDWEST Isolierfarbe L**

57(f) or Commission Delegated regulation (EU) 2017/2100 or  
Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Experience with human exposure****Product:**

General Information

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system.

Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness. Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

**Further information****Product:**

Remarks

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

**SECTION 12: ECOLOGICAL INFORMATION****12.1 Toxicity****Product:**

Toxicity to fish

No data available

**Components:**

**2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine:**

Toxicity to fish

LC50 (Oncorhynchus mykiss (rainbow trout)): 0,89 mg/l

Exposure time: 96 h

Test Type: static test

Method: OECD Test Guideline 202

M-Factor (Acute aquatic toxicity)

1

**12.2 Persistence and degradability****Product:**

Biodegradability

No data available

**Components:**

**2-Propenoic acid, butyl ester, homopolymer, reaction products with N,N-dimethyl-1,3-propanediamine:**

Biodegradability

not rapidly degradable

Method: OECD Test Guideline 301B

**propylidynetrimethanol:**

Biodegradability

not rapidly degradable

Biodegradation: 6 %

Exposure time: 28 d

**12.3 Bioaccumulative potential****Product:**

Bioaccumulation

No data available

**Components:****propylidynetrimethanol:**

Partition coefficient: n-

log Pow: -0,47

**SÜDWEST Isolierfarbe L**

octanol/water

**12.4 Mobility in soil****Product:**

Mobility No data available

**12.5 Results of PBT and vPvB assessment****Product:**

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

**12.6 Endocrine disrupting properties****Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**12.7 Other adverse effects****Product:**

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

Product The user is responsible for proper coding and marking of any waste. When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste" Partial and residual quantities can be reused. Fluid remains constitute hazardous waste and should not be poured into the sewage system. They should be taken to a local waste disposal site.

Contaminated packaging Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.

Waste key for the unused product 08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

(\*) hazardous waste in terms of the European directive 2008/98/EG

**SECTION 14: TRANSPORT INFORMATION****14.1 UN number or ID number**

ADR 1263

IMDG 1263

IATA 1263

**14.2 UN proper shipping name**

ADR PAINT

**SÜDWEST Isolierfarbe L**

<b>IMDG</b>	PAINT
-------------	-------

<b>IATA</b>	Paint
-------------	-------

**14.3 Transport hazard class(es)**

<b>ADR</b>	3
------------	---

<b>IMDG</b>	3
-------------	---

<b>IATA</b>	3
-------------	---

**14.4 Packing group****ADR**

Packing group	III
---------------	-----

Classification Code	F1
---------------------	----

Hazard Identification Number	30
------------------------------	----

Labels	3
--------	---

Tunnel restriction code	(D/E)
-------------------------	-------

**IMDG**

Packaging group	III
-----------------	-----

Labels	3
--------	---

EmS number	F-E, <u>S-E</u>
------------	-----------------

**IATA**

Packaging group	III
-----------------	-----

Labels	3
--------	---

**14.5 Environmental hazards****ADR**

Environmentally hazardous	: no
---------------------------	------

**IMDG**

Marine pollutant	: no
------------------	------

**14.6 Special precautions for user**

Remarks	This information is not available.
---------	------------------------------------

**14.7 Maritime transport in bulk according to IMO instruments**

Remarks	Not applicable
---------	----------------

**Additional advice**

ADR: Packages < 450l: No dangerous goods (ADR 2.2.3.1.5), IMDG: Packages < 450l: No dangerous goods (IMDG 2.3.2.5).

**SÜDWEST Isolierfarbe L****SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC  
 Directive 2010/75/EU 21,2 %

VOC  
 Directive 2004/42/EC 20,3 %  
 286,6 g/l

EU limit value for this product (cat. A/g) :350 g/l This product contains  
 max350 g/lVOC.

Regulation (EU) No 649/2012 of  
 the European Parliament and the  
 Council concerning the export and  
 import of dangerous chemicals Not applicable

REACH - Restrictions on the  
 manufacture, placing on the  
 market and use of certain  
 dangerous substances, mixtures  
 and articles (Annex XVII) Conditions of restriction for the following entries should be considered:  
 (3)

Other regulations Comply with the statutory regulations on health and safety at work.  
 Take note of Dir 94/33/EC on the protection of young people at work.  
 Take note of Dir 92/85/EEC on the safety and health at work of pregnant  
 workers.

**15.2 Chemical safety assessment**

This information is not available.

**SECTION 16: OTHER INFORMATION**

**Changes from the previous version are indicated by markings in the left-hand margin.  
 The information in this Safety Data Sheet corresponds to our present state of knowledge and  
 conforms to both national and EU legislation. The user's working conditions are, however,  
 beyond our knowledge and control. The user is responsible for complying with all necessary  
 legal requirements. The information in this Safety Data Sheet describes the safety requirements  
 of our product and does not constitute any assurance of product properties.**

**Full text of H-Statements**

H226 : Flammable liquid and vapour.  
 H304 : May be fatal if swallowed and enters airways.  
 H315 : Causes skin irritation.  
 H318 : Causes serious eye damage.  
 H351 : Suspected of causing cancer if inhaled.  
 H361fd : Suspected of damaging fertility. Suspected of damaging the unborn  
 child.

**SÜDWEST Isolierfarbe L**

- H400 : Very toxic to aquatic life.  
H410 : Very toxic to aquatic life with long lasting effects.  
H413 : May cause long lasting harmful effects to aquatic life.

**Full text of other abbreviations**

- Aquatic Acute : Short-term (acute) aquatic hazard  
Aquatic Chronic : Long-term (chronic) aquatic hazard  
Asp. Tox. : Aspiration hazard  
Carc. : Carcinogenicity  
Eye Dam. : Serious eye damage  
Flam. Liq. : Flammable liquids  
Repr. : Reproductive toxicity  
Skin Irrit. : Skin irritation

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Further information**

Other information : The assessment was carried out in accordance with Article 6 (5) and Appendix I of EC Directive no. 1272/2008.

It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de

# SÜDWEST Isolierfarbe L