



**SÜDWEST Schnellhärter**

Specific target organ toxicity -  
single exposure, Category 3,  
Central nervous system

H336: May cause drowsiness or dizziness.

Specific target organ toxicity -  
single exposure, Category 3,  
Respiratory system

H335: May cause respiratory irritation.

**2.2 Label elements****Labelling (REGULATION (EC) No 1272/2008)**

Hazard pictograms



Signal word : Warning

Hazard statements : H226 Flammable liquid and vapour.  
H317 May cause an allergic skin reaction.  
H335 May cause respiratory irritation.  
H336 May cause drowsiness or dizziness.

Supplemental Hazard Statements EUH066 Repeated exposure may cause skin dryness or cracking.

Precautionary statements : **Prevention:**  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P271 Use only outdoors or in a well-ventilated area.  
P280 Wear protective gloves/ eye protection/ face protection.  
**Response:**  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water or shower.  
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.  
**Disposal:**  
P501 Contents/container to be disposed of through approved disposal contractor or taken to municipal collection point.

**Hazardous components which must be listed on the label:**

n-butyl acetate  
Isophorone diisocyanate homopolymer

**2.3 Other hazards**

This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher.

Ecological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

Toxicological information: The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS****3.2 Mixtures****Components**

Chemical name	CAS-No.	Classification	Concentration
---------------	---------	----------------	---------------

**SÜDWEST Schnellhärter**

	EC-No. Index-No. Registration number		(% w/w)
n-butyl acetate	123-86-4 204-658-1 607-025-00-1 01-2119485493-29-XXXX	Flam. Liq. 3; H226 STOT SE 3; H336 (Central nervous system) EUH066	≥ 70 - < 80
Isophorone diisocyanate homopolymer	53880-05-0 500-125-5 01-2119488734-24-XXXX	Skin Sens. 1; H317 STOT SE 3; H335	≥ 20 - < 25
4-isocyanatosulphonyltoluene	4083-64-1 223-810-8 615-012-00-7 01-2119980050-47-XXXX	Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 EUH014  specific concentration limit Eye Irrit. 2 ≥ 5 % STOT SE 3 ≥ 5 % Skin Irrit. 2 ≥ 5 %	≥ 0,1 - < 1
3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate	4098-71-9 223-861-6 615-008-00-5 01-2119490408-31-XXXX	Acute Tox. 1; H330 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317 Aquatic Chronic 2; H411  specific concentration limit Resp. Sens. 1; H334 ≥ 0,5 % Skin Sens. 1; H317 ≥ 0,5 %	≥ 0,025 - < 0,1

For explanation of abbreviations see section 16.

**SECTION 4: FIRST AID MEASURES****4.1 Description of first aid measures**

General advice	When symptoms persist or in all cases of doubt seek medical advice. First aider needs to protect himself.
Inhalation	Move to fresh air in case of accidental inhalation of vapours or decomposition products. Consult a physician after significant exposure.
Skin contact	Take off contaminated clothing and shoes immediately.

**SÜDWEST Schnellhärter**

Take off contaminated clothing and wash it before reuse.  
Wash skin thoroughly with soap and water or use recognized skin cleanser.  
Do NOT use solvents or thinners.  
If symptoms persist, call a physician.

Eye contact	In case of eye contact, remove contact lens and rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Consult a physician. Eye rinsing bottle must be kept immediately to hand.
Ingestion	Never give anything by mouth to an unconscious person. Clean mouth with water and drink afterwards plenty of water. Do NOT induce vomiting. Obtain medical attention.

**4.2 Most important symptoms and effects, both acute and delayed**

Symptoms	Contact with eyes or skin causes irritation. Repeated or prolonged skin contact may cause skin irritation and/or dermatitis and sensitisation of susceptible persons.
----------	--

**4.3 Indication of any immediate medical attention and special treatment needed**

Treatment	Treat symptomatically. When symptoms persist or in all cases of doubt seek medical advice.
-----------	---

**SECTION 5: FIREFIGHTING MEASURES****5.1 Extinguishing media**

Suitable extinguishing media	CO <sub>2</sub> , extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.
------------------------------	---

Unsuitable extinguishing media	High volume water jet
--------------------------------	-----------------------

**5.2 Special hazards arising from the substance or mixture**

Fire may cause evolution of:  
Carbon monoxide  
Carbon dioxide (CO<sub>2</sub>)  
Nitrogen oxides (NO<sub>x</sub>)

**5.3 Advice for firefighters**

In the event of fire, wear self-contained breathing apparatus.  
Complete suit protecting against chemicals

**Additional advice**

Water for fire fighting must not be emptied into drains, earth or waters.  
Contaminated water and earth must be disposed of according to official local regulations.

**SECTION 6: ACCIDENTAL RELEASE MEASURES****6.1 Personal precautions, protective equipment and emergency procedures**

Do not breathe fumes / aerosol  
Avoid contact with skin and eyes.  
Use personal protective equipment.  
Ensure adequate ventilation.  
Prevent unauthorized access.

**6.2 Environmental precautions**

Prevent seepage into sewage system, workpits and cellars.  
Do not allow contact with soil, surface or ground water.

**6.3 Methods and material for containment and cleaning up**

Contain spillage, and then collect with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

**SÜDWEST Schnellhärter**

Subsequently put in the waste container. Do not seal ( CO2 may be given off )  
Clean contaminated surface thoroughly.  
Suitable cleaning agents  
Water  
Should not be released into the environment.

**6.4 Reference to other sections**

Refer to protective measures listed in sections 7 and 8.

**SECTION 7: HANDLING AND STORAGE****7.1 Precautions for safe handling**

Advice on safe handling	Avoid contact with skin and eyes. Do not breathe vapours or spray mist. Persons with a history of skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used. Comply with the statutory regulations on health and safety at work. Do not re-use empty containers.
Hygiene measures	Take off immediately all contaminated clothing. Keep working clothes separately. Wash hands before breaks and immediately after handling the product. After washing hands, replenish lost skin oil by means of oily skin ointment. When using do not eat, drink or smoke.

**7.2 Conditions for safe storage, including any incompatibilities**

Requirements for storage areas and containers	Keep out of reach of children. Store in original container. Containers which are opened must be carefully resealed and kept upright to prevent leakage. Protect from frost, heat and sunlight. Keep in a dry place.
Advice on protection against fire and explosion	Prevent the creation of flammable or explosive concentrations of vapour in air and avoid vapour concentration higher than the occupational exposure limit values. Vapours are heavier than air and may spread along floors. Flammable gas-air mixtures may be formed in empty receptacles. Keep product and empty container away from heat and sources of ignition. The product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Operators should wear antistatic footwear and clothing. No sparking tools should be used.
Advice on common storage	Keep away from oxidizing agents, strongly acid or alkaline materials, as well as of amines, alcohols and water.

**7.3 Specific end use(s)**

For further information, see also Technical Data Sheet for the product.

**SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION**

**SÜDWEST Schnellhärter****8.1 Control parameters****Occupational Exposure Limits**

Components	CAS-No.	Value type (Form of exposure)	Control parameters	Basis
n-butyl acetate	123-86-4	STEL	150 ppm 723 mg/m <sup>3</sup>	2019/1831/EU
Further information: Indicative				
		TWA	50 ppm 241 mg/m <sup>3</sup>	2019/1831/EU
Further information: Indicative				

The lists that were valid during the creation were used as basis.

Monitoring procedures for the assessment of workplace exposure: standard EN 482

**8.2 Exposure controls****Engineering measures**

Washing facilities / water for rinsing eyes and skin should be available.

**Personal protective equipment**

Eye/face protection : Safety glasses with side-shields conforming to EN166

**Hand protection**

Material : Nitrile rubber

Glove thickness : 0,4 mm

Wearing time : < 60 min

Material : Fluorinated rubber

Glove thickness : 0,7 mm

Wearing time : > 480 min

Remarks : Gloves made of the following materials are suitable as protection from splashes: Gloves made of nitrile rubber, e.g. KCL 730 Camatril® Velours (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equivalent. Wetted gloves must be disposed of immediately!

Gloves in the following material can be used for prolonged contact up to max. 8 hours:

Fluorocarbon rubber gloves eg. KCL 890 Vitoject® (Kächele-Cama-Latex GmbH, Hotline: 0049(0)6659-87-300, kcl-uk@kcl.de), or equal. Dispose of wetted gloves at the end of the shift!

The selected protective gloves have to satisfy the specifications of Regulation (EU) 2016/425 and the standard EN 374 derived from it. Cotton undergloves are recommendable when wearing protective

**SÜDWEST Schnellhärter**

gloves! To avoid skin problems reduce the wearing of gloves to the required minimum. Only use chemical-protective gloves with CE-labelling of category III.

- Skin and body protection : Impervious clothing  
If splashes are likely to occur, wear:  
Solvent-resistant apron and boots
- Respiratory protection : For brief exposure or low level concentrations use a respiratory filter;  
for more intense or longer exposure use a self-contained respiratory protective device.  
Respiratory filter for brief exposure:  
Combination filter A-P2  
Respiratory protection complying with EN 14387.
- Protective measures : The instructions for the personal protective equipment apply to the handling of both individual components and of the ready-to-use mixture.

**SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES****9.1 Information on basic physical and chemical properties**

- Physical state : liquid
- Colour : Yellowish
- Odour : characteristic
- Odour Threshold : No data available
- Melting point/freezing point : No data available

**SÜDWEST Schnellhärter**

Initial boiling point and boiling range	:	> 124 °C
Upper explosion limit / Upper flammability limit	:	7,5 %(V) Medium: Upper explosion limit
Lower explosion limit / Lower flammability limit	:	1,2 %(V) Medium: Lower explosion limit
Flash point	:	27,5 °C
Decomposition temperature	:	No data available
pH	:	8 - 9,9 (23 °C) Concentration: 1 % hydrolyses
Viscosity Viscosity, dynamic	:	No data available
Viscosity, kinematic	:	ca. 10,7 mm <sup>2</sup> /s (40 °C)
Flow time	:	ca. 10 s at 20 °C Method: ISO 2431
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	not determined

**SÜDWEST Schnellhärter**

Vapour pressure : 13 hPa (20 °C)

Density : ca. 0,935 g/cm<sup>3</sup>

Relative vapour density : No data available

**9.2 Other information**

Explosives : Not explosive  
In use may form flammable/explosive vapour-air mixture.

Oxidizing properties : Not applicable

Self-ignition : not auto-flammable

Evaporation rate : not determined

**SECTION 10: STABILITY AND REACTIVITY****10.1 Reactivity**

Container can be pressurized by carbon dioxide due to reaction with humid air and/or water.

**10.2 Chemical stability**

Stable under normal conditions.

**10.3 Possibility of hazardous reactions**

Hazardous reactions Amines and alcohols cause exothermic reactions.  
Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.  
With water (moisture): CO<sub>2</sub> is produced; pressure may build up inside closed containers (danger of bursting)



**SÜDWEST Schnellhärter****3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

Species Rabbit  
Causes serious eye irritation.

**Respiratory or skin sensitisation****Product:**

May cause sensitisation by skin contact.  
Does not cause respiratory sensitisation.

**Components:****Isophorone diisocyanate homopolymer:**

May cause an allergic skin reaction.

**4-isocyanatosulphonyltoluene:**

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

May cause an allergic skin reaction.

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

**Germ cell mutagenicity****Product:**

Genotoxicity in vitro

Based on available data, the classification criteria are not met.

**Carcinogenicity****Product:**

Based on available data, the classification criteria are not met.

**Reproductive toxicity****Product:**

Effects on fertility

Based on available data, the classification criteria are not met.

Developmental Toxicity

Based on available data, the classification criteria are not met.

**STOT - single exposure****Product:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation., May cause drowsiness or dizziness.

**Components:****n-butyl acetate:**

Exposure routes

inhalation (vapour)

Assessment

May cause drowsiness or dizziness.

**Isophorone diisocyanate homopolymer:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation.

**4-isocyanatosulphonyltoluene:**

Exposure routes

Inhalation

Assessment

May cause respiratory irritation.

**3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

Exposure routes

Inhalation

Target Organs

Upper respiratory tract

Assessment

May cause respiratory irritation.

**STOT - repeated exposure****Product:**

Based on available data, the classification criteria are not met.

**SÜDWEST Schnellhärter****Aspiration toxicity****Product:**

Based on available data, the classification criteria are not met.

**Toxicology, Metabolism, Distribution****Further information****Product:**

The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

**11.2 Information on other hazards****Endocrine disrupting properties****Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**Experience with human exposure****Product:****General Information**

Exposure to component solvent vapours concentration in excess of the stated occupational exposure limit may result in adverse health effects.

Such as: mucous membrane irritation, respiratory system irritation, adverse effects on kidney, liver and central nervous system. Symptoms and signs: headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases loss of consciousness. Long-term or repeated contact with the product leads to degreasing of the skin and can cause nonallergenic contact skin damage (contact dermatitis) and / or the resorption of substances.

Solvent sprays can cause irritation and reversible damage to the eye.

**Further information****Product:****Remarks**

: The product itself has not been tested. The mixture is classified in accordance with Annex I to EC Directive 1272/2008. (See sections 2 and 3 for details).

**SECTION 12: ECOLOGICAL INFORMATION****12.1 Toxicity****Product:****Toxicity to fish**

No data available

**12.2 Persistence and degradability****Product:****Biodegradability**

Together with water the resin turns at the surface into a solid and insoluble reaction product (polycarbamide) with a high melting point, by forming carbon dioxide.

**Components:****n-butyl acetate:****Biodegradability**

rapidly degradable  
Biodegradation: > 90 %  
Exposure time: 28 d

**3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:****Biodegradability**

Test Type: aerobic

**SÜDWEST Schnellhärter**

Inoculum: activated sludge  
not rapidly degradable  
Biodegradation: 0 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**12.3 Bioaccumulative potential****Product:**

Bioaccumulation No data available

**Components:****n-butyl acetate:**

Partition coefficient: n-  
octanol/water log Pow: 2,3  
Method: OECD Test Guideline 117

**3-isocyanatomethyl-3,5,5-trimethylcyclohexyl isocyanate:**

Bioaccumulation Bioaccumulation is unlikely.

**12.4 Mobility in soil****Product:**

Mobility No data available

**12.5 Results of PBT and vPvB assessment****Product:**

Assessment This substance/mixture contains no components considered to be either persistent, bioaccumulative and toxic (PBT), or very persistent and very bioaccumulative (vPvB) at levels of 0.1% or higher..

**12.6 Endocrine disrupting properties****Product:**

Assessment : The substance/mixture does not contain components considered to have endocrine disrupting properties according to REACH Article 57(f) or Commission Delegated regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at levels of 0.1% or higher.

**12.7 Other adverse effects****Product:**

Additional ecological information Do not allow product to enter into ground water, bodies of water or sewage systems.

**SECTION 13: DISPOSAL CONSIDERATIONS****13.1 Waste treatment methods**

Product The user is responsible for proper coding and marking of any waste. When used as recommended, the waste code can be selected according to the code of the European Waste Catalogue (EWC), category 17.09 "Other Construction and Demolition Waste" Unhardened product residues should be disposed of under the recommended waste code number.

Contaminated packaging Packaging that is not properly emptied must be disposed of as the unused product. Empty packaging should be recycled through disposal systems.

Waste key for the unused product 08 01 11\* waste paint and varnish containing organic solvents or other hazardous substances

(\* ) hazardous waste in terms of the European directive 2008/98/EG

**SÜDWEST Schnellhärter****SECTION 14: TRANSPORT INFORMATION****14.1 UN number or ID number**

<b>ADR</b>	1866
<b>IMDG</b>	1866
<b>IATA</b>	1866

**14.2 UN proper shipping name**

<b>ADR</b>	RESIN SOLUTION
<b>IMDG</b>	RESIN SOLUTION
<b>IATA</b>	Resin solution

**14.3 Transport hazard class(es)**

<b>ADR</b>	3
<b>IMDG</b>	3
<b>IATA</b>	3

**14.4 Packing group**

<b>ADR</b>	
Packing group	III
Classification Code	F1
Hazard Identification Number	30
Labels	3
Tunnel restriction code	(D/E)
<b>IMDG</b>	
Packaging group	III
Labels	3
EmS number	F-E, <u>S-E</u>
<b>IATA</b>	
Packaging group	III
Labels	3

**14.5 Environmental hazards**

<b>ADR</b>	
Environmentally hazardous	: no
<b>IMDG</b>	
Marine pollutant	: no

**14.6 Special precautions for user**

**SÜDWEST Schnellhärter**

Remarks This information is not available.

**14.7 Maritime transport in bulk according to IMO instruments**

Remarks Not applicable

**Additional advice**

ADR ADR: Up to 5 l per inner package, transport as limited quantity in accordance with ADR 3.4.  
IMDG IMDG: Up to 5 l per inner package, transport as limited quantity in accordance with IMDG Code 3.4.

**SECTION 15: REGULATORY INFORMATION****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

VOC  
Directive 2010/75/EU 76,8 %

VOC  
Directive 2004/42/EC

does not fall under Directive 2004/42/EC

Regulation (EU) No 649/2012 of the European Parliament and the Council concerning the export and import of dangerous chemicals Not applicable

REACH - Restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles (Annex XVII)

Conditions of restriction for the following entries should be considered:  
(75, 3)

4-isocyanatosulphonyltoluene

Further notes For further information, see also Technical Data Sheet for the product.

**15.2 Chemical safety assessment**

This information is not available.

**SECTION 16: OTHER INFORMATION**

Changes from the previous version are indicated by markings in the left-hand margin.

**SÜDWEST Schnellhärter**

The information in this Safety Data Sheet corresponds to our present state of knowledge and conforms to both national and EU legislation. The user's working conditions are, however, beyond our knowledge and control. The user is responsible for complying with all necessary legal requirements. The information in this Safety Data Sheet describes the safety requirements of our product and does not constitute any assurance of product properties.

**Full text of H-Statements**

H226	: Flammable liquid and vapour.
H315	: Causes skin irritation.
H317	: May cause an allergic skin reaction.
H319	: Causes serious eye irritation.
H330	: Fatal if inhaled.
H334	: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	: May cause respiratory irritation.
H336	: May cause drowsiness or dizziness.
H411	: Toxic to aquatic life with long lasting effects.

**Full text of other abbreviations**

Acute Tox.	: Acute toxicity
Aquatic Chronic	: Long-term (chronic) aquatic hazard
Eye Irrit.	: Eye irritation
Flam. Liq.	: Flammable liquids
Resp. Sens.	: Respiratory sensitisation
Skin Irrit.	: Skin irritation
Skin Sens.	: Skin sensitisation
STOT SE	: Specific target organ toxicity - single exposure

ADN - European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways; ADR - Agreement concerning the International Carriage of Dangerous Goods by Road; AIIC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CLP - Classification Labelling Packaging Regulation; Regulation (EC) No 1272/2008; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECHA - European Chemicals Agency; EC-Number - European Community number; ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RID - Regulations concerning the International Carriage of Dangerous Goods by Rail; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; SVHC - Substance of Very High Concern; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TRGS - Technical Rule for Hazardous Substances; TSCA - Toxic Substances Control Act (United States); UN - United Nations; vPvB - Very Persistent and Very Bioaccumulative

**Further information**

Other information	It is possible in the interim period that you may find different markings on packaging compared to the Material Safety Data Sheet until stocks have been used up. We ask for your understanding in this matter.
-------------------	---

# SÜDWEST Schnellhärter

Department issuing MSDS  
REG\_EU / EN

sdb@suedwest.de