



TECHNICAL DATA SHEET

30034

2K-ACRYL-HÄRTER

AREA OF APPLICATION

Use SÜDWEST 2K-Acryl-Härter as component B for the following SÜDWEST products (component A) when applying by spraying:

SÜDWEST 2K-Acryl-Hochglanzlack
SÜDWEST 2K-Acryl-Seidenglanzlack
SÜDWEST 2K-All-Grund

COLOUR SHADE: colourless

CONTAINER: 250 ml, 1 l

AREA OF APPLICATION

MATERIAL PREPARATION:

Wherever possible, the two components A and B should be mixed exactly in accordance with the specified **mixing ratio by volume**. Decant component A into a suitable container and add the required amount of 2K-Acryl-Härter. This can be done in a cylindrical container with a measuring stick, for example. Stir vigorously then transfer to another container and mix thoroughly once again. Avoid mixing in large quantities of air if possible.

Mixing ratios

SÜDWEST 2K-Acryl-Hochglanzlack: 2:1
(two parts component A to one part component B)

SÜDWEST 2K-Acryl-Seidenglanzlack: 2:1
(two parts component A to one part component B)

SÜDWEST 2K-All-Grund 6:1
(six parts component A to one part component B)

The materials have a product-specific pot life once they are ready to use. Do not

continue to apply the material mixture once the pot life has expired. Please also observe the Technical Data Sheet for component A.

SPECIAL INFORMATION

Danger! Only for commercial users / experts. Contains isocyanates. May produce an allergic reaction. For more information about the safe use of the product, refer to the label and the current SDS.

VDL DECLARATION

Acetates, aromatic hydrocarbon mixtures, p-Toluenesulfonyl isocyanates, aliphatic polyisocyanates

GISCODE PU35

GENERAL SAFETY ADVICE

Good ventilation must be ensured while paints and varnishes are being applied and are drying. Keep away from food, drink, and animal feed. Avoid contact with skin and eyes. Do not breathe in dust during sanding work. Only use in well-ventilated areas. Do not eat, drink, smoke, or inhale snuff tobacco during work. Keep out of reach of children. Do not allow to enter the sewer system or bodies of water. If rivers, lakes, or drains become contaminated, inform the relevant authorities in accordance with the local laws.

Further information and the current SDS are available at www.suedwest.de

STORAGE

Close opened containers so that they are airtight after use. Store in cool but frost-free conditions.

DISPOSAL

Only recycle empty containers.

TECHNICAL CONSULTATION

Our sales force will be happy to answer any questions which have not been covered by this Technical Data Sheet. Our technical customer service team at the factory is also available to answer any detailed queries you may have. (06324/709-0)

DISCLAIMER

We are committed to taking the utmost care. However, we are only able to provide general information based on our own experiences, developments, and investigations, and these naturally cannot take the individual conditions of a project (substrates, weather conditions, other conditions) into account. The applicator is therefore obliged to maintain their knowledge in accordance with the state of the art and act responsibly. Our employees are available to provide specific advice and will be happy to do so. We accept no responsibility for the use of the product in combination with other products. The data provided in this Technical Data Sheet does not constitute binding information or liability. Furthermore, suspension or the appearance of a subsequent edition will invalidate this Technical Data Sheet; information about this can be accessed at any time on our website: www.suedwest.de.

STATUS: 2023/AUGUST/KM