



TECHNICAL DATA SHEET

30036

2K-ACRYL-VERDÜNNUNG

AREA OF APPLICATION

2K-Acryl-Verdünnung is a thinning agent for paints and spray paints. It can also be used to clean tools after they have been used to apply SÜDWEST two-component products.

2K-Acryl-Verdünnung can also be used as a thinning agent for the following SÜDWEST products:

Single-component products:

SÜDWEST All-Grund
SÜDWEST Unterwasser-Farbe

Two-component products:

SÜDWEST 2K-Acryl-Hochglanzlack
SÜDWEST 2K-Acryl-Seidenglanzlack
SÜDWEST 2K-Acryl Strukturlack SG/GL
SÜDWEST 2K-All-Grund
SÜDWEST 2K-Epoxi-Füllprimer

Material preparation for two-component products:

After mixing the two components A and B, please refer to the Technical Data Sheet for both components and adjust the material to spray viscosity.

The materials have a product-specific pot life once they are ready to use. Do not continue to thin or apply the material mixture once the pot life has expired. Please also refer to the relevant information in the Technical Data Sheets for the products.

COLOUR SHADE: colourless

CONTAINER: 1 l

SPECIAL INFORMATION

Please observe the SDS.

VDL DECLARATION

Acetates, aromatics, ketones

GISCODE M-VM04

GENERAL SAFETY ADVICE

Good ventilation must be ensured while paints and varnishes are being applied and are drying. Keep away from food, drink, and animal feed. Avoid contact with skin and eyes. Do not breathe in dust during sanding work. Only use in well-ventilated areas. Do not eat, drink, smoke, or inhale snuff tobacco during work.

Keep out of reach of children. Do not allow to enter the sewer system or bodies of water. If rivers, lakes, or drains become contaminated, inform the relevant authorities in accordance with the local laws.

Further information and the current SDS are available at www.suedwest.de

STORAGE

Close opened containers so that they are airtight after use. Store in cool but frost-free conditions.

DISPOSAL

Only recycle empty containers.

TECHNICAL CONSULTATION

Our sales force will be happy to answer any questions which have not been covered by this Technical Data Sheet. Our technical customer service team at the factory is also available to answer any detailed queries you may have. (06324/709-0)

DISCLAIMER

We are committed to taking the utmost care. However, we are only able to provide general information based on our own experiences, developments, and investigations, and these naturally cannot take the individual conditions of a project (substrates, weather conditions, other conditions) into account. The applicator is therefore obliged to maintain their knowledge in accordance with the state of the art and act responsibly. Our employees are available to provide specific advice and will be happy to do so. We accept no responsibility for the use of the product in combination with other products. The data provided in this Technical Data Sheet does not constitute binding information or liability.

Furthermore, suspension or the appearance of a subsequent edition will invalidate this Technical Data Sheet; information about this can be accessed at any time on our website: www.suedwest.de.

STATUS: 2023/AUGUST/KM