



TECHNICAL DATA SHEET

30650 ADDITIV R

AREA OF APPLICATION

Supplement for SÜDWEST 2K-Epoxi-Siegel to achieve R10 slip resistance class in accordance with DIN 51130.

PROPERTIES

COVERAGE: 250 g per 10 kg 2K-Epoxi-Siegel base material.

AREA

GENERAL RULES:

The substrate must be prepared and the coating work performed in accordance with the state of the art. All coatings and preliminary work should always be geared towards the project and the requirements it is exposed to. Please also observe the current BFS data sheets, published by the German Federal Committee for Paints and the Protection of Objects.

Also see German construction contract procedures (VOB), Part C, DIN 18363, Paragraph 3 "Painting and coating work". Treating/removing layers of paint by sanding, welding, burning off, etc. can cause harmful dust and/or vapours. Only carry out work in well-ventilated areas. Use appropriate breathing apparatus/protective equipment, if necessary. Substrates must be checked in terms of their load-bearing capacity and suitability for subsequent coatings. If necessary, create a test surface and test the adhesion.

APPLICATION:

Please refer to the product Technical Data Sheet for SÜDWEST 2K-Epoxi-Siegel.

MATERIAL PREPARATION:

An entire 250 g bottle of SÜDWEST is added to a 10 kg pail of 2K-Epoxi-Siegel base material Additiv R. The material is homogenised for a minimum stirring time of 3 minutes with a mixing paddle running at low speed (max. 300 rpm). Never add pigment concentrate and SÜDWEST Additiv R to the container at the same time. Alternatively, the material can also be homogenised in an All-Color vibrator. The mixture must be applied immediately once the Additiv R has been stirred into the 2K-EpoxiSiegel.

VDL (GERMAN PAINT AND PRINTING INK ASSOCIATION) DECLARATION

Silicic acid

GENERAL SAFETY ADVICE

Good ventilation must be ensured while paints and varnishes are being applied and are drying. Keep away from food, drink, and animal feed. Avoid contact with skin and eyes. Do not breathe in dust during sanding work. Keep out of reach of children. Do not allow to enter ground water, bodies of water, or the sewer system in undiluted or large quantities. Further information and the current SDS are available at www.suedwest.de

STORAGE

Keep containers tightly closed and store in a dry place.

DISPOSAL

Only return empty containers for recycling. Dispose of containers with residues at the responsible hazardous waste centre. Dispose of dried paint brushes and rollers with

residual waste. Do not dispose of paint or rinse painting tools in sinks or drains.

TECHNICAL CONSULTATION

Our sales representatives will be happy to answer any questions which have not been covered by this Technical Data Sheet. Our technical customer service team at the factory is also available to answer any detailed queries you may have. (06324/709-0).

DISCLAIMER

We are committed to taking the utmost care. However, we are only able to provide general information based on our own experiences, developments, and investigations, and these naturally cannot take the individual conditions of a project (substrates, weather conditions, other conditions) into account. The applicator is therefore obliged to maintain their knowledge in accordance with the state of the art and act responsibly. Our employees are available to provide specific advice and will be happy to do so. We accept no responsibility for the use of the product in combination with other products. The data provided in this Technical Data Sheet does not constitute binding information or liability.

Furthermore, suspension or the appearance of a subsequent edition will invalidate this Technical Data Sheet; information about this can be accessed at any time on our website: www.suedwest.de.

STATUS: 2026/SEPTEMBER/CS