



TECHNICAL DATA SHEET

30005 FIXATIV

AREA OF APPLICATION

Mineral primer and thinning agent for silicate paints. For initial fixing and/or priming on highly absorbent mineral substrates mixed with water at a ratio of 1:1. For use in both interiors and exteriors.

PROPERTIES

- Free of substances that contribute to "black dust" on walls
- Highly consolidating
- mineral
- Solvent-free
- water-dilutable
- Deep penetrating
- Absorbency-regulating
- Highly water vapour permeable
- Silicifies with mineral substrates

COLOUR SHADE: 0901 colourless

CONTAINER: 5 l, 10 l

COVERAGE: 150 – 600 ml/m² per coating, depending on absorption capacity

DENSITY: approx. 1.0 g/m³

APPLICATION

GENERAL RULES:

The substrate must be prepared and the coating work performed in accordance with the state of the art. All coatings and preliminary work should always be geared towards the project and the requirements it is exposed to. Please also observe the current BFS data sheets, published by the German Federal Committee for Paints and the Protection of Objects. Also see German construction contract procedures (VOB), Part C, DIN 18363, Paragraph 3 "Painting and coating work".

Treating/removing layers of paint by sanding, welding, burning off, etc. can cause harmful dust and/or vapours. Only carry out work in well-ventilated areas. Use appropriate breathing apparatus/protective equipment, if necessary.

All substrates must be clean, dry, load-bearing, and free from release agents. Substrates must be checked in terms of their load-bearing capacity and suitability for subsequent coatings. If necessary, create a test surface and test the adhesion.

SUBSTRATE

Concrete, cellular concrete, cement render, lime and lime-cement plaster, silicate plaster, weathered silicate coatings.

SUBSTRATE PREPARATION:

Prior to coating work, new and existing render and plaster must be at least 28 days old, cured, and dry (rule of thumb: 1 day drying time per mm of thickness). Remove all traces of non-load bearing existing coatings. Cleaning according to the type, composition, and soiling of the substrate, e.g. using a jet wash. Cleaning must expose the pores so that SÜDWEST Fixativ can penetrate deep into the substrate.

APPLICATION

By painting or brushing; mix SÜDWEST Fixativ for priming 1:1 with water and apply saturating the substrate; remove excess product from the surface.

Warning: SÜDWEST Fixativ must not form a layer.

APPLICATION TEMPERATURE:

Do not apply or leave to dry at an air or substrate temperature of less than +5°C. Do not apply in direct sunlight.

THINNING AGENT/TOOL CLEANING:

Dilute 1:1 with water. Clean tools with water.

DRYING

(+20°C / 65 % rel. humidity)

Can be painted: after 12 h

SPECIAL INFORMATION

Do not use on substrates containing gypsum, e.g. gypsum plaster, anhydrite plaster, etc., or on substrates with efflorescence. All substrates must have a high absorption capacity.

Fixativ must not be used for priming undiluted and must not form a layer on the coating substrate. Substrates that are sensitive to alkalines, e.g. glass, ceramics, metal, etc., must be covered carefully for protection prior to product application. Wash off splashes immediately with water.

caution:

SÜDWEST Fixativ reacts alkaline. Protect eyes and skin from splashes during application. Rinse splashes immediately with clean water.

EC DIRECTIVE 2004/42/CE

The Fixativ product falls below the maximum VOC value of product category h (30 g/l) and is therefore VOC-compliant.

VDL DECLARATION

Mineral binder, polymer dispersion, water, aliphatics, stabilisers

GISCODE BSW20

GENERAL SAFETY ADVICE

Good ventilation must be ensured while paints and varnishes are being applied and are drying. Keep away from food, drink, and animal feed. Avoid contact with skin and eyes. Do not breathe in dust during sanding work. Keep out of reach of children. Do not allow to enter ground water, bodies of water, or the sewer system in undiluted or large quantities.

Further information and the current SDS are available at www.suedwest.de

STORAGE

Close opened containers so that they are airtight after use. Store in cool but frost-free conditions.

DISPOSAL

Only recycle empty containers. The current legal requirements regarding disposal must be observed.

TECHNICAL CONSULTATION

Our sales force will be happy to answer any questions which have not been covered by this Technical Data Sheet. Our technical customer service team at the factory is also available to answer any detailed queries you may have. (06324/709-0)

DISCLAIMER

We are committed to taking the utmost care. However, we are only able to provide general information based on our own experiences, developments, and investigations, and these naturally cannot take the individual conditions of a

project (substrates, weather conditions, other conditions) into account. The applicator is therefore obliged to maintain their knowledge in accordance with the state of the art and act responsibly. Our employees are available to provide specific advice and will be happy to do so. We accept no responsibility for the use of the product in combination with other products. The data provided in this Technical Data Sheet does not constitute binding information or liability.

Furthermore, suspension or the appearance of a subsequent edition will invalidate this Technical Data Sheet; information about this can be accessed at any time on our website: www.suedwest.de.

STATUS: 2024/MARCH/CS