



TECHNICAL DATA SHEET

30845 PATINA-LASUR

AREA OF APPLICATION

Patina-Lasur is a thin-layer lasure with pearl lustre pigments for non-dimensionally-stable timber elements in exteriors. The attractive special pigmentation lends the product the appearance of old wood.

Typical areas of application: fences, clapboards, tongue and groove boarding, balconies, timber facades.

PROPERTIES

- Attractive old wood character
- Good depth of penetration
- Minimum film formation
- Open-pored
- Even weathering (no spalling)
- Streak-free, seamless application
- Good UV protection due to reflecting pigments
- Free from aromatic compounds (VdL-RL-01)
- With preventive film protection against algae and fungi

COLOUR SHADE: PAT0600 emerald, PAT0700 silver, PAT0701 titanium, PAT0100 gold, PAT0200 copper, PAT0800 driftwood

CONTAINER: 750 ml, 2.5 l, 5 l

COVERAGE: 50 – 80 ml/m²

Actual coverage will depend on the specific project and is heavily influenced by factors including surface appearance and absorption capacity. Exact consumption values can be determined by applying a test coat.

GLOSS LEVEL: silk gloss

AREA OF APPLICATION

GENERAL RULES:

The substrate must be prepared and the coating work performed in accordance

with the state of the art. All coatings and preliminary work should always be geared towards the project and the requirements it is exposed to. Please also observe the current BFS data sheets, published by the German Federal Committee for Paints and the Protection of Objects. Also see German construction contract procedures (VOB), Part C, DIN 18363, Paragraph 3 "Painting and coating work".

Treating/removing layers of paint by sanding, welding, burning off, etc. can cause harmful dust and/or vapours. Only carry out work in well-ventilated areas. Use appropriate breathing apparatus/protective equipment, if necessary.

All substrates must be clean, dry, load-bearing, and free from release agents. Substrates must be checked in terms of their load-bearing capacity and suitability for subsequent coatings. If necessary, create a test surface and test the adhesion by means of a cross cut and/or mesh tape tear-off. For coating build-ups, carry out intermediate sanding in between the individual coatings.

SUBSTRATE

SUBSTRATE PREPARATION:

Sand grey and weathered wooden areas down to the load-bearing substrate. Clean and sand existing load-bearing paint coats. Round off sharp wooden edges. Ensure adequate drainage inclinations on horizontal surfaces. Moisture content in the wood should not exceed 13 +/- 2 % for dimensionally stable building elements; it should not exceed 18 % for non-dimensionally-stable building elements. The drier the substrate, the greater the depth of penetration, improving the protective function and service life of subsequent paint coats. Wash

tropical woods with constituents that delay the drying time with a cellulose thinner and apply a test coat.

Sand and thoroughly clean new smooth or planed wooden surfaces. Remove emerging resin/wood constituents. Apply a priming coat and an intermediate coat to all sides of new wooden building elements.

For exterior applications, it is recommended to pretreat untreated or exposed timbers that are susceptible to fungus with SÜDWEST Holz-Imprägnier-Grund LH. Observe Technical Data Sheet, DIN 68800 Part 3, and BFS data sheet 18.

APPLICATION

Stir SÜDWEST Patina-Lasur before use. Application by brush will achieve the best surface finish. Paint on 2–3 undiluted coats depending on the substrate. SÜDWEST Patina-Lasur is designed ready-to-use. Do not apply or leave to dry at an air or project temperature of less than +5°C or more than +30°C. Only suitable for dimensionally stable building elements such as windows and doors.

THINNING AGENT:

Apply undiluted.

TOOL CLEANING:

Clean with alkyd resin lacquer thinner after use. Dispose of cleaning agents properly.

DRYING

(+20°C / 60 % rel. humidity, 100 µm wet-layer thickness)

Dust-dry: approx. 3 h

Tack-free: approx. 4 h

Over-coatable: approx. 12 h

Higher layer thicknesses and/or lower temperatures delay the drying times.

SPECIAL INFORMATION

Do not paint onto heated substrates in direct sunlight and/or onto wooden substrates that will be exposed to direct sunlight within 2 to 3 hours of application. Drying times may be delayed for first coatings on timber that is rich in active substances. Apply a second coat only after drying.

EC DIRECTIVE 2004/42/CE

The Patina-Lasur product falls below the maximum VOC value of product category f (700 g/l) and is therefore VOC-compliant.

BIOCIDAL PRODUCTS REGULATION

Contains 3-iodo-2-propinyl butyl carbamate (IPBC) as an active ingredient for protection of the coating in accordance with the Biocidal Products Regulation (528/2012), Article 58 (3).

VDL DECLARATION

Alkyd resins (mineral and/or organic pigments, depending on the colour shade), aliphatic hydrocarbon mixtures, glycol ether, rheology additives, light stabilisers, driers, antioxidants, film protection based on 3-iodo-2-propinyl butyl carbamate (IPBC)

GISCODE BSL40

GENERAL SAFETY ADVICE

Good ventilation must be ensured while paints and varnishes are being applied and are drying. Keep away from food, drink, and animal feed. Avoid contact with skin and eyes. Do not breathe in dust during sanding work. Only use in well-ventilated areas. Do not eat, drink, smoke, or inhale snuff tobacco during work. Keep out of reach of children. Do not allow to enter the sewer system or bodies of water. If rivers, lakes, or drains become contaminated, inform the relevant authorities in accordance with the local laws. Further information and the current SDS are available at www.suedwest.de.

STORAGE

Store in cool but frost-free conditions, seal opened containers tightly. The legal requirements governing the pollution of ground water and surface water, as well as air, must be met when storing and applying wood preservatives. Do not expose to temperatures above +30°C for prolonged periods and store in frost-free conditions.

DISPOSAL

Only return empty containers for recycling. Dispose of containers with residues at the responsible hazardous waste centre. Dispose of dried paint brushes and rollers with residual waste. Do not dispose of paint or rinse painting tools in sinks or drains.

TECHNICAL CONSULTATION

Our sales force will be happy to answer any questions which have not been covered by this Technical Data Sheet. Our technical customer service team at the factory is also available to answer any detailed queries you may have. (06324/709-0)

DISCLAIMER

We are committed to taking the utmost care. However, we are only able to provide general information based on our own experiences, developments, and investigations, and these naturally cannot take the individual conditions of a project (substrates, weather conditions, other conditions) into account. The applicator is therefore obliged to maintain their knowledge in accordance with the state of the art and act responsibly. Our employees are available to provide specific advice and will be happy to do so. We accept no responsibility for the use of the product in combination with other products. The data provided in this Technical Data Sheet does not constitute binding information or liability. Furthermore, suspension or the appearance of a subsequent edition will invalidate this Technical Data Sheet; information about this can be accessed at any time on our website: www.suedwest.de.

STATUS: 2026/MARCH/KM