



TECHNICAL DATA SHEET

30485 SCHIMMEL-FRESSER

AREA OF APPLICATION

Disinfection; spray for removing mould, fungi, mould stains, algae, and moss. For mould-infested substrates including emulsion paint, washable wallpaper, tiles, joints, plaster, and stone. Do not use together with and do not mix with acids, toilet cleaning agents, or strippers. Dangerous vapours (chlorine) may be released.

WARNING: Schimmel-Fresser contains biocides. Use biocides safely. Always read the label and product information before use.

Product type 2: Disinfectant and algicide.

BAUA Reg-No. N-58028
Switzerland: Federal authorisation number: CHZN4136

Active ingredients: Sodium hypochlorite: 43.00 g/kg

Shelf life: We guarantee the biocidal effect of the product until the expiration date (container imprint: EXP month/year)

PROPERTIES

- Removes mould, moss, algae, bacteria, and fungal attack
- Regular use will protect against fungal attack
- For killing off and bleaching fungi, mould stains, moss, algae, and bacteria
- Cleans and disinfects
- Bleaching effect

COLOUR SHADE: colourless

CONTAINER: 250 ml, 500 ml

COVERAGE: approx. 100 ml/m²

ACTIVE INGREDIENT: sodium hypochlorite solution 47.00 g/kg

APPLICATION

Adjust the spray head prior to spraying (see the symbol). Do not remove mould prior to spraying. Only remove coarse soiling such as moss prior to spraying. Spray the product onto visibly infested surfaces from a distance of approx. 5–10 cm. Spray again if areas that are still dark remain visible after approx. 30 minutes. Use a brush or a vacuum cleaner to remove surface-dry residue. Wash treated surfaces with clean water after applying the product.

Wash off permanently elastic joints & tile joints after 10 minutes. Unscrew the screw head and rinse with water after use. Seal the container again.

SPECIAL INFORMATION

Warning!

The bleaching effect can cause colour changes in textiles and timber. Be careful not to get the product on your clothes. Prior to application, check the colour-fastness of colour-sensitive substrates (e.g. wallpaper) in an inconspicuous place. Pre-wet highly absorbent substrates with water to stop SÜDWEST Schimmel-Fresser penetrating the substrate and enable residue to be washed off the surface with water. We recommend applying SÜDWEST FungiStop as a preventive measure before repainting ceilings and wall areas.

EC DIRECTIVE 2004/42/CE

The Schimmel-Fresser product is out of scope of the VOC Directive.

GENERAL SAFETY ADVICE

Good ventilation must be ensured while paints and varnishes are being applied and are drying. Keep away from food, drink, and animal feed. Avoid contact with skin and eyes. Do not breathe in dust during sanding work. Keep out of reach of children. Wear suitable protective gloves and safety glasses/face protection when working with this product. Do not allow to enter ground water, bodies of water, or the sewer system in undiluted or large quantities.

Further information and the current SDS are available at www.suedwest.de

SAFETY INFORMATION:

The product is alkaline. The product must only be used as described in the instructions for use and only in the permitted application ranges.

HAZARD WARNINGS: HAZARD STATEMENTS



Danger

H290: May be corrosive to metals. H315: Causes skin irritation. H318: Causes serious damage to the eyes. H410: Very toxic to aquatic life with long lasting effects. P101: If medical advice is needed, have product container or label at hand. P102: Keep out of the reach of children. P260: Do not breathe mist. P264: Wash skin thoroughly after handling. P271: Use only outdoors and in a well-ventilated area. P305 + P351 + P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove any contact lenses if possible. Continue rinsing. P310: Immediately call a POISON CENTER/doctor.

P501: Dispose of contents/container to authorised waste disposal company or municipal collection point. Warning. Do not use together with other products, as dangerous gases (chlorine) may be released.

GERMAN FEDERAL INSTITUTE
FOR OCCUPATIONAL SAFETY
AND HEALTH REG. NO.:
N-12237

STORAGE

Store in cool and dark conditions. Seal opened containers tightly. Do not expose to temperatures above 30°C for prolonged periods. Keep away from frost.

DISPOSAL

Rinse out the container with water or take to a local disposal centre. Only recycle empty containers.

TECHNICAL CONSULTATION

Our sales force will be happy to answer any questions which have not been covered by this Technical Data Sheet. Our technical customer service team at the factory is also available to answer any detailed queries you may have. (06324/709-0)

DISCLAIMER

We are committed to taking the utmost care. However, we are only able to provide general information based on our own experiences, developments, and investigations, and these naturally cannot take the individual conditions of a project (substrates, weather conditions,

other conditions) into account. The applicator is therefore obliged to maintain their knowledge in accordance with the state of the art and act responsibly. Our employees are available to provide specific advice and will be happy to do so. We accept no responsibility for the use of the product in combination with other products. The data provided in this Technical Data Sheet does not constitute binding information or liability.

Furthermore, suspension or the appearance of a subsequent edition will invalidate this Technical Data Sheet; information about this can be accessed at any time on our website: www.suedwest.de.

STATUS: 2016/FEBRUARY/KM